



ENVIRONMENTAL PRODUCT DECLARATION

# SINAMICS S120 Booksize

## Smart Line Module 36 kW

Type II according to ISO 14021 including life cycle impact assessment (LCIA)



# SIEMENS

# General information

This environmental product declaration (EPD) is based on the international standard ISO 14021 (“Environmental labels and declarations – Self declared environmental claims – Type II environmental labelling”). The data in this EPD has been evaluated on a full-scale life cycle assessment (LCA) study according to ISO 14040/44, taking into account the product category rules (PCR) for electronic and electrotechnical products and systems defined in EN 50693. The use phase for line module is described according to the reference scenario in the Table 1 of the Appendix.

Siemens is dedicated to an environmentally conscious design of its products in line with IEC 62430 and has implemented an integrated management system according to ISO 9001, ISO 14001 and ISO 45001.


<b>Products</b>	<b>SINAMICS S120 Smart Line Modules, power range 5 to 55 kW at 380 ... 480 V 3AC</b>
<b>Represented by the reference product</b>	6SL3130-6TE23-6AA3, 36 kW, 3 AC 380 ... 480V
<b>Product Description</b>	The SINAMICS S120 Smart Line Module is one of the components of SINAMICS S120 Booksize drive system. The Smart Line Module is a non-regulated infeed/regenerative feedback unit. The Smart Line Module supplies the Motor Module with a non-regulated DC voltage at the DC output. Input: 380-480V, 50/60HZ. Output: DC 600V, 60A, 36 kW. Internal air cooling, energy recovery capability, include DRIVE-CLiQ cable.
<b>Functional Unit</b>	A device that converts 380-480V 3AC power into DC power and feeds to the S120 Booksize Motor Module. Calculation of the environmental impacts is based on 15 years of product service lifetime. This value cannot be equated with the minimum, average or individual life time. <sup>1</sup>

<sup>1</sup> The lifetime value used for calculation is a reference value and does not equate with the minimum, average or real life time.

# Material composition

The following chart outlines the overall material composition of the calculated reference product without packaging. Product weight of 10.61 kg adds up with packaging weight of 1.22 kg to a total weight of 11.83 kg. Packaging consists of: Corrugated box (average composition), PE film, Graphic paper, EPS-Foam .

## Product Weight 10.61 kg



# Substance assessment

At Siemens, we are committed to the development and production of environmentally sound and sustainably produced equipment. This includes avoiding hazardous substances in our products without compromising their benefits for our customers. Please visit the following website to learn more about how we comply with product-related environmental regulations like RoHS, REACH, WEEE and others: [Product Related Environmental Protection](#)

## Life cycle stages and reference scenarios

Scenarios		
 <p><b>Manufacturing</b></p> <p>This stage covers the extraction of natural resources, production of raw materials, manufacturing, packaging, and transportation.</p>	 <p><b>Distribution and Operation</b></p> <p>This stage covers the product's distribution, installation, use, and maintenance. Different operating conditions can lead to deviations from the reference scenario.</p>	 <p><b>End-of-Life</b></p> <p>This stage covers the disassembly or shredding and material recycling of all recyclable materials, as well as energy recovery, thermal treatment and the disposal of all other materials.</p>
<p><b>Energy model used:</b> Germany (renewable mix), Germany (standard mix), Germany (Thermal energy from biogas)</p> <p><b>Transportation model:</b> Road Truck (7.5 t-12 t) 1000 km</p>	<p><b>Energy model used:</b> Europe (standard mix);</p> <p><b>Distribution scenario:</b> Truck (7.5 t-12 t) 3500 km</p> <p><b>Use Scenario:</b> Definition of the operational points are: OP1: 61% of time at 100% Infeed Load OP2: 19% of time at 50% Infeed Load OP3: 8% of time at 25% Infeed Load OP4: 12% of time at 0% Infeed Load Lifetime 15 years and 5000h/year</p>	<p><b>Energy model used:</b> EMEA</p> <p><b>End-of-Life methodology:</b> Avoided burden (net-scrap calculation)</p>

# Key environmental performance indicators

The following impact categories characterize the product's environmental footprint. They have been calculated with LCIA methodology EN15804+A2 (EF 3.1); LCA tool: Green Digital Twin Version 4.0, Database: One Siemens LCA Database (based on Sphera MLC CUP 2024.1).


To ensure the high quality and completeness of the LCA results, primary data have been used whenever possible. Datasets for resources, such as electrical energy or natural gas, are chosen from the region where the device is produced and assembled. If primary data are not available, datasets reflecting state-of-the-art manufacturing technology are considered.

For products belonging to the same homogeneous product family range the following extrapolation criteria (Appendix) can be used to module their climate change impact in kg CO<sub>2</sub> eq. The rest of the listed impacts will be determined in the following version of the EPD.

Impact Category	Unit	Total	Manufacturing	Distribution	Operation	End of life
Climate change – total	kg CO <sub>2</sub> eq	7.06E+3	1.70E+2	1.13E+1	6.91E+3	-3.52E+1
Climate change – fossil	kg CO <sub>2</sub> eq	6.97E+3	1.42E+2	1.11E+1	6.85E+3	-3.51E+1
Climate change – biogenic	kg CO <sub>2</sub> eq	8.99E+1	2.82E+1	3.83E-2	6.17E+1	1.61E-3
Climate Change, land use and land use change	kg CO <sub>2</sub> eq	1.33E+0	2.07E-1	1.62E-1	1.04E+0	-7.93E-2
Ozone depletion	kg CFC-11 eq	1.80E-7	2.50E-8	1.50E-12	1.55E-7	-2.04E-10
Acidification	Mole of H+ eq	1.37E+1	9.93E-1	1.49E-2	1.32E+1	-5.06E-1
Eutrophication, freshwater	kg P eq	2.95E-2	9.19E-4	4.21E-5	2.86E-2	-4.59E-5
Eutrophication, marine	kg N eq	3.42E+0	1.51E-1	5.60E-3	3.30E+0	-3.80E-2
Eutrophication, terrestrial	Mole of N eq	3.58E+1	1.63E+0	6.64E-2	3.45E+1	-4.11E-1
Photochemical ozone formation, human health	kg NMVOC eq	9.07E+0	4.64E-1	1.47E-2	8.72E+0	-1.30E-1
Resource use, mineral and metals	kg Sb eq	3.83E-2	4.33E-2	8.42E-7	1.28E-3	-6.23E-3
Resource use, fossils	MJ	1.45E+5	2.26E+3	1.27E+2	1.43E+5	-4.46E+2
Water use	m <sup>3</sup> world eq deprived water	1.89E+3	3.37E+1	2.73E-1	1.87E+3	-9.13E+0
Particulate matter	Disease incidences	1.19E-4	1.34E-5	1.63E-7	1.10E-4	-4.51E-6
Ionising radiation, human health	kBq U235 eq	3.77E+3	1.07E+1	3.52E-2	3.77E+3	-3.52E+0
Ecotoxicity, freshwater – total	CTUe	4.26E+4	1.09E+3	9.45E+1	4.16E+4	-1.29E+2
Human toxicity, cancer – total	CTUh	2.83E-6	5.06E-7	1.92E-9	2.33E-6	-1.22E-8
Human toxicity, non-cancer – total	CTUh	3.68E-5	1.37E-6	8.56E-8	3.58E-5	-4.46E-7
Land Use	dimensionless (pt)	6.17E+4	9.51E+2	6.26E+1	6.07E+4	-3.19E+1

# Climate change

This chart shows the overall impact of the product on climate change – total. The operations phase is the lifecycle phase with the biggest overall impact. Different operating conditions can lead to deviations from the reference scenario. The distribution stage of the reference product is not shown separately in the chart due to its relatively small contribution to climate change and its impact is placed under the operation bar.



## End-of-Life results

The end-of-life stage considers the recyclability rates of metal, plastics contents and minimum disposal rates according to the guidelines IEC TR 62635:2012 for end-of-life information provided by manufacturers and recyclers and for recyclability rate calculation of electrical and electronic equipment.



It leads to:

- **product recyclability of up to 73%** mainly due to metal content
- **energy recoverability of up to 13%** from plastic materials
- **minimum disposal rate of 14%**

The exact final values depend on the used recycling process and add up to 100%.

**Note:** The device should not be disposed of as unsorted municipal waste. Special treatment for specific components may be mandated by law or recommended for environmental reasons. Observe all local and applicable laws.

# Appendix

For other MLFBs covered by this EPD under SINAMICS S120 Booksize system Smart Line Modules, the climate change impact (CC) in kg CO<sub>2</sub> eq. of the manufacturing, the operation phase and the end of life phase are listed in the Table 1.

For **the operation phase**, the climate change in kgCO<sub>2</sub>eq was derived for 400V and rated power PR (LO) in kW for European standard energy mix, lifetime of 15 years, annual operation 5000h/year and 4 operational points. The climate change values for operation phase are described in Tab. 1.

Definition of the operational points are:

OP1: 61% of time at 100% Infeed Load

OP2: 19% of time at 50% Infeed Load

OP3: 8% of time at 25% Infeed Load

OP4: 12% of time at 0% Infeed Load

*Tab.1 Climate change results of SINAMICS S120 Smart Line Modules*

MLFB	Voltage	Power Rate	Manufact-uring Phase	Operatio-n Phase	End-of-Life Phase
/	v	kW	kg CO <sub>2</sub> eq	kg CO <sub>2</sub> eq	kg CO <sub>2</sub> eq
6SL3130-6AE15-0AB1	380-480	5	80.8	1348	-13.5
6SL3130-6AE21-0AB1	380-480	10	82.4	2411	-13.9
6SL3130-6TE23-6AA3	380-480	36	170	6912	-35.2
6SL3130-6TE25-5AA3	380-480	55	213	11331	-59.6

# Legal Disclaimer

This Environmental Product Declaration (EPD) is for information purposes only. It is based upon the standards mentioned above. This EPD does not warrant or guarantee the composition of a product or that the product will retain a particular composition for a particular period. Therefore, all warranties, representations, conditions, and all other terms of any kind whatsoever implied by statute or common law are – to the fullest extent permitted by applicable law – excluded.

**Siemens therefore does not assume any liability for any error or for any consequence which may arise from the use of this information to the maximum extent under the law.**

Please be aware that the data of this EPD cannot be compared with data calculated based upon product category rules (PCRs) other than the standards mentioned above. The values given are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

**Published by**

Digital Industries

Motion Control

Frauenauracher Str. 80

91056 Erlangen

Germany

Subject to changes and errors.

The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. In particular no assurance is given that those descriptions and performance features stand under warranty or guarantee in sense of any liability for any error or for any consequence which may arise from the use of this information to the maximum extent under the law. The requested performance features are binding only when they are expressly agreed upon in the concluded contract.

All product designations may be trademarks or product names of Siemens AG or other companies whose use by third parties for their own purposes could violate the rights of the owners.

© 2025 by Siemens