



Figure similar

SIPLUS ET 200SP AI 8xRTD/TC HF T1 rail based on 6ES7134-6JF00-0CA1 with conformal coating, -40...+60 °C, OT2 with ST1/2 (+70 °C für 10 minutes), analog input module, suitable for BU type A0, A1, color code CC00, channel diagnostics, 16-bit, +/-0.1%

General information	
Product type designation	AI 8xRTD/TC 2-wire HF
Firmware version	
• FW update possible	Yes
based on	6ES7134-6JF00-0CA1
usable BaseUnits	BU type A0, A1
Color code for module-specific color-coded label	CC00
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
• Measuring range scalable	Yes
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	see entry ID: 109746275
Operating mode	
• Oversampling	No
• MSI	No
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	35 mA
Power loss	
Power loss, typ.	0.75 W
Address area	
Address space per module	
• Address space per module, max.	16 byte; + 1 byte for QI information
Hardware configuration	
Automatic encoding	
• Mechanical coding element	Yes
• Type of mechanical coding element	Type A
Selection of BaseUnit for connection variants	
• 2-wire connection	BU type A0, A1
Analog inputs	

Number of analog inputs	8
permissible input voltage for voltage input (destruction limit), max.	30 V
Constant measurement current for resistance-type transmitter, typ.	2 mA
Cycle time (all channels), min.	Sum of the basic conversion times and additional processing times (depending on the parameterization of the active channels)
Technical unit for temperature measurement adjustable	Yes; °C/°F/K
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> ● -1 V to +1 V <ul style="list-style-type: none"> — Input resistance (-1 V to +1 V) ● -250 mV to +250 mV <ul style="list-style-type: none"> — Input resistance (-250 mV to +250 mV) ● -50 mV to +50 mV <ul style="list-style-type: none"> — Input resistance (-50 mV to +50 mV) ● -80 mV to +80 mV <ul style="list-style-type: none"> — Input resistance (-80 mV to +80 mV) 	<ul style="list-style-type: none"> Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ
Input ranges (rated values), thermocouples	
<ul style="list-style-type: none"> ● type B <ul style="list-style-type: none"> — Input resistance (Type B) ● type C <ul style="list-style-type: none"> — Input resistance (Type C) ● Type E <ul style="list-style-type: none"> — Input resistance (Type E) ● Type J <ul style="list-style-type: none"> — Input resistance (type J) ● Type K <ul style="list-style-type: none"> — Input resistance (Type K) ● Type L <ul style="list-style-type: none"> — Input resistance (Type L) ● Type N <ul style="list-style-type: none"> — Input resistance (Type N) ● Type R <ul style="list-style-type: none"> — Input resistance (Type R) ● Type S <ul style="list-style-type: none"> — Input resistance (Type S) ● Type T <ul style="list-style-type: none"> — Input resistance (Type T) ● Type U <ul style="list-style-type: none"> — Input resistance (Type U) ● Type TXK/TXK(L) to GOST <ul style="list-style-type: none"> — Input resistance (Type TXK/TXK(L) to GOST) 	<ul style="list-style-type: none"> Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ
Input ranges (rated values), resistance thermometer	
<ul style="list-style-type: none"> ● Ni 100 <ul style="list-style-type: none"> — Input resistance (Ni 100) ● Ni 1000 <ul style="list-style-type: none"> — Input resistance (Ni 1000) ● LG-Ni 1000 <ul style="list-style-type: none"> — Input resistance (LG-Ni 1000) ● Ni 120 <ul style="list-style-type: none"> — Input resistance (Ni 120) ● Ni 200 <ul style="list-style-type: none"> — Input resistance (Ni 200) ● Ni 500 <ul style="list-style-type: none"> — Input resistance (Ni 500) ● Pt 100 <ul style="list-style-type: none"> — Input resistance (Pt 100) ● Pt 1000 <ul style="list-style-type: none"> — Input resistance (Pt 1000) ● Pt 200 	<ul style="list-style-type: none"> Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign 1 MΩ Yes; 16 bit incl. sign

— Input resistance (Pt 200)	1 MΩ
● Pt 500	Yes; 16 bit incl. sign
— Input resistance (Pt 500)	1 MΩ
Input ranges (rated values), resistors	
● 0 to 150 ohms	Yes; 15 bit
— Input resistance (0 to 150 ohms)	1 MΩ
● 0 to 300 ohms	Yes; 15 bit
— Input resistance (0 to 300 ohms)	1 MΩ
● 0 to 600 ohms	Yes; 15 bit
— Input resistance (0 to 600 ohms)	1 MΩ
● 0 to 3000 ohms	Yes; 15 bit
— Input resistance (0 to 3000 ohms)	1 MΩ
● 0 to 6000 ohms	Yes; 15 bit
— Input resistance (0 to 6000 ohms)	1 MΩ
● PTC	Yes; 15 bit
— Input resistance (PTC)	1 MΩ
Thermocouple (TC)	
Temperature compensation	
— Parameterizable	Yes
— Reference channel of the module	Yes
— internal comparison point	Yes; with BaseUnit type A1
— Reference channel of the group	Yes
— Number of reference channel groups	4; Group 0 to 3
— fixed reference temperature	Yes
Cable length	
● shielded, max.	200 m; 50 m with thermocouples
Analog value generation for the inputs	
Measurement principle	integrating (Sigma-Delta)
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	16 bit
● Integration time, parameterizable	Yes
● Basic conversion time, including integration time (ms)	
— additional processing time for wire-break check	2 ms; In the ranges resistance thermometers, resistors and thermocouples
● Interference voltage suppression for interference frequency f1 in Hz	16.6 / 50 / 60 Hz
● Conversion time (per channel)	180 / 60 / 50 ms
Smoothing of measured values	
● Number of smoothing levels	4; None; 4/8/16 times
● parameterizable	Yes
Encoder	
Connection of signal encoders	
● for voltage measurement	Yes
● for resistance measurement with two-wire connection	Yes
● for resistance measurement with three-wire connection	No
● for resistance measurement with four-wire connection	No
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.01 %; ±0.1 % for resistance thermometers and resistance
Temperature error (relative to input range), (+/-)	0.0009 %/K; ±0.005 % / K at thermocouple
Crosstalk between the inputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %
Operational error limit in overall temperature range	
● Voltage, relative to input range, (+/-)	0.2 %
● Resistance, relative to input range, (+/-)	0.2 %
Basic error limit (operational limit at 25 °C)	
● Voltage, relative to input range, (+/-)	0.05 %
● Resistance, relative to input range, (+/-)	0.05 %
Interference voltage suppression for $f = n \times (f1 \pm 1 \%)$, f1 = interference frequency	
● Series mode interference (peak value of interference < rated value of input range), min.	70 dB

<ul style="list-style-type: none"> • Common mode voltage, max. 	10 V
<ul style="list-style-type: none"> • Common mode interference, min. 	90 dB
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm 	Yes
<ul style="list-style-type: none"> • Limit value alarm 	Yes; two upper and two lower limit values in each case
Diagnoses	
<ul style="list-style-type: none"> • Monitoring the supply voltage 	Yes
<ul style="list-style-type: none"> • Wire break 	Yes; channel by channel
<ul style="list-style-type: none"> • Group error 	Yes
<ul style="list-style-type: none"> • Overflow/Underflow 	Yes; channel by channel
Diagnostics indication LED	
<ul style="list-style-type: none"> • Monitoring of the supply voltage (PWR-LED) 	Yes; green PWR LED
<ul style="list-style-type: none"> • Channel status display 	Yes; green LED
<ul style="list-style-type: none"> • for channel diagnostics 	Yes; red LED
<ul style="list-style-type: none"> • for module diagnostics 	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
<ul style="list-style-type: none"> • between the channels 	No
<ul style="list-style-type: none"> • between the channels and backplane bus 	Yes
<ul style="list-style-type: none"> • between the channels and the power supply of the electronics 	Yes
Permissible potential difference	
between the inputs (UCM)	10 V DC
Isolation	
Isolation tested with	750 V DC (type test) and according to EN 50155 (routine test)
Standards, approvals, certificates	
Railway application	
<ul style="list-style-type: none"> • EN 50121-3-2 	Yes; EMC for rail vehicles
<ul style="list-style-type: none"> • EN 50121-4 	Yes; EMC for signal and telecommunications systems
<ul style="list-style-type: none"> • EN 50121-5 	Yes; EMC for fixed installations and railway power supply equipment
<ul style="list-style-type: none"> • EN 50124-1 	Yes; Railway applications - overvoltage category OV2; pollution degree PD2; rated surge voltage UNi = 0.5 kV; UNm = 24 V DC
<ul style="list-style-type: none"> • EN 50125-1 	Yes; Rail vehicles - see ambient conditions
<ul style="list-style-type: none"> • EN 50125-2 	Yes; Stationary electrical equipment - see ambient conditions
<ul style="list-style-type: none"> • EN 50125-3 	Yes; Signal and telecommunications systems - see ambient conditions; vibrations and shocks: Application point outside of tracks (1 m to 3 m away from track)
<ul style="list-style-type: none"> • EN 50155 	Yes; Rail vehicles - temperature class OT2, ST1/ST2, horizontal mounting position
<ul style="list-style-type: none"> • EN 61373 	Yes; Rail vehicles - vibrations and shocks: Category 1 Class A/B
<ul style="list-style-type: none"> • Fire protection acc. to EN 45545-2 	Yes; For proof of conformity, see Service & Support
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • horizontal installation, min. 	-40 °C; = Tmin (incl. condensation/frost)
<ul style="list-style-type: none"> • horizontal installation, max. 	60 °C; = Tmax; +70 °C for 10 min (OT2, ST1/ST2 acc. to EN 50155); +70 °C continuously with spacing modules (6AG2193-6BN00-4BA0) or configured slots to the left and right of the module (OT4, ST0 acc. to EN 50155)
<ul style="list-style-type: none"> • vertical installation, min. 	-40 °C; = Tmin
<ul style="list-style-type: none"> • vertical installation, max. 	50 °C; = Tmax
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> • Installation altitude above sea level, max. 	2 000 m
<ul style="list-style-type: none"> • Ambient air temperature-barometric pressure-altitude 	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Relative humidity	
<ul style="list-style-type: none"> • With condensation, tested in accordance with IEC 60068-2-38, max. 	100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air

Use in stationary industrial systems		
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request	
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *	
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *	
— Against mechanical environmental conditions acc. to EN 60721-3-3	Yes; Class 3M8 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)	
Use on land craft, rail vehicles and special-purpose vehicles		
— to biologically active substances according to EN 60721-3-5	Yes; Class 5B2 mold, fungus and dry rot spores (with the exception of fauna); Class 5B3 on request	
— to chemically active substances according to EN 60721-3-5	Yes; Class 5C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *	
— to mechanically active substances according to EN 60721-3-5	Yes; Class 5S3 incl. sand, dust; *	
— Against mechanical environmental conditions acc. to EN 60721-3-5	Yes; Class 5M2 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)	
— against mechanical environmental conditions in agriculture acc. to ISO 15003	Yes; level 1 (Location LE) using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)	
Usage in industrial process technology		
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)	
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)	
Remark		
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!	
Conformal coating		
• Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high reliability	
• Protection against fouling acc. to EN 60664-3	Yes; Type 1 protection	
• Electronic equipment on rolling stock acc. to EN 50155	Yes; Class PC2 protective coating acc. to EN 50155:2017	
• Military testing according to MIL-I-46058C, Amendment 7	Yes; Discoloration of coating possible during service life	
• Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A	
Dimensions		
Width	15 mm	
Height	73 mm	
Depth	58 mm	
Weights		
Weight, approx.	32 g	
Other		
Note:	for use in railway applications, also observe the product information "SIPLUS extreme RAIL" A5E37661960A, Online Support article 109736776	
Classifications		
	Version	Classification
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596
IDEA	4	3562

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)[China RoHS](#)

General Product Approval

Railway

[China RoHS](#)[Confirmation](#)

last modified:

10/23/2025