



SIMATIC S7-1500, TM FAST Field Adaptable High-Speed Technology, programmable with Intel(R) Quartus(R) Prime software, 8xDI, 8xDQ, 4xDIQ 24 V, 8xRS485 DIQ, for extremely short response time of less than 1  $\mu$ s

General information	
Product type designation	TM FAST
Firmware version	V2.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	STEP 7 V17 with HSP or higher
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	GSDML V2.35
Installation type/mounting	
Rail mounting	Yes; S7-1500 mounting rail
Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>permissible range, lower limit (DC)</li> </ul>	19.2 V
<ul style="list-style-type: none"> <li>permissible range, upper limit (DC)</li> </ul>	28.8 V
<ul style="list-style-type: none"> <li>Reverse polarity protection</li> </ul>	Yes
Input current	
Current consumption, max.	100 mA; without load
Power	
Power consumption from the backplane bus	1.3 W
Power loss	
Power loss, typ.	4 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Inputs</li> </ul>	32 byte
<ul style="list-style-type: none"> <li>Outputs</li> </ul>	32 byte
Digital inputs	
Number of digital inputs	12; including 4 DIQs
Digital inputs, parameterizable	Yes
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Input voltage	
<ul style="list-style-type: none"> <li>Type of input voltage</li> </ul>	DC
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>for signal "0"</li> </ul>	-5 ... +5 V
<ul style="list-style-type: none"> <li>for signal "1"</li> </ul>	+11 to +30V
<ul style="list-style-type: none"> <li>permissible voltage at input, min.</li> </ul>	-5 V; -5 V continuous, -30 V brief reverse polarity protection
<ul style="list-style-type: none"> <li>permissible voltage at input, max.</li> </ul>	30 V

<b>Input current</b>	
• for signal "1", typ.	2.5 mA
<b>Input frequency</b>	
• For signal interface 24 V asymmetrical	200 kHz
• For signal interface RS 422 symmetrical	5 MHz
• For signal interface TTL (5 V) asymmetrical	1 MHz
<b>Input delay (for rated value of input voltage)</b>	
• Minimum pulse width for program reactions	application specific below 1 μs possible
for standard inputs	
— parameterizable	Yes; customer defined / 0.001 / 0.003 / 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms
<b>Cable length</b>	
• shielded, max.	100 m
<b>Digital outputs</b>	
Number of digital outputs	12; including 4 DIQs
Current-sinking	Yes; 8 push-pull outputs
Current-sourcing	Yes
Short-circuit protection	Yes; electronic/thermal
• Response threshold, typ.	0.2 A; for DQ; 0.9 A for DIQ
<b>Switching capacity of the outputs</b>	
• with resistive load, max.	0.1 A; 0.3 A for DIQs
<b>Load resistance range</b>	
• lower limit	240 Ω; 80 ohms for DIQs
• upper limit	12 kΩ
<b>Output voltage</b>	
• Type of output voltage	DC
• for signal "1", min.	23.2 V; L+ (-0.8 V), L+ (-1.3 V) for DIQs
<b>Output current</b>	
• for signal "1" rated value	0.1 A; 0.3 A for DIQs
• for signal "1" permissible range, max.	0.12 A; 0.36 A for DIQs
• for signal "1" minimum load current	2 mA
• for signal "0" residual current, max.	0.5 mA
<b>Output delay with resistive load</b>	
• "0" to "1", typ.	420 ns; for DQn
• "1" to "0", typ.	420 ns; for DQn
<b>Switching frequency</b>	
• with resistive load, max.	200 kHz; 1 kHz for DIQs
• For signal interface 24 V asymmetrical	200 kHz; 1 kHz for DIQs
• For signal interface RS 422 symmetrical	2 MHz
• For signal interface TTL (5 V) asymmetrical	200 kHz
<b>Cable length</b>	
• shielded, max.	30 m
<b>Encoder</b>	
<b>Interface types</b>	
• TTL 5 V	Yes; 8 channels (direction switchable)
• RS 422	Yes; 8 channels (direction switchable)
• Sourcing/sinking input	Yes
• Input characteristic curve in accordance with IEC 61131, type 3	Yes
<b>Isochronous mode</b>	
Bus cycle time (TDP), min.	250 μs
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
Substitute values connectable	Yes
<b>Alarms</b>	
• Diagnostic alarm	Yes
<b>Diagnoses</b>	
• Monitoring the supply voltage	Yes
• Wire break	Yes; for RS485/RS422/TTL Input

• Short-circuit	Yes; Thermal overload protection	
• Group error	Yes	
<b>Diagnostics indication LED</b>		
• RUN LED	Yes; green LED	
• ERROR LED	Yes; red LED	
• MAINT LED	Yes; Yellow LED	
• Monitoring of the supply voltage (PWR-LED)	Yes; green LED	
• Channel status display	Yes; green LED	
• for channel diagnostics	Yes; red LED	
<b>Potential separation</b>		
Potential separation channels		
• between the channels	No	
• between the channels and backplane bus	Yes	
• Between the channels and load voltage L+	No	
<b>Isolation</b>		
Isolation tested with	707 V DC (type test)	
<b>Security</b>		
signed firmware update	Yes	
<b>Ambient conditions</b>		
Ambient temperature during operation		
• horizontal installation, min.	-30 °C	
• horizontal installation, max.	60 °C	
• vertical installation, min.	-30 °C	
• vertical installation, max.	40 °C	
Altitude during operation relating to sea level		
• Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200MP system manual	
Absolute humidity		
• dew point, min.	-60 °C; suitable for dry room applications	
<b>Decentralized operation</b>		
to SIMATIC S7-300	Yes	
to SIMATIC S7-400	Yes	
to SIMATIC S7-1200	Yes	
to SIMATIC S7-1500	Yes	
to standard PROFINET controller	Yes	
<b>Dimensions</b>		
Width	35 mm	
Height	147 mm	
Depth	129 mm	
<b>Weights</b>		
Weight, approx.	300 g	
<b>Classifications</b>		
	<b>Version</b>	<b>Classification</b>
eClass	16	27-24-22-05
eClass	14	27-24-22-05
eClass	12	27-24-22-05
eClass	9.1	27-24-22-05
eClass	9	27-24-22-05
eClass	8	27-24-22-05
eClass	7.1	27-24-22-05
eClass	6	27-24-22-05
ETIM	10	EC001422
ETIM	9	EC001422
ETIM	8	EC001422
ETIM	7	EC001422
<b>Approvals / Certificates</b>		

General Product Approval



[Miscellaneous](#)



General Product Approval

For use in hazardous locations



[China RoHS](#)



[EM](#)

[CCC-Ex](#)



For use in hazardous locations



[Type Examination Certificate](#)

[Miscellaneous](#)

[CCC-Ex](#)

last modified:

4/23/2026