

Siemens
EcoTech



SIMATIC S7-1500, digital input module DI 16xNAMUR HF, 16 channels in groups of 8; for 8.2 V NAMUR encoder; sensor supply 8.2 V; input delay; parameterizable 0.05 ... 20 ms; integrated counting function up to 20 kHz pulse stretching; chatter monitoring; signal inversion diagnostics; hardware interrupts; all necessary components for shielding included in the scope of supply; front connector (screw terminals or push-in) to be ordered separately

General information	
Product type designation	DI 16xNAMUR HF
HW functional status	from FS01
Firmware version	V1.0.0
<ul style="list-style-type: none"> FW update possible 	Yes
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> Isochronous mode 	Yes
<ul style="list-style-type: none"> Prioritized startup 	Yes
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version 	STEP 7 V17 or higher
<ul style="list-style-type: none"> STEP 7 configurable/integrated from version 	V5.5 SP3 / -
<ul style="list-style-type: none"> PROFIBUS from GSD version/GSD revision 	V1.0 / V5.1
<ul style="list-style-type: none"> PROFINET from GSD version/GSD revision 	V2.3 / -
Operating mode	
<ul style="list-style-type: none"> DI 	Yes
<ul style="list-style-type: none"> Counter 	Yes
<ul style="list-style-type: none"> Oversampling 	No
<ul style="list-style-type: none"> MSI 	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	220 mA
Encoder supply	
Number of outputs	16; 2x 8.2 V DC
Short-circuit protection	Yes
NAMUR encoder supply	
<ul style="list-style-type: none"> 8.2 V 	Yes
<ul style="list-style-type: none"> Short-circuit protection 	Yes; Per group, electronic
<ul style="list-style-type: none"> Output current, max. 	100 mA; per group
<ul style="list-style-type: none"> Output current per module, max. 	200 mA
Power	
Power consumption from the backplane bus	0.6 W

Power loss	
Power loss, typ.	3.7 W
Address area	
Address space per module	
• Inputs	2 byte
• Outputs	0 byte
Digital inputs	
Number of digital inputs	16; NAMUR
Digital inputs, parameterizable	Yes
Sourcing/sinking input	P-reading
Pulse extension	Yes; 0.05 s, 0.1 s, 0.2 s, 0.5 s, 1 s, 2 s
Edge evaluation	Yes; rising edge, falling edge, edge change
Signal change flutter	Yes; 2 to 32 signal changes
Flutter observation window	Yes; 0.5 s, 1 s to 100 s in 1-s steps
Number of simultaneously controllable inputs	
• Number of simultaneously controllable inputs	16
Digital input functions, parameterizable	
• Gate start/stop	Yes; software/hardware gate
• Freely usable digital input	Yes
• Counter	
— Number, max.	4; 4 counters max. 10 kHz or 2 counters max. 20 kHz + 2 counters max. 10 kHz; see manual for details
— Counting frequency, max.	20 kHz; See manual for details
— Counting width	32 bit
— Counting direction up/down	Yes; forward / backward
• Digital input with oversampling	No
Input voltage	
• Rated value (DC)	8.2 V
Input current	
• for signal "1", typ.	10 mA
for 10 k switched contact	
— for signal "0", min.	0.35 mA
— for signal "0", max.	1.2 mA
— for signal "1", min.	2.1 mA
— for signal "1", max.	10 mA
for unswitched contact	
— for signal "0", max. (permissible quiescent current)	0.35 to 1.2 mA
— for signal "1", typ.	2.1 ... 10 mA
for NAMUR encoders	
— for signal "0", min.	0.35 mA
— for signal "0", max.	1.2 mA
— for signal "1", min.	2.1 mA
— for signal "1", max.	10 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.05 / 0.1 / 0.4 / 1.6 / 3.2 / 12.8 / 20 ms
— at "0" to "1", min.	0.05 ms
— at "0" to "1", max.	20 ms
— at "1" to "0", min.	0.05 ms
— at "1" to "0", max.	20 ms
for interrupt inputs	
— Parameterizable	Yes
for technological functions	
— Parameterizable	Yes
for NAMUR inputs	
— at "0" to "1", max.	20 ms
— at "1" to "0", max.	20 ms
Cable length	
• shielded, max.	200 m; 200 m for technological functions; depending on input frequency,

encoder and cable quality; max. 50 m at 20 kHz

Encoder

Connectable encoders

• NAMUR encoder/changeover contact according to EN 60947	Yes; no CO contact
• Single contact / changeover contact unconnected	Yes; no CO contact
• Single contact / changeover contact connected with 10 kΩ	Yes; no CO contact
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.2 mA

Isochronous mode

Filtering and processing time (TCI), min.	60 μs; At 50 μs filter time
Bus cycle time (TDP), min.	250 μs

Interrupts/diagnostics/status information

Diagnostics function	Yes
----------------------	-----

Alarms

• Diagnostic alarm	Yes
• Hardware interrupt	Yes

Diagnoses

• Monitoring the supply voltage	Yes
• Monitoring of encoder power supply	Yes; short-circuit
• Wire break	Yes; to I < 350 μA
• short-circuit	No

Diagnostics indication LED

• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green LED
• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red LED
• for module diagnostics	Yes; red LED

Potential separation

Potential separation channels

• between the channels	No
• between the channels, in groups of	8
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
• between the channels and the power supply of the electronics	No

Isolation

Isolation tested with	707 V DC (type test)
-----------------------	----------------------

Standards, approvals, certificates

Siemens Eco Profile (SEP)	Siemens EcoTech
Suitable for safety functions	No

Ecological footprint

• environmental product declaration	Yes
-------------------------------------	-----

Global warming potential

— global warming potential, (total) [CO2 eq]	18.9 kg
— global warming potential, (during production) [CO2 eq]	12.1 kg
— global warming potential, (during operation) [CO2 eq]	7.66 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-1.02 kg

Security

signed firmware update	No
safely removing data	No
data integrity	No

Ambient conditions

Ambient temperature during operation	
• horizontal installation, min.	-30 °C

- horizontal installation, max. 60 °C
- vertical installation, min. -30 °C
- vertical installation, max. 40 °C

Altitude during operation relating to sea level

- Installation altitude above sea level, max. 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual

Absolute humidity

- dew point, min. -60 °C; suitable for dry room applications

Dimensions

Width	35 mm
Height	147 mm
Depth	129 mm

Weights

Weight, approx.	240 g
-----------------	-------

Classifications

	Version	Classification
eClass	16	27-24-22-04
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419

Approvals / Certificates

General Product Approval

[Miscellaneous](#)



General Product Approval **For use in hazardous locations**



[China RoHS](#)

[Manufacturer Declaration](#)



[FM](#)

[CCC-Ex](#)

For use in hazardous locations **Maritime application**



[Type Examination Certificate](#)

[Miscellaneous](#)

[CCC-Ex](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



Maritime application **Environment**



last modified:

5/7/2026