



Figure similar

SIMATIC DP, DP/DP coupler coupling module for connecting two PROFIBUS DP networks redundant current infeed; product phase-out planned – see SIOS 109989704

Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption, typ.	90 mA
Power loss	
Power loss, typ.	2 W
Protocols	
PROFIBUS DP	Yes
AS-Interface	No
Interrupts/diagnostics/status information	
Status indicator	Yes
Diagnostics function	Yes
Degree and class of protection	
IP degree of protection	IP20
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Dimensions	
Width	40 mm
Height	127 mm
Depth	117 mm
Classifications	

	Version	Classification
eClass	16	27-24-26-08
eClass	14	27-24-26-08
eClass	12	27-24-26-08
eClass	9.1	27-24-26-08
eClass	9	27-24-26-08
eClass	8	27-24-26-08
eClass	7.1	27-24-26-08
eClass	6	27-24-26-08
ETIM	10	EC001604
ETIM	9	EC001604

ETIM	8	EC001604
ETIM	7	EC001604
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval





[Miscellaneous](#)
[Manufacturer Declaration](#)


General Product Approval

EMV

For use in hazardous locations







[China RoHS](#)

For use in hazardous locations





[FM](#)
[Miscellaneous](#)
[CCC-Ex](#)

Maritime application







[NK / Nippon Kaiji Kyokai](#)

Maritime application

[CCS \(China Classification Society\)](#)
[KR \(Korean Register of Shipping\)](#)

last modified: 11/25/2025 