



Figure similar

SIPLUS ET 200SP IM155-6DP HF based on 6ES7155-6BA01-0CN0 with conformal coating, -40...+70 °C, bundle PROFIBUS IM, max. 32 I/O modules and 16 ET 200AL modules, multi hot swap, bundle consists of: interface module (6AG1155-6BU01-7CN0), server module (6AG1193-6PA00-7AA0), PROFIBUS plug

General information	
Product type designation	IM 155-6 DP HF
Firmware version	
• FW update possible	Yes
based on	6ES7155-6BA01-0CN0
Product function	
• I&M data	Yes; I&M0 to I&M3
• Module swapping during operation (hot swapping)	Yes; Multi-hot swapping
• Isochronous mode	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	see entry ID: 109746275
Configuration control	
via dataset	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Mains buffering	
• Mains/voltage failure stored energy time	10 ms
Input current	
Current consumption, max.	335 mA
Inrush current, max.	1.6 A
I ² t	0.038 A ² ·s
Power loss	
Power loss, typ.	1.5 W
Address area	
Address space per module	
• Address space per module, max.	32 byte; per input / output
Address space per station	
• Address space per station, max.	244 byte; per input / output
Hardware configuration	
Rack	
• Quantity of operable ET 200SP modules, max.	32
• Quantity of operable ET 200AL modules, max.	16
Interfaces	
Number of PROFIBUS interfaces	1
1. Interface	

Interface types	
• RS 485	Yes; 1 integrated RS 485 socket
• Output current of the interface, max.	90 mA
Protocols	
• PROFIBUS DP device	Yes
Interface types	
RS 485	
• Transmission rate, max.	12 Mbit/s
Protocols	
Supports protocol for PROFINET IO	No
PROFIsafe	Yes
PROFIBUS	Yes
EtherNet/IP	No
Modbus TCP	No
Open IE communication	
• TCP/IP	No
PROFIBUS DP	
Services	
— SYNC capability	Yes
— FREEZE capability	Yes
— DPV0	Yes
— DPV1	Yes
Interrupts/diagnostics/status information	
Status indicator	Yes
Alarms	Yes
Diagnostics function	Yes
Diagnostics indication LED	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• MAINT LED	Yes; Yellow LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Connection display DP	Yes; green DP LED
Potential separation	
between backplane bus and electronics	No
between PROFIBUS DP and all other circuit components	Yes
between supply and all other circuits	No
Permissible potential difference	
between different circuits	Safety extra low voltage SELV
Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-40 °C; = Tmin (incl. condensation/frost)
• horizontal installation, max.	70 °C; = Tmax
• vertical installation, min.	-40 °C; = Tmin (incl. condensation/frost)
• vertical installation, max.	50 °C; = Tmax
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna);

60721-3-3	Class 3B3 on request																																													
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *																																													
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust; *																																													
— Against mechanical environmental conditions acc. to EN 60721-3-3	Yes; Class 3M8 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)																																													
Use on ships/at sea																																														
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)																																													
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *																																													
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *																																													
— Against mechanical environmental conditions acc. to EN 60721-3-6	Yes; Class 6M4 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)																																													
Usage in industrial process technology																																														
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)																																													
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)																																													
Remark																																														
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!																																													
Conformal coating																																														
• Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high reliability																																													
• Protection against fouling acc. to EN 60664-3	Yes; Type 1 protection																																													
• Military testing according to MIL-I-46058C, Amendment 7	Yes; Discoloration of coating possible during service life																																													
• Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A																																													
Connection method																																														
ET-Connection																																														
• via BU/BA Send	Yes; + 16 ET 200AL modules																																													
Dimensions																																														
Width	50 mm																																													
Height	117 mm																																													
Depth	74 mm																																													
Weights																																														
Weight, approx.	150 g																																													
Classifications																																														
	<table><tr><td></td><td>Version</td><td>Classification</td></tr><tr><td>eClass</td><td>16</td><td>27-24-26-08</td></tr><tr><td>eClass</td><td>14</td><td>27-24-26-08</td></tr><tr><td>eClass</td><td>12</td><td>27-24-26-08</td></tr><tr><td>eClass</td><td>9.1</td><td>27-24-26-08</td></tr><tr><td>eClass</td><td>9</td><td>27-24-26-08</td></tr><tr><td>eClass</td><td>8</td><td>27-24-26-08</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-26-08</td></tr><tr><td>eClass</td><td>6</td><td>27-24-26-08</td></tr><tr><td>ETIM</td><td>10</td><td>EC001604</td></tr><tr><td>ETIM</td><td>9</td><td>EC001604</td></tr><tr><td>ETIM</td><td>8</td><td>EC001604</td></tr><tr><td>ETIM</td><td>7</td><td>EC001604</td></tr><tr><td>IDEA</td><td>4</td><td>3564</td></tr><tr><td>UNSPSC</td><td>15</td><td>32-15-17-05</td></tr></table>		Version	Classification	eClass	16	27-24-26-08	eClass	14	27-24-26-08	eClass	12	27-24-26-08	eClass	9.1	27-24-26-08	eClass	9	27-24-26-08	eClass	8	27-24-26-08	eClass	7.1	27-24-26-08	eClass	6	27-24-26-08	ETIM	10	EC001604	ETIM	9	EC001604	ETIM	8	EC001604	ETIM	7	EC001604	IDEA	4	3564	UNSPSC	15	32-15-17-05
	Version	Classification																																												
eClass	16	27-24-26-08																																												
eClass	14	27-24-26-08																																												
eClass	12	27-24-26-08																																												
eClass	9.1	27-24-26-08																																												
eClass	9	27-24-26-08																																												
eClass	8	27-24-26-08																																												
eClass	7.1	27-24-26-08																																												
eClass	6	27-24-26-08																																												
ETIM	10	EC001604																																												
ETIM	9	EC001604																																												
ETIM	8	EC001604																																												
ETIM	7	EC001604																																												
IDEA	4	3564																																												
UNSPSC	15	32-15-17-05																																												
Approvals / Certificates																																														

[Manufacturer Declaration](#)

[China RoHS](#)



[CCC-Ex](#)

Maritime application



last modified:

10/23/2025