



protective film 10" mobile devices, TP1000F Mobile, TP1000F Mobile RO, more information, quantity and content: see technical specifications

General information	
Product type designation	Protective film 10" Mobile Panel
Installation type/mounting	
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	-40 °C
• max.	80 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	80 °C
Relative humidity	
• Operation, max.	90 %
• Condensation permissible	No
Mechanics/material	
Material	
• plastic	Yes; Nonreflecting
Dimensions	
Width	233.2 mm
Height	148.6 mm
Thickness	0.125 mm
Scope of supply	
Delivery quantity in pieces	10
Other	
printable with laser printer	No
Merchandise	No
Manufacturer name	SIEMENS AG
Manufacturer's address	Breslauer Strasse 5, 90766 Fürth, Germany
Target devices	TP1000F Mobile, TP1000F Mobile RO
Classifications	

	Version	Classification
eClass	16	27-33-02-92
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92

eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)

[China RoHS](#)

Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415
<https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW>

last modified:

12/17/2024 