



SIMATIC ET 200BL, digital output module, DQ 16x24 V DC/0.5 A, output characteristic according to IEC 61131 source output (PNP,sourcing output) packing unit: 1 unit, color code CC00

General information	
Product type designation	DQ 16x24VDC/0.5A
HW functional status	from FS01
Firmware version	
• FW update possible	No
Color code for module-specific color-coded label	CC00
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	STEP 7 V18 or higher; MicroWin V3.0 or higher; Configuration in ES via GSDML;
• PROFINET from GSD version/GSD revision	GSDML V2.45
Operating mode	
• DQ	Yes
• DQ with energy-saving function	No
• PWM	No
• Cam control (switching at comparison values)	No
• Oversampling	No
• MSO	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
external protection for power supply lines	Yes; 24 V DC/10 A miniature circuit breaker with type B or C tripping characteristic
Input current	
Current consumption (rated value)	55 mA
Current consumption, max.	8.1 A; with 8 A output to load
Output voltage	
Rated value (DC)	24 V
Current carrying capacity	
For P1 and P2 bus, max.	10 A
Power loss	
Power loss, typ.	1 W; rated voltage, 50 % load, 50 % active channels
Address area	
Address space per module	
• Address space per module, max.	2 byte

• Outputs	2 byte
Hardware configuration	
Automatic encoding	No
• Mechanical coding element	No
Formation of potential groups	
• support of potential groups	No
Digital outputs	
Type of digital output	Source output (PNP, current-sourcing)
Number of digital outputs	16
Current-sinking	No
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
output type acc. to IEC 61131, type 0.5	Yes
Short-circuit protection	Yes; per channel, electronic
• Response threshold, typ.	1.45 A; 0.7 to 1.7 A
Limitation of inductive shutdown voltage to	typ. (L+) -52 V
Controlling a digital input	Yes
Switching capacity of the outputs	
• with resistive load, max.	0.5 A
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	100 kΩ
Output current	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, max.	0.5 A
• for signal "0" residual current, max.	5 μA
Output delay with resistive load	
• "0" to "1", max.	100 μs
• "1" to "0", max.	300 μs
Parallel switching of two outputs	
• for uprating	No
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	2 Hz
• on lamp load, max.	10 Hz
Total current of the outputs	
• Current per channel, max.	0.5 A
• Current per module, max.	8 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnoses	
• Monitoring the supply voltage	Yes
• Wire break	No
• Short-circuit	No
• Group error	No
Diagnostics indication LED	
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Channel status display	Yes; green LED
• for channel diagnostics	No
• for module diagnostics	Yes; green/red DIAG LED
Potential separation	
between backplane bus and supply voltage	Yes

Potential separation digital outputs			
• between the channels		No	
• between the channels and backplane bus		Yes	
• between the channels and the power supply of the electronics		No	
Isolation			
Isolation tested with		500 V AC/707 V DC, type test	
Standards, approvals, certificates			
Suitable for safety functions		No	
Ecological footprint			
• environmental product declaration		Yes	
Global warming potential			
— global warming potential, (total) [CO2 eq]		28.7 kg	
— global warming potential, (during production) [CO2 eq]		4.87 kg	
— global warming potential, (during operation) [CO2 eq]		24.5 kg	
— global warming potential, (after end of life cycle) [CO2 eq]		-0.623 kg	
Use in hazardous areas			
• EAC Ex		No	
Ambient conditions			
Ambient temperature during operation			
• horizontal installation, min.		-30 °C	
• horizontal installation, max.		60 °C	
• vertical installation, min.		-30 °C	
• vertical installation, max.		50 °C	
Altitude during operation relating to sea level			
• Installation altitude above sea level, max.		5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200BL system manual	
Connection method			
Terminals			
• Conductor cross-section, min.		0.14 mm²; follow detailed information in System manual of ET 200BL	
• Conductor cross-section, max.		2.5 mm²; follow detailed information in System manual of ET 200BL	
• Number of process terminals to I/O module		16	
• Number of terminals with connection to P1 and P2 bus		0	
Dimensions			
Width		15 mm	
Height		117 mm	
Depth		74 mm	
Weights			
Weight, approx.		80 g	
Classifications			
		Version	Classification
	eClass	16	27-24-26-04
	eClass	14	27-24-26-04
	eClass	12	27-24-26-04
	eClass	9.1	27-24-26-04
	eClass	9	27-24-26-04
	eClass	8	27-24-26-04
	eClass	7.1	27-24-26-04
	eClass	6	27-24-26-04
	ETIM	10	EC001599
	ETIM	9	EC001599
	ETIM	8	EC001599
	ETIM	7	EC001599
Approvals / Certificates			
General Product Approval			



[China RoHS](#)



General Product Approval	EMV	Environment
		

last modified:

11/17/2025 