


plyta montażowa 3VA20 (100 A), 3VA21 (160 A), 3VA22 (250 A), 4-bieg., montaż na stałe, RCD: wbudowany, wys.: 450 mm szer.: 800 mm



Wersja	
Nazwa markowa produktu	SIVACON S4
oznaczenie produktu	Płyta montażowa 3VA
wykonanie produktu	3VA20 (do 100 A); 3VA21 (do 160 A); 3VA22 (do 250 A)
Ogólne dane techniczne	
obróbka powierzchniowa	ocynkowany
właściwość produktu perforowany	Tak
Konstrukcja mechaniczna	
wysokość	400 mm
szerokość	800 mm
głębokość	400 mm
grubość materiału blachy	2 mm
Waga netto na jedn.	5,232 kg
materiał	Blacha stalowa

Zezwolenia Certyfikaty	
Environment	General Product Approval

[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)



[Confirmation](#)

General Product Approval	other
--------------------------	-------

[Miscellaneous](#)



[Confirmation](#)



Więcej informacji

Informacje dotyczące opakowania
[Informacje dotyczące opakowania](#)
Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/lowvoltage/catalogs>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8PQ6000-8BA52>
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/pl/ps/8PQ6000-8BA52>
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8PQ6000-8BA52

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Krzywe charakterystyczne

https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>

Ostatnia zmiana:

7.08.2025 

