



SIMATIC HMI MTP1900 Unified Comfort Panel hygienic, neutral design, IP69, stainless steel, hygienic design, 18.5" widescreen TFT display, 16 million colors, touch operation, blue FDA-compliant gasket, increased impact protection with splinter protection display front according to directives DIN EN 1672-2, FDA 21 CFR 177.2006, PROFINET interface, configurable as of WinCC Unified Comfort V16, contains open-source software, which is provided free of charge see enclosed Blu-Ray

General information	
Product type designation	MTP1900 Unified Comfort
Display	
Design of display	TFT
Screen diagonal	18.5 in
Display width	408.96 mm
Display height	230.04 mm
Number of colors	16 777 216
Resolution (pixels)	
• Horizontal image resolution	1 920 pixel
• Vertical image resolution	1 080 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h; At 25°C
• Backlight dimmable	Yes; 10 ... 100%
Control elements	
Keyboard	
• Numeric keyboard	Yes; Onscreen keyboard
• alphanumeric keyboard	Yes; Onscreen keyboard
Touch operation	
• Design as touch screen	Yes
• Design as multi-touch screen	Yes
• Monitor keyboard	Yes
Installation type/mounting	
Mounting position	Horizontal, vertical
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
maximum permissible angle of inclination without external ventilation	35°
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	1.2 A
Current consumption, max.	1.7 A
Starting current inrush I ² t	0.5 A ² ·s
Storage	
Flash	Yes

RAM	Yes
Type of output	
Acoustics	
• Buzzer	Yes
• Speaker	No
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• Software clock	Yes
• retentive	Yes; Back-up duration typically 6 weeks
• synchronizable	Yes
Interfaces	
Number of industrial Ethernet interfaces	2; 2 ports (switch) + independent port
Number of RS 485 interfaces	1; RS 422 / 485 combined
Number of RS 422 interfaces	0; together with RS 485
Number of USB interfaces	4; USB 3.1 Gen. 1 (type A)
Number of SD card slots	2
Industrial Ethernet	
• Industrial Ethernet status LED	2
• Number of ports of the integrated switch	2
Protocols	
PROFINET	Yes
Supports protocol for PROFINET IO	No
Protocols (Ethernet)	
• TCP/IP	Yes
• DHCP	Yes
• SNMP	Yes
• DCP	Yes
• LLDP	Yes
WEB characteristics	
• HTTP	Yes
• HTTPS	Yes
• HTML	Yes
• XML	Yes
• CSS	Yes
• JavaScript	Yes
Redundancy mode	
Media redundancy	
— MRP	Yes
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class A, for use in industrial areas	Yes
• Limit class B, for use in residential areas	No
Degree and class of protection	
IP (at the front)	IP69
IP (rear)	IP20
NEMA (front)	
• Enclosure Type 4x at the front	No; in preparation
• Enclosure Type 12 at the front	No; in preparation
Standards, approvals, certificates	
CE mark	Yes
UKCA mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	No; in preparation
EAC (formerly Gost-R)	Yes
CCC	No; in preparation
Use in hazardous areas	

• ATEX Zone 2	Yes
• ATEX Zone 22	Yes
• IECEx Zone 2	Yes
• IECEx Zone 22	Yes
• cULus Class I Zone 2, Division 2	Yes
• cULus Class II Division 2	Yes
• FM Class I Division 2	No
• FM Class II Division 2	No
Marine approval	
• Germanischer Lloyd (GL)	No
• American Bureau of Shipping (ABS)	No
• Bureau Veritas (BV)	No
• Det Norske Veritas (DNV)	No
• Korean Register of Shipping (KRS)	No
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (Class NK)	No
• Polski Rejestr Statkow (PRS)	No
• Chinese Classification Society (CCS)	No
Ambient conditions	
Suited for indoor use	Yes
Suited for outdoor use	No
Ambient temperature during operation	
Operation (vertical installation)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	45 °C
Operation (max. tilt angle)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, max.	40 °C
Operation (vertical installation, portrait format)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	40 °C
Operation (max. tilt angle, portrait format)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, max.	35 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	90 %; no condensation
Operating systems	
proprietary	Yes
Configuration	
Message indicator	Yes
Alarm system (incl. buffer and acknowledgment)	Yes
Process value display (output)	Yes
Process value default (input) possible	Yes
Recipe management	Yes
Configuration software	
• WinCC Unified Comfort Engineering (TIA Portal)	Yes
• WinCC Unified PC Engineering (TIA Portal)	Yes
Languages	
Online languages	
• Number of online/runtime languages	32
Project languages	
• Languages per project	32
Functionality under WinCC Unified	
Libraries	Yes
Applications/options	
• Writer	Yes

• Calc	Yes
• Web browser	Yes
• PDF Viewer	Yes
• Media Player	Yes
• SIMATIC WinCC Sm@rtServer	Yes
• SIMATIC WinCC Audit	No
• Unified Collaboration	No
Number of Visual Basic Scripts	No
JavaScript	Yes
Task planner	
• time-controlled	Yes
• task-controlled	Yes
Help system	
• Number of characters per info text	70
• Number of message texts per message	10
Message system	
• Number of alarm classes	32
• Bit messages	
— Number of bit messages	9 000
• Analog messages	
— Number of analog messages	300
• S7 alarm number procedure	Yes
• System messages HMI	Yes
• System event, more (SIMATIC S7, SINUMERIK, SIMOTION, ...)	Yes
• Number of characters per message	512
• Number of process values per message	10
• Acknowledgment groups	Yes
• Message indicator	No
• Message buffer	Yes; Configured as alarm archive
— Circulating buffer	Yes
— retentive	Yes
— maintenance-free	Yes
Parameter set management (recipes)	
• Number of parameter set types	750
• Parameter sets per parameter set type	2 000
• Entries per parameter set	1 000
• Size of internal parameter set memory	12 Mbyte
• Parameter set memory expandable	Yes
Variables	
• Number of variables per device	8 000
• Number of variables per screen	800
• Limit values	Yes
• Structures	Yes
• Arrays	Yes
Images	
• Number of configurable images	1 200
• Faceplate	Yes
Image objects	
• Number of objects per image	1 200
• Picture window	Yes
• Text fields	Yes
• I/O fields	Yes
• Graphic I/O fields (graphics list)	Yes
• Symbolic I/O fields (text list)	Yes
• Scalable Vector Graphics (SVG)	Yes
• Date/time fields	Yes
• Checkbox	Yes
• Option button	Yes

• Switches	Yes
• Buttons	Yes
• Graphic display	Yes
• Icons	Yes
• Custom web display	Yes
• Geometric objects	Yes
Complex image objects	
• Number of complex objects per screen	80
• Alarm view	Yes
• Trend view	Yes
• User view	Yes
• Status/control	No
• Parameter set display	Yes
• HTML browser	Yes
• Bar graphs	Yes
• Sliders	Yes
• Pointer instruments	Yes
• Analog/digital clock	Yes
Lists	
• Number of text lists per project	750
• Number of entries per text list	750
• Number of graphics lists per project	750
• Number of entries per graphics list	750
Archiving	
• Number of archives per device	50
• Number of entries per archive	500 000
• Message archive	Yes
• Process value archive	Yes
• Archiving methods	
— Sequential archive	Yes
— Short-term archive	Yes
• Memory location	
— Memory card	Yes
— USB memory	Yes
— Ethernet	No
Security	
• Number of roles	50
• Number of function rights	0; V16
• Number of users	200
• Password export/import	Yes
• Central user administration	Yes; as of WinCC Unified V17
Transfer (upload/download)	
• USB	No
• Ethernet	Yes
• using external storage medium	Yes; as of WinCC Unified V17
Process coupling	
• S7-1200	Yes
• S7-1500	Yes
• S7-200	No
• S7-300/400	Yes
• Number of S7 connections	16
• LOGO!	No
• SIMOTION	No
• OPC UA Client	Yes
• OPC UA Server	Yes
• Software Controller/Open Controller	Yes
Service tools/configuration aids	
• Backup/Restore manually	Yes
• Backup/Restore automatically	Yes

• Simulation • Device switchover		Yes																																							
		Yes																																							
Peripherals/Options																																									
Peripherals	Printer, barcode reader																																								
Printer	Yes																																								
SIMATIC HMI MM memory card: Multi Media Card	No																																								
SIMATIC HMI SD memory card: Secure Digital memory card	Yes																																								
SIMATIC HMI CF memory card Compact Flash Card	No																																								
USB memory	Yes																																								
SIMATIC IPC USB Flashdrive (USB stick)	Yes																																								
SIMATIC HMI USB stick	Yes																																								
Network camera	No																																								
Accessories																																									
Further accessories are available	No; Service Pack available soon																																								
Mechanics/material																																									
Enclosure material (front) • Plastic • Stainless steel	Yes; shatter protection film Yes																																								
Dimensions																																									
Width of the housing front	479 mm																																								
Height of housing front	309 mm																																								
Mounting cutout, width	448 mm																																								
Mounting cutout, height	278 mm																																								
mounting depth	79 mm																																								
Weights																																									
Weight (without packaging)	6.7 kg																																								
Classifications																																									
	<table><tr><td></td><td>Version</td><td>Classification</td></tr><tr><td>eClass</td><td>16</td><td>27-33-02-01</td></tr><tr><td>eClass</td><td>14</td><td>27-33-02-01</td></tr><tr><td>eClass</td><td>12</td><td>27-33-02-01</td></tr><tr><td>eClass</td><td>9.1</td><td>27-33-02-01</td></tr><tr><td>eClass</td><td>9</td><td>27-33-02-01</td></tr><tr><td>eClass</td><td>8</td><td>27-24-23-02</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-23-02</td></tr><tr><td>eClass</td><td>6</td><td>27-24-23-02</td></tr><tr><td>ETIM</td><td>10</td><td>EC001412</td></tr><tr><td>ETIM</td><td>9</td><td>EC001412</td></tr><tr><td>ETIM</td><td>8</td><td>EC001412</td></tr><tr><td>ETIM</td><td>7</td><td>EC001412</td></tr></table>		Version	Classification	eClass	16	27-33-02-01	eClass	14	27-33-02-01	eClass	12	27-33-02-01	eClass	9.1	27-33-02-01	eClass	9	27-33-02-01	eClass	8	27-24-23-02	eClass	7.1	27-24-23-02	eClass	6	27-24-23-02	ETIM	10	EC001412	ETIM	9	EC001412	ETIM	8	EC001412	ETIM	7	EC001412	
	Version	Classification																																							
eClass	16	27-33-02-01																																							
eClass	14	27-33-02-01																																							
eClass	12	27-33-02-01																																							
eClass	9.1	27-33-02-01																																							
eClass	9	27-33-02-01																																							
eClass	8	27-24-23-02																																							
eClass	7.1	27-24-23-02																																							
eClass	6	27-24-23-02																																							
ETIM	10	EC001412																																							
ETIM	9	EC001412																																							
ETIM	8	EC001412																																							
ETIM	7	EC001412																																							
Approvals / Certificates																																									
General Product Approval																																									
	Miscellaneous	   China RoHS																																							
General Product Approval																																									
EMV																																									
	    																																								
EMV	For use in hazardous locations																																								



[CCC-Ex](#)



other	Food, Pharmaceutical, Medical
-------	-------------------------------



[Miscellaneous](#)

[Special Test Certificate](#)

last modified:

6/18/2026