



Tulejka izolowana do wsuwki płaskiej, 2,8 x 0,8 mm, nasadzana z przodu

Ogólne dane techniczne			
oznaczenie typu produktu			3SB2
wykonanie produktu			Pozostałe
Aprobaty/ Certyfikaty			
General Product Approval		Test Certificates	other
 UL		 EG-Konf.	
		Miscellaneous	Confirmation
other	Environment		
	Environmental Confirmations		

Więcej informacji
Informacje dotyczące opakowania Informacje dotyczące opakowania
Information for data generation and storage https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter https://www.siemens.com/ic10
Industry Mall (System zamawiania online) https://mall.industry.siemens.com/mall/pl/pl/Catalog/product?mlfb=3SB2908-8AB
CAX-Online-Generator https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2908-8AB
Service&Support https://support.industry.siemens.com/cs/ww/en/ps/3SB2908-8AB
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB2908-8AB&lang=en

Ostatnia zmiana: 2.04.2025 