

Electronics module for ET 200S, 8 DO Sink Output, 24 V DC/0.5 A, 15 mm width, 1 unit per packing unit



Supply voltage

Reverse voltage protection	Yes; when using the same correctly polarized load voltage as on the power module
----------------------------	--

Load voltage L+

<ul style="list-style-type: none"> • Rated value (DC) 	24 V; From power module
<ul style="list-style-type: none"> • Reverse polarity protection 	Yes

Input current

from load voltage L+ (without load), max.	5 mA
from backplane bus 3.3 V DC, max.	10 mA

Power loss

Power loss, typ.	1.5 W
------------------	-------

Address area

Address space per module	
<ul style="list-style-type: none"> • Address space per module, max. 	1 byte

Digital outputs

Type of digital output	Transistor
Number of digital outputs	8

Short-circuit protection	Yes
• Response threshold, typ.	1.5 A
Limitation of inductive shutdown voltage to	Typ. 47 V
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	3 400 Ω
Output voltage	
• for signal "1", min.	Max. 1 V
Output current	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, min.	5 mA
• for signal "1" permissible range, max.	600 mA
• for signal "0" residual current, max.	5 μ A
Output delay with resistive load	
• "0" to "1", max.	300 μ s
• "1" to "0", max.	600 μ s
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes; per module
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	10 Hz
Total current of the outputs	
• Current per module, max.	4 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Interrupts/diagnostics/status information	
Diagnostics function	No
Diagnostics indication LED	
• Status indicator digital output (green)	Yes
Parameter	
Remark	3 byte
Potential separation	
Potential separation digital outputs	
• between the channels	No
• between the channels and backplane bus	Yes

Isolation

Isolation tested with	500 V DC
-----------------------	----------

Dimensions

Width	15 mm
-------	-------

Height	81 mm
--------	-------

Depth	52 mm
-------	-------

Weights

Weight, approx.	40 g
-----------------	------

last modified:	04/17/2020
-----------------------	------------