

LOGO! DM16 24 expansion module, PS/I/O: 24 V DC/24 V DC/trans., 8 DI/8 DO, 4 MW for LOGO! 8



Installation type/mounting	
Mounting	on 35 mm DIN rail, 4 spacing units wide
Supply voltage	
Rated value (DC)	Yes
<ul style="list-style-type: none"> <li>• 24 V DC</li> </ul>	
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Digital inputs	
Number of digital inputs	8
Input voltage	
<ul style="list-style-type: none"> <li>• Type of input voltage</li> </ul>	DC
<ul style="list-style-type: none"> <li>• for signal "0"</li> </ul>	< 5 V DC
<ul style="list-style-type: none"> <li>• for signal "1"</li> </ul>	> 12 V DC
Input current	
<ul style="list-style-type: none"> <li>• for signal "0", max. (permissible quiescent current)</li> </ul>	0.85 mA
<ul style="list-style-type: none"> <li>• for signal "1", typ.</li> </ul>	2 mA
Input delay (for rated value of input voltage)	

for standard inputs	
— at "0" to "1", max.	1.5 ms
— at "1" to "0", max.	1.5 ms

#### Digital outputs

Number of digital outputs	8
Short-circuit protection	Yes
Output current	
• for signal "1" rated value	0.3 A
Parallel switching of two outputs	
• for uprating	No
Switching frequency	
• with resistive load, max.	10 Hz
• with inductive load, max.	0.5 Hz

#### EMC

Emission of radio interference acc. to EN 55 011	
• Limit class B, for use in residential areas	Yes

#### Degree and class of protection

Degree of protection acc. to EN 60529	
• IP20	Yes

#### Standards, approvals, certificates

CE mark	Yes
CSA approval	Yes
UL approval	Yes
FM approval	Yes
developed in accordance with IEC 61131	Yes
according to VDE 0631	Yes
Marine approval	Yes

#### Ambient conditions

Ambient temperature during operation	
• min.	0 °C; ES03 and higher: -20 °C
• max.	55 °C

#### Dimensions

Width	71.5 mm
Height	90 mm
Depth	58 mm
<b>last modified:</b>	04/09/2020