

Siemens
EcoTech



SIMATIC ET 200eco PN, AI 8xRTD/TC, M12-L, 8x M12, 16-bit resolution, channel diagnostics for wire break at input, shared device with 2 controllers, prioritized startup, MSI, MRP, S2 redundancy, I&M0...3, multi-fieldbus, PN IO, Ethernet IP, Modbus TCP, degree of protection IP67 / IP69K

General information	
HW functional status	FS03
Firmware version	V5.1.x
• FW update possible	Yes
Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0306H
Manufacturer ID according to ODVA (VendorID)	04E3H
Device ID according to ODVA (Product code)	0FAAH
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
• IRT	Yes
• Prioritized startup	Yes
• Measuring range scalable	Yes
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	STEP 7 V17 or higher with HSP 0369
• PROFINET from GSD version/GSD revision	GSDML V2.4.x
• Multi Fieldbus Configuration Tool (MFCT)	from V1.3 SP1
Operating mode	
• MSI	Yes
CiR - Configuration in RUN	
Calibration possible in RUN	Yes
Supply voltage	
power supply according to NEC Class 2 required	No
Load voltage 1L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
• Reverse polarity protection	Yes; against destruction
Input current	
Current consumption (rated value)	85 mA; without load
from load voltage 1L+ (unswitched voltage)	12 A; Maximum value
from load voltage 2L+, max.	12 A; Maximum value
Power loss	
Power loss, typ.	6.3 W
Address area	

Address space per module	
• Inputs	16 byte; + 1 byte for QI information
Hardware configuration	
Submodules	
• Number of configurable submodules, max.	2
Analog inputs	
Number of analog inputs	8
• For voltage measurement	8
• For resistance/resistance thermometer measurement	8
• For thermocouple measurement	8
permissible input voltage for voltage input (destruction limit), max.	24 V
Constant measurement current for resistance-type transmitter, typ.	0.7 mA
Cycle time (all channels), min.	Sum of the basic conversion times and additional processing times (depending on the parameterization of the active channels); for line compensation in case of a three-wire connection, an additional cycle is necessary
Technical unit for temperature measurement adjustable	Yes; Degrees Celsius / degrees Fahrenheit / Kelvin
Input ranges (rated values), voltages	
• -80 mV to +80 mV	Yes; 16 bit incl. sign
— Input resistance (-80 mV to +80 mV)	10 MΩ
Input ranges (rated values), thermocouples	
• type B	Yes; 16 bit incl. sign
— Input resistance (Type B)	10 MΩ
• type C	Yes; 16 bit incl. sign
— Input resistance (Type C)	10 MΩ
• Type E	Yes; 16 bit incl. sign
— Input resistance (Type E)	10 MΩ
• Type J	Yes; 16 bit incl. sign
— Input resistance (type J)	10 MΩ
• Type K	Yes; 16 bit incl. sign
— Input resistance (Type K)	10 MΩ
• Type L	Yes; 16 bit incl. sign
— Input resistance (Type L)	10 MΩ
• Type N	Yes; 16 bit incl. sign
— Input resistance (Type N)	10 MΩ
• Type R	Yes; 16 bit incl. sign
— Input resistance (Type R)	10 MΩ
• Type S	Yes; 16 bit incl. sign
— Input resistance (Type S)	10 MΩ
• Type T	Yes; 16 bit incl. sign
— Input resistance (Type T)	10 MΩ
• Type U	Yes; 16 bit incl. sign
— Input resistance (Type U)	10 MΩ
Input ranges (rated values), resistance thermometer	
• Ni 100	Yes; Standard/climate
— Input resistance (Ni 100)	10 MΩ
• Ni 1000	Yes; Standard/climate
— Input resistance (Ni 1000)	10 MΩ
• Ni 120	Yes; Standard/climate
— Input resistance (Ni 120)	10 MΩ
• Ni 200	Yes; Standard/climate
— Input resistance (Ni 200)	10 MΩ
• Ni 500	Yes; Standard/climate
— Input resistance (Ni 500)	10 MΩ
• Pt 100	Yes; Standard/climate
— Input resistance (Pt 100)	10 MΩ
• Pt 1000	Yes; Standard/climate
— Input resistance (Pt 1000)	10 MΩ
• Pt 200	Yes; Standard/climate

— Input resistance (Pt 200)	10 MΩ
• Pt 500	Yes; Standard/climate
— Input resistance (Pt 500)	10 MΩ
Input ranges (rated values), resistors	
• 0 to 150 ohms	Yes
— Input resistance (0 to 150 ohms)	10 MΩ
• 0 to 300 ohms	Yes
— Input resistance (0 to 300 ohms)	10 MΩ
• 0 to 600 ohms	Yes
— Input resistance (0 to 600 ohms)	10 MΩ
• 0 to 3000 ohms	Yes
— Input resistance (0 to 3000 ohms)	10 MΩ
• 0 to 6000 ohms	Yes
— Input resistance (0 to 6000 ohms)	10 MΩ
Thermocouple (TC)	
Temperature compensation	
— Parameterizable	Yes
— internal temperature compensation	Yes
— external temperature compensation with compensations socket	Yes
— dynamic reference temperature value	Yes
— fixed reference temperature	Yes
Cable length	
• shielded, max.	30 m
Analog value generation for the inputs	
Analog value display	SIMATIC S7 format
Measurement principle	integrating
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Integration time, parameterizable	Yes; channel by channel
• Integration time (ms)	0.84 / 16.7 (50) / 20 (60) / 60 (180)
• Basic conversion time, including integration time (ms)	4.50 / 21.5 (54) / 24 (64) / 64 (184)
— additional conversion time for wire-break monitoring	2 ms; for 3/4-wire transducer 4 ms
• Interference voltage suppression for interference frequency f1 in Hz	none / 60 / 50 / 16.7
Smoothing of measured values	
• Parameterizable	Yes
• Step: None	Yes; 1x cycle time
• Step: low	Yes; 4x cycle time
• Step: Medium	Yes; 16x cycle time
• Step: High	Yes; 32x cycle time
Encoder	
Connection of signal encoders	
• for resistance measurement with two-wire connection	Yes
• for resistance measurement with three-wire connection	Yes
• for resistance measurement with four-wire connection	Yes
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.01 %; ±0.1 % for resistance thermometers and resistance
Temperature error (relative to input range), (+/-)	0.0009 %/K; ±0.005 % / K at thermocouple
Crosstalk between the inputs, max.	-70 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.008 %
Temperature error of internal compensation	±1,5 °C
Operational error limit in overall temperature range	
• Voltage, relative to input range, (+/-)	0.2 %
• Resistance, relative to input range, (+/-)	0.1 %; See deviations in the manual
• Resistance thermometer, relative to input range, (+/-)	0.1 %; See deviations in the manual
• Thermocouple, relative to input range, (+/-)	0.3 %
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	0.1 %

• Resistance, relative to input range, (+/-)	0.05 %; See deviations in the manual
• Resistance thermometer, relative to input range, (+/-)	0.05 %; See deviations in the manual
• Thermocouple, relative to input range, (+/-)	0.15 %
Interference voltage suppression for $f = n \times (f_1 \pm 0.5 \%)$, f_1 = interference frequency	
• Series mode interference (peak value of interference < rated value of input range), min.	100 dB; at basic conversion time 4.5 / 21.5 / 24 / 64 ms: 46 dB
Interfaces	
Transmission procedure	100BASE-TX
Number of PROFINET interfaces	1
1. Interface	
Interface type	PROFINET with 100 Mbit/s full duplex (100BASE-TX)
Interface types	
• M12 port	Yes; 2x M12, 4-pin, D-coded
• Number of ports	2
• integrated switch	Yes
Protocols	
• PROFINET IO Device	Yes
• Open IE communication	Yes
PROFINET IO Device	
Services	
— IRT	Yes; 250 µs to 4 ms in 125 µs frame
— Prioritized startup	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2
Interface types	
M12 port	
• Autonegotiation	Yes
• Autocrossing	Yes
• Transmission rate, max.	100 Mbit/s
Protocols	
Supports protocol for PROFINET IO	Yes
PROFIsafe	No
EtherNet/IP	Yes
Modbus TCP	Yes
Redundancy mode	
• PROFINET system redundancy (S2)	Yes
— on S7-1500R/H	Yes
— on S7-400H	Yes
• PROFINET system redundancy (R1)	No
• H-Sync forwarding	Yes
Media redundancy	
— MRP	Yes
— MRPD	No
EtherNet/IP	
Services	
— CIP Implicit Messaging	Yes
— CIP Explicit Messaging	Yes
— CIP Safety	No
— Shared device	Yes; 2x EtherNet/IP Scanner
— Number of scanners with shared device, max.	2
Updating times	
— Requested Packet Interval (RPI)	2 ms
Redundancy mode	
— DLR (Device Level Ring)	No
Address area	
— Address space per module, max.	38 byte
— LargeForwardOpen (Class3)	No
Modbus TCP	
Services	

— read coils (code=1)	Yes
— read discrete inputs (code=2)	Yes
— Read Holding Registers (Code=3)	Yes
— write single coil (code=5)	Yes
— write multiple coils (code=15)	Yes
— Write Multiple Registers (Code=16)	Yes
— Parameter change by master	No
— Modbus TCP Security Protocol	No
Address space per station	
— Address space per station, max.	38 byte
— Access-consistent address space	2 byte
Updating time	
— I/O request interval	2 ms
Connections	
— number of connections per device	12
Open IE communication	
• TCP/IP	Yes; (only EtherNet/IP or Modbus TCP)
• SNMP	Yes
• LLDP	Yes
• ARP	Yes
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	Yes; Parameterizable
• Maintenance interrupt	Yes; Parameterizable
• Limit value alarm	Yes; two upper and two lower limit values in each case
Diagnoses	
• Diagnostic information readable	Yes
• Monitoring the supply voltage	Yes
— parameterizable	Yes
• Wire break	Yes; Not for ± 80 mV
• Overflow/Underflow	Yes
Diagnostics indication LED	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• MAINT LED	Yes; Yellow LED
• NS LED	Yes; green/red LED
• MS LED	Yes; green/red LED
• IO LED	Yes; red/green/yellow LEDs
• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red LED
• Connection display LINK TX/RX	Yes; green LED, only link
Potential separation	
between the load voltages	Yes
between Ethernet and electronics	Yes
Potential separation channels	
• between the channels	No
• between the channels and the power supply of the electronics	Yes
Isolation	
tested with	
• 24 V DC circuits	707 V DC (type test)
• Test voltage for interface, rms value [Vrms]	1 500 V; According to IEEE 802.3
Degree and class of protection	
IP degree of protection	IP65/67/69K
Standards, approvals, certificates	
Suitable for safety-related tripping of standard modules	Yes; from FS01
Suitable for applications according to AMS 2750	Yes; Declaration of Conformity, see online support entry 109757262
Suitable for applications according to CQI-9	Yes; based on AMS 2750 F
Highest safety class achievable for safety-related tripping of standard modules	

• Performance level according to ISO 13849-1 • Category according to ISO 13849-1 • SIL acc. to IEC 62061 • remark on safety-oriented shutdown	PL d Cat. 3 SIL 2 https://support.industry.siemens.com/cs/de/en/view/39198632
--	--

Use in hazardous areas	
• Explosion protection category for gas	ATEX, UKEX, IECEx, CCCEX for Zone 2
• Explosion protection category for dust	ATEX, UKEX, IECEx, CCCEX for Zone 22

Security	
signed firmware update	Yes
safely removing data	Yes

Ambient conditions	
Ambient temperature during operation	
• min.	-40 °C
• max.	60 °C
Altitude during operation relating to sea level	
• Ambient air temperature-barometric pressure-altitude	Up to max. 5 000 m, at installation height > 2 000 m additional restrictions

Connection method	
Design of electrical connection	4/5-pin M12 circular connectors
Design of electrical connection for the inputs and outputs	M12, 5-pin, A-coded
Design of electrical connection for supply voltage	M12, 4-pin, L-coded

Dimensions	
Width	45 mm
Height	200 mm
Depth	48 mm

Weights	
Weight, approx.	780 g

Classifications			
		Version	Classification
	eClass	16	27-24-26-01
	eClass	14	27-24-26-01
	eClass	12	27-24-26-01
	eClass	9.1	27-24-26-01
	eClass	9	27-24-26-01
	eClass	8	27-24-26-01
	eClass	7.1	27-24-26-01
	eClass	6	27-24-26-01
	ETIM	10	EC001596
	ETIM	9	EC001596
	ETIM	8	EC001596
	ETIM	7	EC001596
	IDEA	4	3562
	UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	

[Miscellaneous](#)

[Manufacturer Declaration](#)



[Declaration of Conformity](#)



General Product Approval		For use in hazardous locations	
RCM	EAC	China RoHS	CCC-Ex
		ATEX	IECEX

For use in hazardous locations		Maritime application			
Miscellaneous	CCC-Ex				
Maritime application			other	Food, Pharmaceutical, Medical	
NK / Nippon Kaiji Kyokai		CCS (China Classification Society)	KR (Korean Register of Shipping)		Confirmation
Environment		Industrial Communication			
		PROFINET			

last modified: 5/15/2026 