



Figure similar

SIPLUS S7-1200 SM 1222 16DQ RLY based on 6ES7222-1HH32-0XB0 with conformal coating, -40...+70 °C, start up -25 °C, digital output 16 DQ, relay 2 A

General information	
Product type designation	SM 1222, DQ 16x relay/2 A
based on	6ES7222-1HH32-0XB0
Supply voltage	
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
from backplane bus 5 V DC, max.	135 mA
Digital outputs	
from load voltage L+, max.	11 mA/relay coil
Power loss	
Power loss, typ.	8.5 W
Digital outputs	
Number of digital outputs	16
in groups of	1
Short-circuit protection	No; to be provided externally
Switching capacity of the outputs	
with resistive load, max.	2 A
on lamp load, max.	30 W with DC, 200 W with AC
Output voltage	
Rated value (DC)	5 V DC to 30 V DC
Rated value (AC)	5 V AC to 250 V AC
Output current	
for signal "1" rated value	2 A
Output delay with resistive load	
"0" to "1", max.	10 ms
"1" to "0", max.	10 ms
Total current of the outputs (per group)	
horizontal installation	
— up to 50 °C, max.	10 A; Current per mass
Relay outputs	
Number of relay outputs	16
Rated supply voltage of relay coil L+ (DC)	24 V
Number of operating cycles, max.	mechanically 10 million, at rated load voltage 100 000
Switching capacity of contacts	
— with inductive load, max.	2 A
— on lamp load, max.	30 W with DC, 200 W with AC
— with resistive load, max.	2 A

Cable length	
• shielded, max.	500 m
• unshielded, max.	150 m
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	Yes
Diagnostics indication LED	
• for status of the outputs	Yes
Potential separation	
Potential separation digital outputs	
• between the channels	Relays
• between the channels, in groups of	4
• between the channels and backplane bus	1 500 V AC for 1 minute
Permissible potential difference	
between different circuits	750 V AC for 1 minute
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
Ecological footprint	
• environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	68.6 kg
— global warming potential, (during production) [CO2 eq]	8.16 kg
— global warming potential, (during operation) [CO2 eq]	60.7 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.334 kg
Ambient conditions	
Free fall	
• Fall height, max.	0.3 m; five times, in product package
Ambient temperature during operation	
• min.	-40 °C; = Tmin (incl. condensation/frost); start-up @ -25 °C
• max.	70 °C; = Tmax; Tmax > +60 °C number of simultaneously activated outputs 8 (no adjacent points) for horizontal mounting position
• At cold restart, min.	-25 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m); above 2 000 m max. 132 V AC
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity

60721-3-6	degree 3); *																																													
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *																																													
Usage in industrial process technology																																														
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)																																													
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)																																													
Remark																																														
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!																																													
Conformal coating																																														
• Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high reliability																																													
• Protection against fouling acc. to EN 60664-3	Yes; Type 1 protection																																													
• Military testing according to MIL-I-46058C, Amendment 7	Yes; Discoloration of coating possible during service life																																													
• Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A																																													
Connection method																																														
required front connector	Yes																																													
Mechanics/material																																														
Enclosure material (front)																																														
• Plastic	Yes																																													
Dimensions																																														
Width	45 mm																																													
Height	100 mm																																													
Depth	75 mm																																													
Weights																																														
Weight, approx.	260 g																																													
Classifications																																														
	<table><tr><th></th><th>Version</th><th>Classification</th></tr><tr><td>eClass</td><td>16</td><td>27-24-22-04</td></tr><tr><td>eClass</td><td>14</td><td>27-24-22-04</td></tr><tr><td>eClass</td><td>12</td><td>27-24-22-04</td></tr><tr><td>eClass</td><td>9.1</td><td>27-24-22-04</td></tr><tr><td>eClass</td><td>9</td><td>27-24-22-04</td></tr><tr><td>eClass</td><td>8</td><td>27-24-22-04</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-22-04</td></tr><tr><td>eClass</td><td>6</td><td>27-24-22-04</td></tr><tr><td>ETIM</td><td>10</td><td>EC001419</td></tr><tr><td>ETIM</td><td>9</td><td>EC001419</td></tr><tr><td>ETIM</td><td>8</td><td>EC001419</td></tr><tr><td>ETIM</td><td>7</td><td>EC001419</td></tr><tr><td>IDEA</td><td>4</td><td>3566</td></tr><tr><td>UNSPSC</td><td>15</td><td>32-15-17-05</td></tr></table>		Version	Classification	eClass	16	27-24-22-04	eClass	14	27-24-22-04	eClass	12	27-24-22-04	eClass	9.1	27-24-22-04	eClass	9	27-24-22-04	eClass	8	27-24-22-04	eClass	7.1	27-24-22-04	eClass	6	27-24-22-04	ETIM	10	EC001419	ETIM	9	EC001419	ETIM	8	EC001419	ETIM	7	EC001419	IDEA	4	3566	UNSPSC	15	32-15-17-05
	Version	Classification																																												
eClass	16	27-24-22-04																																												
eClass	14	27-24-22-04																																												
eClass	12	27-24-22-04																																												
eClass	9.1	27-24-22-04																																												
eClass	9	27-24-22-04																																												
eClass	8	27-24-22-04																																												
eClass	7.1	27-24-22-04																																												
eClass	6	27-24-22-04																																												
ETIM	10	EC001419																																												
ETIM	9	EC001419																																												
ETIM	8	EC001419																																												
ETIM	7	EC001419																																												
IDEA	4	3566																																												
UNSPSC	15	32-15-17-05																																												
Approvals / Certificates																																														
General Product Approval																																														
Manufacturer Declaration  EG-Konf.  China RoHS  UL 																																														
General Product Approval	EMV	Maritime application																																												

[China RoHS](#)



Environment



last modified:

10/9/2024