



SIMATIC S7-1500, F-analog input module, F-AI 8xI 0(4)...20 mA PROFIsafe; 35 mm, overall width; up to PL e (ISO 13849-1)/ SIL 3 (IEC 61508)

General information	
Product type designation	F-AI 8xI 0(4) ... 20 mA
Firmware version	
• FW update possible	Yes
Product function	
• I&M data	Yes; I&M0 to I&M3
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V18 with HSP0394 (FW V1.0) / V19 with HSP0451 (FW V2.0)
Operating mode	
• MSI	Yes; firmware V2.0 or higher
CiR - Configuration in RUN	
Reparameterization possible in RUN	No
Calibration possible in RUN	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	75 mA
Current consumption, max.	2.5 A; All channels are supplied from the encoder supply
Encoder supply	
Number of outputs	8
Short-circuit protection	Yes
24 V encoder supply	
• 24 V	Yes; min. L+ (-1.5 V)
• Short-circuit protection	Yes
• Output current per channel, max.	300 mA
Power	
Power consumption from the backplane bus	0.5 W
Power loss	
Power loss, typ.	2.5 W
Address area	
Address space per module	
• Inputs	23 byte
• Outputs	6 byte
Hardware configuration	
Automatic encoding	Yes

Analog inputs	
Number of analog inputs	8
permissible input current for current input (destruction limit), max.	35 mA
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	150 Ω
• 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	150 Ω
Cable length	
• shielded, max.	1 000 m
Analog value generation for the inputs	
Measurement principle	Sigma Delta
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Integration time, parameterizable	Yes
• Integration time (ms)	20 / 16,667
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz
Smoothing of measured values	
• Number of smoothing levels	7
• Parameterizable	Yes
• Step: None	Yes; 1x conversion time
• Step: low	Yes; 2x / 4x conversion cycle time
• Step: Medium	Yes; 8x / 16x conversion cycle time
• Step: High	Yes; 32x / 64x conversion cycle time
Encoder	
Connection of signal encoders	
• for current measurement as 2-wire transducer	Yes
— Burden of 2-wire transmitter, max.	650 Ω
• for current measurement as 4-wire transducer	Yes
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.05 %
Temperature error (relative to input range), (+/-)	0.005 %/K
Crosstalk between the inputs, max.	-70 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %
Operational error limit in overall temperature range	
• Current, relative to input range, (+/-)	0.3 %; without HART communication
Basic error limit (operational limit at 25 °C)	
• Current, relative to input range, (+/-)	0.05 %; without HART communication
Influence of a HART signal modulated on the input signal in relation to input range	
• error occurred at interference frequency suppression: 60 Hz	0.12 %
• error occurred at interference frequency suppression: 50 Hz	0.12 %
Interference voltage suppression for $f = n \times (f1 \pm 1 \%)$, f1 = interference frequency	
• Series mode interference (peak value of interference < rated value of input range), min.	40 dB
• Common mode voltage, max.	60 V DC/30 V AC
• Common mode interference, min.	70 dB
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
• Limit value alarm	No
Diagnoses	
• Monitoring the supply voltage	Yes
• Wire break	Yes
• Short-circuit	Yes

• Overflow/Underflow	Yes		
Diagnostics indication LED			
• RUN LED	Yes; green LED		
• ERROR LED	Yes; red LED		
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED		
• Channel status display	Yes; green LED		
• for channel diagnostics	Yes; red LED		
Potential separation			
Potential separation analog inputs			
• between the channels	No		
• between the channels, in groups of	4		
• between the channels and backplane bus	Yes		
• between the channels and the power supply of the electronics	Yes		
Permissible potential difference			
between the inputs (UCM)	60 V DC/30 V AC		
Isolation			
Isolation tested with	707 V DC (type test)		
Standards, approvals, certificates			
Highest safety class achievable in safety mode			
• Performance level according to ISO 13849-1	PLe		
• Category according to ISO 13849-1	Cat. 4		
• SIL acc. to IEC 61508	SIL 3		
Probability of failure (for service life of 20 years and repair time of 100 hours)			
— Low demand mode: PFDavg in accordance with SIL3	< 4.00E-05		
— High demand/continuous mode: PFH in accordance with SIL3	< 1.00E-09 1/h		
Ambient conditions			
Ambient temperature during operation			
• horizontal installation, min.	0 °C		
• horizontal installation, max.	60 °C		
• vertical installation, min.	0 °C		
• vertical installation, max.	40 °C		
Dimensions			
Width	35 mm		
Height	147 mm		
Depth	129 mm		
Weights			
Weight, approx.	290 g		
Classifications			
		Version	Classification
	eClass	16	27-24-22-01
	eClass	14	27-24-22-01
	eClass	12	27-24-22-01
	eClass	9.1	27-24-22-01
	eClass	9	27-24-22-01
	eClass	8	27-24-22-01
	eClass	7.1	27-24-22-01
	eClass	6	27-24-22-01
	ETIM	10	EC001420
	ETIM	9	EC001420
	ETIM	8	EC001420
	ETIM	7	EC001420
Approvals / Certificates			
General Product Approval			



[Miscellaneous](#)



General Product Approval	For use in hazardous locations
--------------------------	--------------------------------

[China RoHS](#)



[FM](#)

[CCC-Ex](#)



[Type Examination Certificate](#)

For use in hazardous locations	Functional Safety	Maritime application
--------------------------------	-------------------	----------------------



[Miscellaneous](#)

[CCC-Ex](#)

[TUEV](#)

[Type Examination Certificate](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

Maritime application	other
----------------------	-------

[KR \(Korean Register of Shipping\)](#)

[PROFIsafe](#)

last modified:

10/23/2025