



SIMATIC ET 200SP, server module for BaseCarrier pack quantity: 1 unit,

General information			
Product type designation		server modules for BaseCarrier	
HW functional status		from FS01	
Input current			
Current consumption, max.		30 mA	
Ambient conditions			
Ambient temperature during operation			
• min.		No condensation	
• horizontal installation, min.		-30 °C	
• horizontal installation, max.		60 °C	
• vertical installation, min.		-30 °C	
• vertical installation, max.		50 °C	
Altitude during operation relating to sea level			
• Installation altitude above sea level, max.		5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual	
Dimensions			
Width		15 mm	
Height		73 mm	
Depth		58 mm	
Weights			
Weight, approx.		25 g	
Classifications			
		Version	Classification
	eClass	16	27-24-26-92
	eClass	14	27-24-26-92
	eClass	12	27-24-26-92
	eClass	9.1	27-24-26-92
	eClass	9	27-24-26-92
	eClass	8	27-24-26-92
	eClass	7.1	27-24-26-92
	eClass	6	27-24-26-92
	ETIM	10	EC002584
	ETIM	9	EC002584
	ETIM	8	EC002584
	ETIM	7	EC002584
Approvals / Certificates			
General Product Approval			

[Manufacturer Declaration](#)



EMV

For use in hazardous locations



[CCC-Ex](#)

[EM](#)



[Type Examination Certificate](#)

For use in hazardous locations

[Miscellaneous](#)



[CCC-Ex](#)

last modified:

6/22/2026 