



Technical Data

H/OFF :	120°C ± 3°C
L/OFF :	30°C
BREAKING CAPACITY	C-1 15(2,5)A 400 VAC C-2 2,5(0,4)A 400VAC
MAX °C AROUND THE BODY:	T110°C
MAX °C AROUND THE BULB:	UPPER SWITCHING VALUE +15%
LIFE OF PRODUCTS:	100.000 CYCLES
DIFFERENTIAL:	4 ± 2°C
MINIMUM CURRENT:	200 mA
INSULATION RESISTANCE:	> 100 M OHM
RIF.	120C-556-12A



DESCRIZIONE :
Termostato reg. 30/120°C SP-DT cap. mm 1500 frame Faston 6,3 X 0,8

SCALA :	1 : 2	DESCRIZIONE :	Termostato reg. 30/120°C SP-DT cap. mm 1500 frame Faston 6,3 X 0,8
DATA :	28-10-2003	DISSEGNA TO:	SALA A.
TOLL. GEN. :	+/-0,1	MODIFICA :	DATA:
Descrizione revisione :			
Descrizione revisione :			
Descrizione revisione :			

TERMOSTATO COMPLETO DI ACCESSORI (MANOPOLA - GHIERA E VITI)
COD. C702003235N