



ELECTRIC DIAGRAM _S.P.D.T.

Technical Data	
H/OFF :	315°C ±12°C
L/OFF :	50°C
BREAKING CAPACITY	C-1 16(2,6)A 250 VAC - C-2 3(0,5)A 250 VAC
MAX °C AROUND THE BODY:	T150°C
MAX °C AROUND THE BULB:	UPPER SWITCHING VALUE +15%
LIFE OF PRODUCTS:	60.000 CYCLES
DIFFERENTIAL:	10 ± 6 °C
INSULATION ANDVOLTAGE RES.:	2000 V / MIN.
INSULATION RESISTANCE:	> 500 M OHM
RIF.:	.

ARTHERMO

DESCRIZIONE :
Termostato reg. 50/315°C SP-DT cap.mn 1500 inox capillary fashon 6,3 X 0,8

TERMOSTATO COMPLETO DI ACCESSORI (MANOPOLA - GHIERA E VITI)
COD. C713202530N

SCALA : 1 : 1
DISEGNATO: SALA A.
MODIFICA : DATA:

DATA : 04/11/2010
CONTROLLATO: SALA A.

TOLL.GEN. : +/-0,1

Descrizione revisione :

Data

Descrizione revisione :

Data

Descrizione revisione :

Data