



## MATERIAL FACT SHEET

### 283559 FX5-4AD-ADP

#### General Data

Product Hierarchy	IAD21703
	Compact PLC
	FX5 Intelligent Unit
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	A (Available from Stock)

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IA/EUR/en/p/000000000000283559](https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000283559)

#### FA-COM PLC: Analogue I/O Module

Series	MELSEC IQ-F SERIES
Type	ANALOG INPUT
Power Supply (V)	24
Current Type	DC
Integrated Analogue Inputs	4
Input Voltage Range (V)	-10-10; 0-10; 0-5; 1-5
Input Current Range (mA)	-20-20; 0-20; 4-20
Min. Ambient Temperature (°C)	0
Max. Ambient Temperature (°C)	55

#### Product Dimensions & Weight

Width (mm)	17,6
Height (mm)	106
Depth (mm)	89,1
Weight (kg)	0,1

#### Logistic Dimensions & Gross Weight

Length (cm)	11,5
Width (cm)	11,0
Height (cm)	4,5
Gross Weight (kg)	0,150
Volume (cdm)	0,569

#### Stock Data

Planned Delivery Time (Days)	296
------------------------------	-----

#### Life Cycle

Sales Start	23.02.2015
Predecessor	No Predecessor

#### Additional Product Information

Binding Tariff Information	DEBTI-10745/21-1
BTI validity date	09.09.2024

#### Export Data

Commodity Code	85389099
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

#### Environmental

REACH Limit Exceeded	NO
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

**Conformity**

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	COMPLIANT
Shipping Approvals	ABS,BV,DNV GL,KR,LR,NK,RINA
UKCA	COMPLIANT

**Documentation & Media Data**

Manual URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=FX5-4AD-ADP&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=FX5-4AD-ADP&amp;doc-lang=en</a>
Certificates URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=FX5-4AD-ADP&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=FX5-4AD-ADP&amp;doc-lang=en</a>
CAD URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=FX5-4AD-ADP&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=FX5-4AD-ADP&amp;doc-lang=en</a>

**Product Packaging**

Cardboard (g)	88
Other paper (g)	0
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	0
Wood (g)	0
Glass (g)	0
Others (g)	0