

Ordering

Contact sequence	Front plate no.	Main contacts	Auxiliary contacts	Max. motor rating AC-23 A, 400/415 V, 50/60 Hz	Rated uninterrupted current	Flush mounting Front IP65	Part no. Article no.	Price See price list	Std. pack
		Pole N/O	N/O	400 V P kW	I _u A				
Main switch as emergency switching off/emergency stop device									
With red rotary handle and yellow locking collar To IEC/EN 60204-1, VDE 0113 Part 1 Lockable in the 0 (Off) position									
Without auxiliary contacts									
		1	0	6.5	20		T0-1-8200/EA/SVB 053110		1 Off
				13	32		T3-1-8200/EA/SVB¹⁾ 066576		
				22	63		T5B-1-8200/EA/SVB³⁾ 094279		
		2	0	6.5	20		T0-1-102/EA/SVB¹⁾ 091078		
				13	32		T3-1-102/EA/SVB¹⁾ 014374		
				22	63		T5B-1-102/EA/SVB³⁾ 094469		
				30	100		T5-1-102/EA/SVB 098808		1 Off
		3	0	6.5	20		T0-2-1/EA/SVB¹⁾ 038873		1 Off
				13	25		P1-25/EA/SVB¹⁾ 041097		
				13	25				
				15	32		P1-32/EA/SVB¹⁾ 081438		
				37	63		P3-63/EA/SVB¹⁾ 031607		
				45	125		P5-125/EA/SVB⁴⁾ 280898		
				50	100		P3-100/EA/SVB¹⁾ 074320		
				55	160		P5-160/EA/SVB⁴⁾ 280922		
				90	250		P5-250/EA/SVB⁴⁾ 280936		
				110	315		P5-315/EA/SVB⁴⁾ 280950		
		3 + N	0	6.5	20		T0-2-8900/EA/SVB¹⁾ 207400		1 Off
		3 + N	0	13	25		P1-25/EA/SVB/N¹⁾ 081587		
				13	25				
				15	32		P1-32/EA/SVB/N¹⁾ 091079		
				15	32				
				37	63		P3-63/EA/SVB/N¹⁾ 010398		
				45	125		P5-125/EA/SVB/N⁴⁾ 280910		
				50	100		P3-100/EA/SVB/N¹⁾ 019890		
				55	160		P5-160/EA/SVB/N⁴⁾ 280924		

Surface mounting IP65	Price See price list	Std. pack	Rear mounting Front IP65	Price See price list	Std. pack	Information relevant for export to North America
T0-1-8200/11/SVB 207145		1 Off	T0-1-8200/V/SVB 057856		1 Off	1) Product Standards UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No. E36332 UL CCN NLRV CSA File No. 12528 CSA Class No. 3211-05 NA Certification UL Listed, CSA certified Suitable for Branch circuits, suitable as motor disconnect Degree of Protection IEC: IP65; UL/CSA Type 3R, 12
T3-1-8200/12/SVB²⁾ 207200		1 Off	T3-1-8200/V/SVB¹⁾ 007255		1 Off	
T5B-1-8200/14/SVB³⁾ 207240		1 Off	T5B-1-8200/V/SVB³⁾ 094273		1 Off	
T0-1-102/11/SVB 207143		1 Off	T0-1-102/V/SVB¹⁾ 095824		1 Off	
T3-1-102/12/SVB²⁾ 207198		1 Off	T3-1-102/V/SVB¹⁾ 019120		1 Off	2) Product Standards UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94; IEC/EN 60947-3; CE marking UL File No. E36332 UL CCN NLRV CSA File No. 12528 CSA Class No. 3211-05 NA Certification UL Listed, CSA certified Suitable for Branch circuits, suitable as motor disconnect Degree of Protection IEC: IP65; UL/CSA Type 3R, 12
T5B-1-102/14/SVB³⁾ 207238		1 Off	T5B-1-102/V/SVB³⁾ 094463		1 Off	
T5-1-102/15/SVB 207273		1 Off			1 Off	
T0-2-1/11/SVB 207147		1 Off	T0-2-1/V/SVB¹⁾ 043619		1 Off	
P1-25/12/SVB²⁾ 207293		1 Off	P1-25/V/SVB²⁾ 055335		1 Off	3) Product Standards UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No. E36332 UL CCN NLRV CSA File No. 12528 CSA Class No. 3211-05 NA Certification UL Listed, CSA certified Suitable for Branch circuits, suitable as motor disconnect Degree of Protection IEC: IP65; UL/CSA Type 3R, 12
P1-25/12H/SVB 226900		1 Off			1 Off	
P1-32/12/SVB²⁾ 207314		1 Off	P1-32/V/SVB¹⁾ 095676		1 Off	
P3-63/14/SVB¹⁾ 207343		1 Off	P3-63/V/SVB¹⁾ 048218		1 Off	
P3-100/15/SVB¹⁾ 207373		1 Off	P5-125/V/SVB⁴⁾ 280914		1 Off	4) Product Standards UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No. E36332 UL CCN NLRV, NLRV7 CSA File No. 223805 CSA Class No. 3211-05 NA Certification UL Listed, CSA certified Suitable for Branch circuits, suitable as motor disconnect Degree of Protection IEC: IP65; UL/CSA Type 3R, 12
T0-2-8900/11/SVB 207151		1 Off	T0-2-8900/V/SVB¹⁾ 207405		1 Off	
P1-25/12/SVB/N²⁾ 207298		1 Off	P1-25/V/SVB/N²⁾ 086333		1 Off	
P1-25/12H/SVB/N 227860		1 Off			1 Off	
P1-32/12/SVB/N²⁾ 207319		1 Off	P1-32/V/SVB/N¹⁾ 095825		1 Off	4) Product Standards UL 508; CSA-C22.2 No. 14-05; IEC/EN 60947-3; CE marking UL File No. E36332 UL CCN NLRV, NLRV7 CSA File No. 223805 CSA Class No. 3211-05 NA Certification UL Listed, CSA certified Suitable for Branch circuits, suitable as motor disconnect Degree of Protection IEC: IP65; UL/CSA Type 3R, 12
P1-32/12H/SVB/N 227871		1 Off			1 Off	
P3-63/14/SVB/N¹⁾ 207349		1 Off	P3-63/V/SVB/N¹⁾ 015144		1 Off	
P3-100/15/SVB/N¹⁾ 207379		1 Off	P5-125/V/SVB/N⁴⁾ 280916		1 Off	
			P3-100/V/SVB/N¹⁾ 024636		1 Off	
			P5-160/V/SVB/N⁴⁾ 280930		1 Off	