

Product view	For use with	Part no. Article no. when ordered separately	Price See price list	Std. pack	Notes
Door coupling rotary handles					
Complete including rotary drive and coupling parts An additional extension shaft is necessary with the NZM...-XT(V)D(V)(R)(-60) part numbers. Degree of protection IP66/UL/CSA type 4X, 12					
Standard, black/grey					
	Lockable in 0 position on handle with up to 3 padlocks. With door interlock.	NZM1(-4), PN1(-4), N(S)1(-4)	NZM1-XTVD 260166	1 off	Door interlock <ul style="list-style-type: none"> • Not defeated in the locked OFF and ON positions • Can be modified such that it can be defeated from the outside using a screwdriver, when it is in the unlocked ON position. • Door can be opened in OFF NZM...-XTVD(V) <ul style="list-style-type: none"> • External warning plate/designation label can be clipped on
		NZM2(-4), PN2(-4), N(S)2(-4)	NZM2-XTVD 260168		
		NZM3(-4), PN3(-4), N(S)3(-4)	NZM3-XTVD 260170		
		NZM4(-4), N(S)4(-4)	NZM4-XTVD 266614		
	Lockable on handle and switch with up to 3 padlocks. Can be locked in 0 position, with adequate modification also in I position. With door interlock. Lockable on switch in 0 position.	NZM1(-4), PN1(-4), N(S)1(-4)	NZM1-XTVDV 260172		
		NZM2(-4), PN2(-4), N(S)2(-4)	NZM2-XTVDV 260174		
		NZM3(-4), PN3(-4), N(S)3(-4)	NZM3-XTVDV 260176		
		NZM4(-4), N(S)4(-4)	NZM4-XTVDV 266616		
Red-yellow for emergency switching off					
	Lockable on handle and switch with up to 3 padlocks. Lockable in 0 position on handle. With door interlock. Lockable on switch in 0 position.	NZM1(-4), PN1(-4), N(S)1(-4)	NZM1-XTVDVR 260178	1 off	Door interlock <ul style="list-style-type: none"> • Not defeated in the locked OFF position. • Can be modified such that it can be defeated from the outside using a screwdriver, when it is in the unlocked ON position. • Door can be opened in OFF NZM...-XTVDVR <ul style="list-style-type: none"> • External warning plate/designation label can be clipped on
		NZM2(-4), PN2(-4), N(S)2(-4)	NZM2-XTVDVR 260180		
		NZM3(-4), PN3(-4), N(S)3(-4)	NZM3-XTVDVR 260182		
		NZM4(-4), N(S)4(-4)	NZM4-XTVDVR 266618		
Extension shaft					
	400 mm max. mounting depth	NZM1(-4), PN1(-4), N(S)1(-4) NZM2(-4), PN2(-4), N(S)2(-4) NZM3(-4), PN3(-4), N(S)3(-4) NZM4(-4), N(S)4(-4)	NZM1/2-XV4 261232 NZM3/4-XV4 261234	1 off	Length 290 mm, can be cut to required length.
	600 mm max. mounting depth	NZM1(-4), PN1(-4), N(S)1(-4) NZM2(-4), PN2(-4), N(S)2(-4) NZM3(-4), PN3(-4), N(S)3(-4) NZM4(-4), N(S)4(-4)	NZM1/2-XV6 260191 NZM3/4-XV6 260193		Length 425 mm, can be cut to required length.
Notes Circuit-breaker can also be installed in a horizontal position 90° left/right, with the handle still in the same position.					

For maximum shaft length 60 mm	Part no. Article no. when ordered separately	Price See price list	Std. pack	Notes	Extremely narrow fittings	Part no. Article no. when ordered separately	Price See price list	Std. pack	Notes	Information relevant for export to North America
	NZM1-XTVD-60 271504		1 off	Door interlock <ul style="list-style-type: none"> • Can not be defeated in the locked OFF and ON positions • Can be modified such that it can be defeated from the outside using a screwdriver, when it is in the unlocked ON position. • Door can be opened in OFF NZM...-XTVD(V)-60 <ul style="list-style-type: none"> • For maximum shaft length 60 mm • Without shaft support • Cannot be combined with additional handle NZM...-XDZ • External warning plate/designation label can be clipped on. 		NZM1-XTVD-0 279392		1 off	Door interlock <ul style="list-style-type: none"> • Can not be defeated in the locked OFF and ON positions • Can be modified such that it can be defeated from the outside using a screwdriver, when it is in the unlocked ON position. • Door can be opened in OFF NZM...-XTVD(V)-0 <ul style="list-style-type: none"> • For extremely narrow fittings • With special short extension shaft • Cannot be combined with additional handle NZM...-XDZ • External warning plate/designation label can be clipped on. 	Product Standards UL489; CSA-C22.2 No. 5-09; IEC60947, CE marking UL File No. E140305 UL CCN DIHS CSA File No. 022086 CSA Class No. 1437-01 NA Certification UL Listed, CSA certified Degree of Protection IEC: IP66, UL/CSA Type 4X, 12
	NZM2-XTVD-60 271505					NZM2-XTVD-0 279393				
	NZM3-XTVD-60 271506					NZM3-XTVD-0 279394				
	NZM4-XTVD-60 271507					NZM4-XTVD-0 279395				
	NZM1-XTVDV-60 271508					NZM1-XTVDV-0 279396				
	NZM2-XTVDV-60 271509					NZM2-XTVDV-0 279397				
	NZM3-XTVDV-60 271510					NZM3-XTVDV-0 279398				
	NZM4-XTVDV-60 271511					NZM4-XTVDV-0 279399				
	NZM1-XTVDVR-60 271512		1 off	Door interlock <ul style="list-style-type: none"> • Can not be defeated in the locked OFF position. • Can be modified such that it can be defeated from the outside using a screwdriver, when it is in the unlocked ON position. • Door can be opened in OFF NZM...-XTVDVR-60 <ul style="list-style-type: none"> • For maximum shaft length 60 mm • Without shaft support • Cannot be combined with additional handle NZM...-XDZ • External warning plate/designation label can be clipped on. 		NZM1-XTVDVR-0 279400		1 off	Door interlock <ul style="list-style-type: none"> • Can not be defeated in the locked OFF position. • Can be modified such that it can be defeated from the outside using a screwdriver, when it is in the unlocked ON position. • Door can be opened in OFF NZM...-XTVDVR-0 <ul style="list-style-type: none"> • For extremely narrow fittings • With special short extension shaft • Cannot be combined with additional handle NZM...-XDZ • External warning plate/designation label can be clipped on. 	UL/CSA certification not required
	NZM2-XTVDVR-60 271513					NZM2-XTVDVR-0 279401				
	NZM3-XTVDVR-60 271514					NZM3-XTVDVR-0 279402				
	NZM4-XTVDVR-60 271515					NZM4-XTVDVR-0 279403				