

SYSTEM D0

RATED VOLTAGE
~ 400V

D01UQ6A



D02UQ50A



Technical data:

Standards:
IEC 60269-4-1
VDE 0636

Breaking capacity:
~ 50kA / --- 8kA
Rated voltage:
~ 400V / --- 250V

Characteristic:
gR

Application:

Fuse-links of system D0 are applied in fuse base E14 and E18 and fuse-switch disconnectors VLDO1 and STV D02.

Size	In (A)	Type	Code No.	Operating I ² t-value (A ² s)	Power dissipation (W)	Char.	Colour	Dimension A	Packaging (pcs)	Weight (g)
D01	2	D01UQ2A	004311001	6.3	2.3	gR	pink	7.3	10/500	6
	4	D01UQ4A	004311002	13	3.1	gR	brown	7.3	10/500	6
	6	D01UQ6A	004311003	20	4.0	gR	green	7.3	10/500	6
	10	D01UQ10A	004311004	65	4.2	gR	red	8.5	10/500	6
	16	D01UQ16A	004311005	200	5.3	gR	grey	9.7	10/500	6
D02	20	D02UQ20A	004312001	275	8.0	gR	blue	10.9	10/500	11
	25	D02UQ25A	004312002	480	9.0	gR	brown	12.1	10/500	12
	35	D02UQ35A	004312003	1.000	10.0	gR	black	13.3	10/500	13
	50	D02UQ50A	004312004	1.800	15.0	gR	white	14.5	10/500	13
	63	D02UQ63A	004312005	2.500	17.0	gR	copper	15.9	10/500	15

Dimensions:

