

TeSys VARIO - auxiliary contact block - 1 NC early-break+1 NO latemake

VZ7

Product availability: Stock - Normally stocked in distribution

Price*: 42.80 USD

Main	
Range	TeSys
Device short name	VZ
Product or Component Type	Auxiliary contact block
Performance level	High performance
Contacts type and composition	1 NO + 1 NC
Contact operation	Late-make 1 NO Early-break 1 NC
Product Compatibility	V2 V5 V02 V6 V1 V4 V01 V0
Network type	AC DC
Network Frequency	50/60 Hz

Complementary

- Compromontary	
Mounting Location	Right
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	12 A
[Ithe] conventional enclosed thermal current	10 A
Mechanical durability	100000 cycles
Electrical durability	30000 cycles DC-11 100000 cycles AC-15
Connections - terminals	screw clamp terminals 2 0.000.00 in² (0.751.5 mm²) flexible - with cable end screw clamp terminals 2 0.000.00 in² (12.5 mm²) solid
Tightening torque	6.20 lbf.in (0.7 N.m) screw clamp terminals
Height	2.56 in (65 mm)

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Width	0.79 in (20 mm)
Depth	1.91 in (48.5 mm)
Net Weight	0.11 lb(US) (0.05 kg)

Environment

Standards	IEC 60947-5
Product Certifications	GL CSA UL UKCA
Protective treatment	TC
IP degree of protection	IP20 conforming to IEC 60529
Ambient Air Temperature for Operation	-4122 °F (-2050 °C)
Fire resistance	1760 °F (960 °C) IEC 60695-2-1

Ordering and shipping details

Category	21730-V VARIO SWITCH
Discount Schedule	CP1
GTIN	3389110551969
Returnability	Yes
Country of origin	CZ

Packing Units

r deking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.17 in (5.5 cm)
Package 1 Width	1.46 in (3.7 cm)
Package 1 Length	3.54 in (9.0 cm)
Package 1 Weight	1.83 oz (52.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	69
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	8.67 lb(US) (3.931 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes
Halogen content performance	Halogen free product
Contractual warranty	
Warranty	18 months

Recommended replacement(s)