



TeSys VARIO - additional neutral block - 175 A - for V5 / V6

VZ13

Product availability: Stock - Normally stocked in distribution

Price*: 70.00 USD

| Range | TeSys | | |
|-------------------------------|---|--|--|
| Device short name | VZ | | |
| Product or Component Type | Additional neutral block | | |
| Performance level | High performance | | |
| Poles description | 1N | | |
| Contacts type and composition | 1 NO | | |
| Contact operation | Early make, late break | | |
| Product Compatibility | V5 V6 | | |
| Range compatibility | TeSys (TeSys VARIO) switch disconnector | | |
| Network type | AC DC | | |
| Network Frequency | 50/60 Hz | | |

| Complementary | | | |
|---|---|--|--|
| Mounting Location | Right Left | | |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz | | |
| [Uimp] rated impulse withstand voltage | 6 kV | | |
| [Ith] conventional free air thermal current | 175 A | | |
| Mechanical durability | 30000 cycles | | |
| Electrical durability | 30000 cycles DC-15 30000 cycles AC-21 | | |
| Connections - terminals | screw clamp terminals 0.11 in² (70 mm²) flexible - with cable end screw clamp terminals 0.15 in² (95 mm²) solid | | |
| Tightening torque | 200.03 lbf.in (22.6 N.m) screw clamp terminals | | |
| Height | 4.92 in (125 mm) | | |
| Width | 1.18 in (30 mm) | | |
| Depth | 2.48 in (63 mm) | | |
| Net Weight | 0.55 lb(US) (0.25 kg) | | |

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

| Standards | IEC 60947-3 | | |
|---------------------------------------|---|--|--|
| Product Certifications | UL CSA GL UKCA | | |
| Protective treatment | TC | | |
| IP degree of protection | IP20 conforming to IEC 60529 | | |
| Mechanical robustness | Vibrations 10150 Hz 1 gn) IEC 60068-2-6 Shocks 11 ms 15 gn) IEC 60068-2-27 | | |
| Ambient Air Temperature for Operation | -4122 °F (-2050 °C) | | |
| Fire resistance | 1760 °F (960 °C) IEC 60695-2-1 | | |

Ordering and shipping details

| Category | 21730-V VARIO SWITCH | | |
|-------------------|----------------------|--|--|
| Discount Schedule | CP1 | | |
| GTIN | 3389110551921 | | |
| Returnability | No | | |
| Country of origin | CZ | | |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|------------------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.95 in (7.5 cm) |
| Package 1 Width | 2.76 in (7.0 cm) |
| Package 1 Length | 4.72 in (12.0 cm) |
| Package 1 Weight | 9.07 oz (257.0 g) |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 30 |
| Package 2 Height | 11.81 in (30.0 cm) |
| Package 2 Width | 11.81 in (30.0 cm) |
| Package 2 Length | 15.75 in (40.0 cm) |
| Package 2 Weight | 18.06 lb(US) (8.19 kg) |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|--|--|
| | | |
| REACh Regulation | REACh Declaration | |
| EU RoHS Directive | Compliant EU RoHS Declaration | |
| Mercury free | Yes | |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information. | |
| RoHS exemption information | Yes | |
| Environmental Disclosure | Product Environmental Profile | |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. | |

| PVC free | Yes | |
|-----------------|-----------|--|
| Contractual war | ranty | |
| Warranty | 18 months | |

Recommended replacement(s)