



## MATERIAL FACT SHEET

### 315551 FX5UC-32MT/DSS-TS

#### General Data

Product Hierarchy	IAD21701
	Compact PLC
	FX5U CPU
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	A (Available from Stock)

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IA/EUR/en/p/000000000000315551](https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000315551)

#### FA-COM PLC: Main Unit

Series	MELSEC IQ-F SERIES
Type	FX5UC
Power Supply (V)	24
Current Type	DC
Program Memory	64K STEPS
Program Memory Unit	FLASH
Integrated Digital Inputs	16
Integrated Digital Outputs	16
Output Type	TRANSISTOR
Output Logic	SOURCE
Local I/O Points	256
Local + Remote I/O Points	512
Expandable	YES
Cycle Time LD (ns)	34
Cycle Time MOV (ns)	34
Ethernet Port	1
RS-485	1
Power Consumption (W)	5
Buffer Battery	OPTION
Protection Class	IP10
Min. Ambient Temperature (°C)	0
Max. Ambient Temperature (°C)	55

#### Product Dimensions & Weight

Width (mm)	48,1
Height (mm)	90
Depth (mm)	93,7
Weight (kg)	0,25

#### Logistic Dimensions & Gross Weight

Length (cm)	14,0
Width (cm)	11,0
Height (cm)	10,0
Gross Weight (kg)	0,318
Volume (cdm)	1,540

#### Stock Data

Planned Delivery Time (Days)	212
------------------------------	-----

#### Life Cycle

Sales Start	01.09.2017
Predecessor	No Predecessor

#### Additional Product Information

Binding Tariff Information	DEBTI-10856/21-1
BTI validity date	10.10.2024

## Export Data

Commodity Code	85371091
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

## Environmental

REACH Limit Exceeded	NO
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

## Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	COMPLIANT
Shipping Approvals	ABS,BV,DNV GL,KR,LR,NK,RINA

## Documentation & Media Data

Manual URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=FX5UC-32MT/DSS-TS&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=FX5UC-32MT/DSS-TS&amp;doc-lang=en</a>
Certificates URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=FX5UC-32MT/DSS-TS&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=FX5UC-32MT/DSS-TS&amp;doc-lang=en</a>
CAD URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=FX5UC-32MT/DSS-TS&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=FX5UC-32MT/DSS-TS&amp;doc-lang=en</a>

## Product Packaging

Cardboard (g)	75
Other paper (g)	0
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	0
Wood (g)	0
Glass (g)	0
Others (g)	0

## Compatible products

Material	Description / Price List Text / Classification
<a href="#">104509</a>	FX2NC-100MPCB PLC, FX Series Power supply cable for FX2NC base unit, 1 m Class 100100110: FA-COM PLC: Cable
<a href="#">104510</a>	FX2NC-100BPCB Cable for 24V DC supply to input units Class 100100110: FA-COM PLC: Cable
<a href="#">104511</a>	FX2NC-10BPCB1 Crossover cable for input units Class 100100110: FA-COM PLC: Cable
<a href="#">165286</a>	FX3U-32BL PLC, FX3U/C Battery Class 100100112: FA-COM PLC: Spare Part
<a href="#">165286</a>	FX3U-32BL PLC, FX3U/C Battery Class 100101303: FA-OTHERS: Battery
<a href="#">278166</a>	SC-E5EW-S45M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor;45m Class 100100214: FA-MOD PLC: Cable
<a href="#">280510</a>	FX5-CNV-BUS FX5;FX3 Bus Conversion Unit Class 100100111: FA-COM PLC: Other Option
<a href="#">283557</a>	FX5-CNV-IFC FX5UC;FX5U Bus Converter Class 100100111: FA-COM PLC: Other Option
<a href="#">283558</a>	FX5-CNV-BUSC FX5UC;FX3 Bus Conversion Unit Class 100100111: FA-COM PLC: Other Option

Material	Description / Price List Text / Classification
<a href="#">284378</a>	GX Works3 V01-2L0C-E PLC Programming-S/W for Melsec iQ-R/iQ- F;engl;USB;2 PC's Class 100101201: FA-Software: Software PLC
<a href="#">284379</a>	GX Works3 V01-5L0C-E PLC Programming-S/W for Melsec iQ-R/iQ- F; engl; USB; 5 PC's Class 100101201: FA-Software: Software PLC
<a href="#">284966</a>	NZ1MEM-2GBSD SD Memory Card; 2 GByte Class 100100215: FA-MOD PLC: Other Option
<a href="#">284967</a>	NZ1MEM-4GBSD SD Memory Card; 4 GByte Class 100100215: FA-MOD PLC: Other Option
<a href="#">284968</a>	NZ1MEM-8GBSD SD Memory Card; 8 GByte Class 100100215: FA-MOD PLC: Other Option
<a href="#">284969</a>	NZ1MEM-16GBSD SD Memory Card; 16 GByte Class 100100215: FA-MOD PLC: Other Option
<a href="#">286227</a>	iQ Works V02-2L0C-E iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;engl;USB;2 PC's Class 100101201: FA-Software: Software PLC
<a href="#">286228</a>	iQ Works V02-5L0C-E iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;engl;USB;5 PC's Class 100101201: FA-Software: Software PLC
291807	SC-E5EW-S1M-MV Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 1m Class 100100214: FA-MOD PLC: Cable
291808	SC-E5EW-S3M-MV Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 3m Class 100100214: FA-MOD PLC: Cable
<a href="#">294586</a>	FX5-C1PS-5V FX5UC;Power Supply Unit 5VDC Bus Class 100100111: FA-COM PLC: Other Option
<a href="#">295425</a>	SC-E5EW-S05M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight;indoor;0,5m Class 100100214: FA-MOD PLC: Cable
<a href="#">295426</a>	SC-E5EW-S1M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 1m Class 100100214: FA-MOD PLC: Cable
<a href="#">295427</a>	SC-E5EW-S3M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 2m Class 100100214: FA-MOD PLC: Cable
<a href="#">297456</a>	FX5-CNV-BC FX5;Bus Extension cable connector Class 100100111: FA-COM PLC: Other Option
<a href="#">297457</a>	FX5-30EC FX5;Bus Extension cable (0,3m) Class 100100110: FA-COM PLC: Cable
<a href="#">297458</a>	FX5-65EC FX5;Bus Extension cable (0,65m) Class 100100110: FA-COM PLC: Cable
<a href="#">303426</a>	iQ Works V02-15L0C-E iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;engl;USB;15 PC's Class 100101201: FA-Software: Software PLC
<a href="#">304614</a>	GX Works3 V01-2L0C-G PLC Programming SW; Melsec iQ-R/iQ- F only (no GXW2/GX Dev); USB; 2 PCs; German Class 100101201: FA-Software: Software PLC
<a href="#">304645</a>	GX Works3 V01-5L0C-G PLC Programming SW; Melsec iQ-R/iQ- F only (no GXW2/GX Dev); USB; 5 PCs; German Class 100101201: FA-Software: Software PLC
<a href="#">308856</a>	GX Works3 V01-2L0C-IT PLC Programming-S/W for Melsec iQ-R/iQ- F;engl;USB;2 PC's; Italian Class 100101201: FA-Software: Software PLC
<a href="#">338821</a>	iQ Works V02-2L0C-G iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;German;USB;2 PC's Class 100101201: FA-Software: Software PLC
<a href="#">339022</a>	iQ Works V02-5L0C-G iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;German;USB;5 PC's Class 100101201: FA-Software: Software PLC

Material	Description / Price List Text / Classification
<a href="#">340984</a>	Transcend SDHC card 16GB Class 10 SDHC memory card 16GB; Class 10; R: 30MB/s; W: 15MB/s Class 100100304: FA-HMI: Other Option
<a href="#">401853</a>	iQ Works V02-2L0C-IT iQ Works V2.0;incl Navigator,GX Works,GT Works,MT Works;Italian;USB;2 PCs Class 100101201: FA-Software: Software PLC
<a href="#">413182</a>	SC-E5EW-S10M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor;10m Class 100100214: FA-MOD PLC: Cable
<a href="#">413183</a>	SC-E5EW-S25M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor;25m Class 100100214: FA-MOD PLC: Cable
<a href="#">413184</a>	SC-E5EW-S5M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 5m Class 100100214: FA-MOD PLC: Cable
<a href="#">413493</a>	TRIO-PS-2G/1AC/24DC/5 Power supply unit for 100-240V AC; Output 24V DC / 5A, DIN rail mounting Class 100100304: FA-HMI: Other Option
414700	TRIO-PS-2G/1AC/24DC/3/C2LPS Power supply unit for 100-240V AC; Output 24V DC / 3A C2LPS, DIN rail mounting Class 100100304: FA-HMI: Other Option
<a href="#">486376</a>	SC-E5EW-S2M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 2m Class 100100214: FA-MOD PLC: Cable
<a href="#">486377</a>	SC-E5EW-S4M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor; 4m Class 100100214: FA-MOD PLC: Cable
<a href="#">487403</a>	SC-E5EW-S15M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor;15m Class 100100214: FA-MOD PLC: Cable
<a href="#">487404</a>	SC-E5EW-S20M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight; indoor;20m Class 100100214: FA-MOD PLC: Cable
<a href="#">491761</a>	Verbatim microSDHC Card 16GB Class 10 MicroSDHC memory card 16GB; Class 10; R/W: 10MB/s; adapter included Class 100100215: FA-MOD PLC: Other Option
<a href="#">506252</a>	TRIO-PS-2G/1AC/24DC/10 Primary switched power supply; input: single phase, output: 24 VDC/10A, DIN rail Class 100100304: FA-HMI: Other Option
<a href="#">506253</a>	TRIO-PS-2G/1AC/24DC/20 Primary switched power supply; input: single phase, output: 24 VDC/20A, DIN rail Class 100100304: FA-HMI: Other Option
<a href="#">506254</a>	TRIO-PS-2G/3AC/24DC/20 Primary switched power supply; input: 3-phase, output: 24 VDC/20A, DIN rail Class 100100304: FA-HMI: Other Option
<a href="#">506255</a>	TRIO-PS-2G/3AC/24DC/40 Primary switched power supply; input: 3-phase, output: 24 VDC/40A, DIN rail Class 100100304: FA-HMI: Other Option
<a href="#">557483</a>	SC-E5EW-S100M Ethernet cable; CC-Link IE; category 5e; dbl. shielded/STP; straight;indoor;100m Class 100100214: FA-MOD PLC: Cable
<a href="#">612154</a>	FX5-CNV-BUS-BS FX5;FX3 Bus Conversion Unit; coated Class 100100111: FA-COM PLC: Other Option
<a href="#">612156</a>	FX5-CNV-IFC-BS FX5UC;FX5U Bus Converter; coated Class 100100111: FA-COM PLC: Other Option
<a href="#">612268</a>	Transcend SDHC Card 8GB Class 4 SDHC memory card 8GB; Class 4; R: 18MB/s; W: 6MB/s Class 100100304: FA-HMI: Other Option