

Eaton 190008

Catalog Number: 190008

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 18.5 kW, 1 NC, RDC 24: 24 - 27 V DC, DC operation, Screw terminals DILM38-01-EA(RDC24)

Specyfikacje produktu

Rated operational power at AC-3, 380/400 V, 50 Hz	Rated operational power at AC-4, 380/400 V, 50 Hz
18.5 kW	7 kW
Rated control supply voltage (Us) at AC, 60 Hz - min	Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V
0 V	45 A
Operating voltage at AC, 50 Hz - max	Rated control supply voltage (Us) at AC, 50 Hz - min
690 V	0 V
Operating voltage at AC, 60 Hz - min	Electrical connection type of main circuit
24 V	Screw connection
Number of contacts (normally closed) as main contact	Rated control supply voltage (Us) at DC - max
0	27 V
Rated operational power (NEMA)	Rated control supply voltage (Us) at DC - min
14.9 kW	24 V
Number of auxiliary contacts (normally closed contacts)	Rated control supply voltage (Us) at AC, 60 Hz - max
1	0 V
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V	Operating voltage at AC, 50 Hz - min
38 A	24 V
	Rated control supply voltage (Us) at AC, 50 Hz - max
	0 V
Number of auxiliary contacts (normally open contacts)	Number of main contacts (normally open contact)

Do pobrania

2D drawings

210N018

210N017

eaton-contactors-dilm-dimensions.eps

210X202

210T014

210I192

Modele 3D

DA-CS-dil_m17_38

DA-CD-dil_m17_38

Instruction/installation leaflet

IL034042ZU

Schematy okablowania

eaton-contactors-contact-dilm-wiring-diagram-002.eps

2100SWI-117

210S027



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)