



Figure similar

COMPONENT FOR ENCLOSURE, 22MM LAMP HOLDER WITH INTEGRATED LED 230V AC RATED VOLTAGE 230V AC SCREW TERMINAL WHITE !!!
 Phased-out product !!! SIRIUS ACT 3SU1 is successor Preferred successor type is
 >>3SU1401-2BF60-1AA0<<

product designation	lampholder
Contact block/ lampholder	
socket design	integrated
number of lampholders	1
General technical data	
product function positive opening	No
product component	
• diode	Yes
• lamp transformer	No
• light source	Yes
• series resistor	No
insulation voltage rated value	250 V
degree of pollution	class 3
type of voltage	
• of the operating voltage	AC
surge voltage resistance rated value	4 kV
protection class IP	
• of the enclosure	IP40
• of the terminal	IP20
reference code according to IEC 81346-2	P
Substance Prohibitance (Date)	07/01/2006
operating voltage 1	
• at AC	
— at 50 Hz rated value	230 V
— at 60 Hz rated value	230 V
Supply voltage	
type of voltage of the supply voltage of the light source	AC
supply voltage of the light source at AC	
• at 50 Hz rated value	230 V
• at 60 Hz rated value	230 V
relative negative tolerance of the supply voltage	-15 %
relative positive tolerance of the supply voltage	10 %
Auxiliary circuit	
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	0
number of CO contacts for auxiliary contacts	0
consumed current for rated value of supply voltage maximum	17 mA
Connections/ Terminals	

type of electrical connection	screw-type terminals
type of connectable conductor cross-sections	
<ul style="list-style-type: none"> ● for auxiliary contacts <ul style="list-style-type: none"> — solid 2x (1.0 ... 1.5 mm²) — solid with core end processing 2x (0.5 ... 0.75 mm²) — finely stranded with core end processing 2x (0.5 ... 1.5 mm²) ● for AWG cables for auxiliary contacts 2x (18 ... 14) 	
tightening torque for auxiliary contacts with screw-type terminals	0.8 N·m

Lamp

type of light source	LED
color of the light source	white

Ambient conditions

ambient temperature	
<ul style="list-style-type: none"> ● during operation -25 ... +70 °C ● during storage -25 ... +80 °C 	

Installation/ mounting/ dimensions

fastening method	floor mounting
height	49 mm
width	10 mm
depth	28 mm

Certificates/ approvals

General Product Approval	other
--------------------------	-------



[Confirmation](#)

Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB3420-1RE>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB3420-1RE>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB3420-1RE>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB3420-1RE&lang=en



