SIEMENS

Data sheet 3SB3001-6BA20



Indicator light, 22mm, round, plastic, red, lens with concentric rings with holder !!! Phased-out product !!! SIRIUS ACT 3SU1 is successor Preferred successor type is >>3SU1001-6AA20-0AA0 + 3SU1500-0AA10-0AA0<

Figure similar

Enclosure number of command points design of the actuating element product extension optional light source color of the actuating element material of the actuating element product extension optional light source red material of the actuating element plastic shape of the actuating element plastic shape of the actuating element concentric rings outer diameter of the actuating element product component front ring product component front ring No Holder material of the holder Plastic General technical data product function EMERGENCY OFF function EMERGENCY STOP function EMERGENCY STOP function Protection class IP Vibration resistance according to IEC 60068-2-6 Substance Prohibitance (Date) 7/701/2006 Connections/ Torminals tightening torque of the screws in the bracket Ambient conditions ambient temperature during operation during storage Auo+80 "C environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method front mounting mounting diameter 22 mm mounting diameter mounting diameter product function 22 mm installation depth 29 mm	design of the product	Single device round
number of command points 0 Actuator design of the actuating element indicator light product extension optional light source Yes color of the actuating element red material of the actuating element plastic shape of the actuating element Concentric rings outer diameter of the actuating element 28 mm number of switching positions 0 Front ring product component front ring No Holder material of the holder Plastic General technical data product function No EMERGENCY OFF function No EMERGENCY STOP function No Portection class IP IP66 vibration resistance according to IEC 80368-2-6 20 200 Hz; 5g reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 Connections/ Teminals tightening torque of the screws in the bracket 1 1.2 N·m Ambient conditions ambient emperature		
Actuator design of the actuating element indicator light product extension optional light source (and in actuating element) red (and in actuating element) red (and in actuating element) plastic (and in actuating element) plastic (and in actuating element) plastic (and in actuating element)		0
design of the actuating element product extension optional light source Yes color of the actuating element red plastic shape of the actuating element plastic pour diameter of the actuating element plastic pour diameter of the actuating element plastic pour diameter of the actuating element pour diameter plastic plastic pour diameter pour diameter pour diameter plastic pla	·	
product extension optional light source color of the actuating element material of the actuating element shape of the actuating element outer diameter outer of the actuating element outer diameter of the actuating element outer diameter outer outer diamete		indicator light
color of the actuating element plastic shape of the actuating element plastic shape of the actuating element Concentric rings outer diameter of the actuating element 28 mm number of switching positions 0 Front ring product component front ring No Holder material of the holder Plastic Ceneral technical data product function • EMERGENCY OFF function No • EMERGENCY STOP function No • Connections I technicals are product function vibration resistance according to IEC 60068-2-6 20 200 Hz: 5g reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 Connections/ Terminals tightening torque of the screws in the bracket 1 1.2 N·m Ambient temperature • during operation -25 +70 °C • during storage -40 +80 °C environmental category during operation according to IEC 60721 Installation/ mounting dimensions fastening method front mounting mounting diameter 22 mm mounting diameter mounting height 11 mm installation width 28 mm installation depth 29 mm		
material of the actuating element Concentric rings outer diameter of the actuating element 28 mm number of switching positions 0 Front ring product component front ring No Holder material of the holder Plastic General technical data product function • EMERGENCY OFF function No • EMERGENCY OFF function No • EMERGENCY STOP function No protection class IP Vibration resistance according to IEC 60068-2-6 20 200 Hz: 5g reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 Connections/ Terminals tightening torque of the screws in the bracket 1 1.2 N·m Ambient conditions ambient temperature • during operation - 25 +70 °C • during storage - 40 +80 °C environmental category during operation according to IEC 60068 final function opening round mounting diameter 22 mm mounting diameter 22 mm installation depth 29 mm		
shape of the actuating element		
outer diameter of the actuating element 28 mm number of switching positions 0 Front ring No product component front ring No Holder Holder material of the holder Plastic General technical data Product function • EMERGENCY OFF function No • EMERGENCY STOP function No • protection class IP IP66 vibration resistance according to IEC 60068-2-6 20 200 Hz: 5g reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 Connections/ Terminals tightening torque of the screws in the bracket 1 1.2 N·m Ambient conditions ambient temperature -0 during operation -25 +70 °C • during operation -25 +70 °C -40 +80 °C environmental category during operation according to IEC 60721 3K6 Installation/ mounting/ dimensions fastening method front mounting shape of the installation opening round mounting diameter 22 mm mounting height <t< th=""><th></th><th></th></t<>		
number of switching positions Front ring product component front ring Mo Holder material of the holder Ceneral technical data product function • EMERGENCY OFF function • EMERGENCY STOP function No protection class IP vibration resistance according to IEC 60068-2-6 20 200 Hz: 5g reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter mounting diameter mounting diameter installation width installation width installation width installation width installation depth		•
Front ring product component front ring No Holder material of the holder General technical data Product function EMERGENCY OFF function EMERGENCY STOP function No Protection class IP Vibration resistance according to IEC 60068-2-6 PSubstance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature during operation during storage environmental category during operation according to IEC Installation/ mounting/ dimensions fastening method shape of the installation opening mounting height Installation width Installation wi		
product component front ring No Holder material of the holder Plastic General technical data product function • EMERGENCY OFF function No • EMERGENCY STOP function No protection class IP IP66 vibration resistance according to IEC 60068-2-6 20 200 Hz: 5g reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 Connections/ Terminals tightening torque of the screws in the bracket 1 1.2 N·m Ambient conditions ambient temperature • during operation -25 +70 °C • during storage 440 +80 °C environmental category during operation according to IEC 3K6 60721 Installation/ mounting/ dimensions fastening method front mounting mounting diameter 22 mm mounting height 111 mm installation width 28 mm installation depth 29 mm		
Holder material of the holder General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function No protection class IP vibration resistance according to IEC 60068-2-6 vibration resistance according to IEC 60168-2-6 Zou 200 Hz: 5g reference code according to IEC 81346-2 P Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage -40 +80 °C environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter 22 mm mounting height 11 mm installation width 28 mm installation depth 29 mm		No
material of the holder General technical data product function • EMERGENCY OFF function • EMERGENCY STOP function • EMERGENCY STOP function protection class IP vibration resistance according to IEC 60068-2-6 reference code according to IEC 81346-2 P Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket 1 1.2 N·m Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter 22 mm mounting height installation width 28 mm installation depth		NO
General technical data product function • EMERGENCY OFF function No • EMERGENCY STOP function No protection class IP IP66 vibration resistance according to IEC 60068-2-6 20 200 Hz: 5g reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 Connections/ Terminals tightening torque of the screws in the bracket 1 1.2 N·m Ambient conditions ambient temperature • during operation -25 +70 °C • during storage -40 +80 °C environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method front mounting shape of the installation opening round mounting diameter 22 mm mounting height 11 mm installation width 28 mm installation depth 29 mm		Plastic
product function • EMERGENCY OFF function • EMERGENCY STOP function No protection class IP vibration resistance according to IEC 60068-2-6 reference code according to IEC 81346-2 P Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter product function No No No No No No No No 1P66 20 200 Hz: 5g P O7/01/2006 21 1.2 N·m Ambient conditions ambient temperature • during operation -25 +70 °C 40 +80 °C environmental category during operation according to IEC 80721 Installation/ mounting/ dimensions fastening method front mounting shape of the installation opening mounting diameter 22 mm mounting diameter 22 mm mounting height 11 mm installation width 28 mm installation depth		Flastic
EMERGENCY OFF function EMERGENCY STOP function Protection class IP Vibration resistance according to IEC 60068-2-6 Vibration resistance according to IEC 60068-2-6 Vibration resistance according to IEC 81346-2 P Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage • 40 +80 °C environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter punctions mounting diameter 22 mm mounting height 11 mm installation width 28 mm installation depth		
• EMERGENCY STOP function No protection class IP IP66 vibration resistance according to IEC 60068-2-6 20 200 Hz: 5g reference code according to IEC 81346-2 P Substance Prohibitance (Date) 07/01/2006 Connections/ Terminals tightening torque of the screws in the bracket 1 1.2 N·m Ambient conditions ambient temperature • during operation -25 +70 °C • during storage 40 +80 °C environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method front mounting shape of the installation opening round mounting diameter 22 mm mounting height 11 mm installation width 28 mm installation depth 29 mm	•	No
protection class IP vibration resistance according to IEC 60068-2-6 vibration resistance according to IEC 81346-2 reference code according to IEC 81346-2 P Substance Prohibitance (Date) O7/01/2006 Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature		
vibration resistance according to IEC 60068-2-6 reference code according to IEC 81346-2 Substance Prohibitance (Date) Or/01/2006 Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage • during storage • during storage • during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter mounting height installation width installation width 28 mm installation depth		
reference code according to IEC 81346-2 Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage • during storage • environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter mounting height installation width installation width installation depth P 07/01/2006 1 1.2 N·m 1 1.2 N·m Ambient conditions 4 1.2 N·m 3 +70 °C 40 +80 °C 3 +80 °C 3 +80 °C 4 +80 °C 3 +80 °C 4 +80 °C 4 +80 °C 3 +80 °C 4 +80 °C	•	
Substance Prohibitance (Date) Connections/ Terminals tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter mounting diameter 22 mm mounting height installation width 28 mm installation depth 1 1.2 N·m 2 +70 °C 4 +80 °C 3K6 60721 3K6 60721 Installation/ mounting/ dimensions front mounting shape of the installation opening mounting diameter 22 mm mounting height 11 mm installation width 28 mm installation depth		
tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter mounting diameter mounting height installation width installation width installation depth 1 1.2 N·m 2 4 4 4 6 2 4 4 4 6 6 2 4 4 4 6 6 3 K6 6 0721 Installation/ mounting/ dimensions front mounting front mounting mounting mounting diameter 2 4 4 4 6 6 2 4 4 4 6 6 6 3 K6 6 0721 Installation wounting diameter 2 4 4 4 6		
tightening torque of the screws in the bracket Ambient conditions ambient temperature • during operation • during storage • during storage • antiron according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter mounting height installation width installation width 28 mm installation depth 1 1.2 N·m 2		0770 172000
Ambient conditions ambient temperature • during operation • during storage • during storage • revironmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter mounting diameter mounting height installation width installation width 28 mm installation depth		1 12 N.m
ambient temperature • during operation • during storage • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter mounting diameter mounting height installation width installation depth -25 +70 °C 3K6 3K6 6 6 7 8 9 9 9 1 1 1 1 1 1 1 1 1 1		1 1.2 N·III
 during operation -25 +70 °C during storage -40 +80 °C environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter mounting height installation width installation depth 29 mm 		
 during storage -40 +80 °C environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method shape of the installation opening mounting diameter mounting height installation width installation depth 	•	25 ±70 °C
environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions fastening method front mounting shape of the installation opening round mounting diameter 22 mm mounting height 11 mm installation width 28 mm installation depth 29 mm		
Installation/ mounting/ dimensions fastening method front mounting shape of the installation opening round mounting diameter 22 mm mounting height 11 mm installation width 28 mm installation depth 29 mm	environmental category during operation according to IEC	
fastening method front mounting shape of the installation opening round mounting diameter 22 mm mounting height 11 mm installation width 28 mm installation depth 29 mm		
shape of the installation opening mounting diameter 22 mm mounting height 11 mm installation width 28 mm installation depth 29 mm		front mounting
mounting diameter22 mmmounting height11 mminstallation width28 mminstallation depth29 mm		
mounting height 11 mm installation width 28 mm installation depth 29 mm		
installation width 28 mm installation depth 29 mm		
installation depth 29 mm		
	Certificates/ approvals	













other

<u>Confirmation</u> <u>Miscellaneous</u>

Further information

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB3001-6BA20

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB3001-6BA20

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SB3001-6BA20

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB3001-6BA20&lang=en

last modified:	1/18/2021	♂