

Pin busbar touch-safe, 16 mm<sup>2</sup> 1-phase+AUX 1016 mm long can be cut, without end caps



Model		
product brand name	SETRON	
product designation	Pin busbar	
design of the product	16 mm <sup>2</sup> , 1PH+AS 1016mm	
General technical data		
phase number	1	
cross-section	16 mm <sup>2</sup>	
Main circuit		
operational current rated value	80 A	
Product details		
product feature insulated	Yes	
Connections		
type of electrical connection	Pin	
Mechanical Design		
width	15.5 mm	
length	1 016 mm	
net weight	197.42 g	
Approvals Certificates		
General Product Approval	Declaration of Conformity	other

[Confirmation](#)

[Miscellaneous](#)

**EAC**

**UK  
CA**

**CE**  
EG-Konf.

[Confirmation](#)

other

Environment

[Miscellaneous](#)

[Environmental Con-  
firmations](#)

### Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3703>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3703>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5ST3703](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3703)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



1) Pin spacings in MW (Modular widths, 1 MW = 18

