



## E3FB-DP13 2M

Photoelectric sensor, M18 threaded barrel, metal, red LED, diffuse, 1 m, PNP, Light-ON/Dark-ON, 2 m cable

# Dane techniczne

<b>Shape</b>	Cylindrical axial
<b>Sensing method</b>	Diffuse reflective
<b>Sensing distance</b>	1000 mm
<b>Setting method</b>	Manual adjustment
<b>Connection method</b>	Cable
<b>Cable length</b>	2 m
<b>Output type</b>	PNP
<b>Operation mode</b>	Dark-ON, Light-ON
<b>Response time</b>	0.5 ms
<b>Material housing</b>	Brass, nickel plated
<b>Thread size</b>	M18
<b>Product Length (unpacked)</b>	44 mm
<b>Type of light</b>	Polarity free red light
<b>Power supply voltage</b>	10-30 V
<b>Degree of protection (IP)</b>	IP67/IP69K

## Akcesoria



**E39-L183**

M18 L-type mounting bracket, stainless steel (SUS304)

#### WARUNKI KORZYSTANIA Z WITRYNY INTERNETOWEJ

Ten dokument PDF został utworzony za pomocą europejskiej strony internetowej firmy OMRON Industrial Automation w dniu 8 January, 2024. Kliknij tutaj, aby wyświetlić [regulacje prawne](#).

**OMRON**

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU