

WKREŃTAKI IMBUSOWE VDE DLA ELEKTRYKÓW




Końcówka sześciokątna

- Klinga: brązowiona, izolowana
- Końcówka: DIN 911
- Norma: DIN 7439, IEC 900, EN 60900

1000 V



Symbol	Diagram			Nr artykułu	Sztuk
	A mm	B/C mm	A cal		
2,5	80	83/27	3 1/8"	0613 635 025	1
3,0	80	83/27	3 1/8"	0613 635 03	1
4,0	75	96/31	3 1/8"	0613 635 04	1
5,0	75	106/35	3 1/8"	0613 635 05	1
6,0	100	106/35	4"	0613 635 06	1
8,0	100	114/38	4"	0613 635 08	1



Wkrętaki z końcówką AW®

- Klinga: brązowiona, izolowana
- Norma: IEC 900, EN 60900

1000 V



Symbol	Diagram			Nr artykułu	Sztuk
	A mm	B/C mm	A cal		
AW 20	100	106/35	4"	0613 637 20	1
AW 25	100	106/35	4"	0613 637 25	1

Zestaw wkrętaków izolowanych dla elektroinstalatorów

- Norma: DIN 7437/7438, IEC 900, EN 60900

1000 V



Symbol	Nr artykułu	Symbol	Nr artykułu	Sztuk
0,4 x 2,5 x 80	0613 631 025	PH 1	0613 632 1	1
0,8 x 4,0 x 100	0613 631 04	PH 2	0613 632 2	1
1,2 x 6,5 x 150	0613 631 065			1

Nr art. 0613 963 25 Ilość - 1 kpl.



Symbol	Nr artykułu	Symbol	Nr artykułu	Sztuk
0,4 x 2,5 x 80	0613 631 025	PZ 1	0613 633 1	1
0,8 x 4,0 x 100	0613 631 04	PZ 2	0613 633 2	1
1,2 x 6,5 x 150	0613 631 065			1

Nr art. 0613 963 35 Ilość - 1 kpl.

