6GK7277-1AA10-0AA0

## **Data sheet**

product type designation



Compact Switch Module CSM 1277 for connecting SIMATIC S7-1200 and up to 3 further nodes to Industrial Ethernet with 10/100 Mbit/s; unmanaged switch, 4 RJ45 ports, ext. 24 V DC power supply LED diagnostics, S7-1200 module incl. electronic Equipment Manual on CD-ROM.

product type designation	SCALANCE CON 1277	
transfer rate		
transfer rate	10 Mbit/s, 100 Mbit/s	
interfaces / for communication / maximum configuration for modular devices		
number of electrical ports / maximum	4	
interfaces / for communication / integrated		
number of electrical connections		
<ul> <li>for network components or terminal equipment</li> </ul>	4	
number of 100 Mbit/s SC ports		
• for multimode	0	
number of 1000 Mbit/s LC ports		
• for multimode	0	
• for single mode (LD)	0	
interfaces / other		
number of electrical connections		
<ul><li>for power supply</li></ul>	1	
type of electrical connection		
<ul><li>for power supply</li></ul>	3-pole terminal block	
supply voltage, current consumption, power loss		
type of voltage / 1 / of the supply voltage	DC	
<ul><li>supply voltage / 1 / rated value</li></ul>	24 V	
<ul><li>power loss [W] / 1 / rated value</li></ul>	1.6 W	
<ul><li>supply voltage / 1 / rated value</li></ul>	19.2 28.8 V	
<ul><li>consumed current / 1 / maximum</li></ul>	0.07 A	
<ul> <li>type of electrical connection / 1 / for power supply</li> </ul>	3-pole terminal block	
<ul> <li>product component / 1 / fusing at power supply input</li> </ul>	Yes	
<ul> <li>fuse protection type / 1 / at input for supply voltage</li> </ul>	0.5 A / 60 V	
ambient conditions		
ambient temperature		
<ul> <li>during operation</li> </ul>	0 60 °C	
<ul> <li>during storage</li> </ul>	-40 +70 °C	
during transport	-40 +70 °C	
relative humidity		
at 25 °C / without condensation / during operation / maximum	95 %	
protection class IP	IP20	
design, dimensions and weights		
design	SIMATIC S7-1200 device design	
width	45 mm	
height	100 mm	

SCALANCE CSM 1277

donth	75 mm	
depth net weight	75 mm	
net weight	0.15 kg	
fastening method	Voo	
35 mm top hat DIN rail mounting	Yes	
wall mounting     C7 200 rail mounting	Yes	
S7-300 rail mounting     7-4500 rail mounting	No	
S7-1500 rail mounting	No	
product functions / management, configuration, engineering		
product function		
multiport mirroring	No	
product function / switch-managed	No	
product functions / redundancy		
product function		
<ul> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	Yes	
<ul> <li>Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)</li> </ul>	No	
standards, specifications, approvals		
standard		
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T, CL.1, Zone 2, GP. IIC, T	
	Та	
<ul> <li>for safety / from CSA and UL</li> </ul>	UL 508, CSA C22.2 No. 142	
<ul> <li>for emitted interference</li> </ul>	EN 61000-6-4 (Class A)	
for interference immunity	EN 61000-6-2	
MTBF	273 a	
reference code		
<ul><li>according to IEC 81346-2</li></ul>	KF	
<ul> <li>according to IEC 81346-2:2019</li> </ul>	KFE	
standards, specifications, approvals / CE		
certificate of suitability / CE marking	Yes	
standards, specifications, approvals / hazardous environments		
standard / for hazardous zone		
•	EN 600079-15:2005, EN 600079-0:2006, II 3 G Ex nA II T4, KEMA 08 ATEX 0003 X	
certificate of suitability		
CCC / for hazardous zone according to GB standard	Yes; GB3836.1, GB3836.8	
CCC / for hazardous zone according to GB standard / as	Ex nA IIC T4 Gc	
marking	EXTINUITY OF	
standards, specifications, approvals / other		
certificate of suitability	EN 61000-6-2, EN 61000-6-4	
• C-Tick	Yes	
KC approval	No	
standards, specifications, approvals / marine classification		
Marine classification association		
American Bureau of Shipping Europe Ltd. (ABS)	Yes	
	Yes	
French marine classification society (BV)     Pot Nersko Veritas (DNV)		
Det Norske Veritas (DNV)     Cormanische Llevel (CL)	Yes	
Germanische Lloyd (GL)     Haude Parieta of Chinaina (LDC)	No	
Lloyds Register of Shipping (LRS)	Yes	
Nippon Kaiji Kyokai (NK)	Yes	
Polski Rejestr Statkow (PRS)	No 	
Royal Institution of Naval Architects (RINA)	No	
product functions / general		
Warranty period	5 a	
further information / internet links		
internet link		
• to website: Image database	https://www.automation.siemens.com/bilddb	
to website: Industry Online Support	https://support.industry.siemens.com	
security information		
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats,	

it is necessary to implement – and continuously maintain – a holistic, state-ofthe-art industrial security concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial security measures that may be implemented, please visit https://www.siemens.com/industrialsecurity. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Security RSS Feed under https://www.siemens.com/cert. (V4.6)

## Approvals / Certificates

## **General Product Approval**

Manufacturer Declaration











For use in hazardous locations

IECEx IECEx



<u>FM</u>

CCC-Ex



Marine / Shipping



Marine / Shipping





NK / Nippon Kaiji Kyokai



Confirmation

Environment



last modified:

2/9/2024

