



MATERIAL FACT SHEET

584883 GS2107-WTBD-N

General Data

Product Hierarchy	IAT93001
	HMI
	Small HMI
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	A (Available from Stock)

e-shop: https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000584883

FA-HMI: Human Machine Interface

Series	GOT SIMPLE SERIES
Type	GS21 MODEL
Power Supply (V)	24
Current Type	DC
Display	TFT
Display Colour	65536
Display Size (Inch)	7
Resolution (Pixels)	800X480
Internal Memory Capacity (MB)	15
Memory Card Slot	SD
USB	1
Ethernet Port	1
RS-232	1
RS-422/485	1
Network Options	CCLINK
Network Options (2)	ETHERNET
Network Options (3)	MODBUS
Protection Class	IP65F

Product Dimensions & Weight

Width (mm)	206
Height (mm)	155
Depth (mm)	50
Weight (kg)	0,9

Logistic Dimensions & Gross Weight

Length (cm)	27,5
Width (cm)	20,0
Height (cm)	9,5
Gross Weight (kg)	1,043
Volume (cdm)	5,225

Stock Data

Planned Delivery Time (Days)	65
------------------------------	----

Life Cycle

Sales Start	01.02.2021
Predecessor	273362 / GS2107-WTBD

Additional Product Information

Binding Tariff Information	DEBTI-10694/21-1
BTI validity date	10.10.2024
Battery included	YES - CHECK SPARE PART LIST

Export Data

Legal Control (Dual Use List)	Not Listed
-------------------------------	------------

Country of Origin	China (CN)
Preference Status (Supplier Declaration)	Non EU

Environmental

Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	COMPLIANT
Shipping Approvals	NON-COMPLIANT
UKCA	COMPLIANT

Documentation & Media Data

Manual URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=bltdae25c2bd5f2f94&q=GS2107-WTBD-N&doc-lang=en
Certificates URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt8050dd1408c11cc2&q=GS2107-WTBD-N&doc-lang=en
CAD URL Indicator	https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&doc-cats=blt26ecc97a31a841c1&q=GS2107-WTBD-N&doc-lang=en

Product Packaging

Cardboard (g)	317,83
Other paper (g)	8,9
Aluminum (g)	0,0
Steel (g)	0,0
Styrofoam (g)	0,0
Other plastic (g)	6,1
Wood (g)	0,0
Glass (g)	0,0
Others (g)	0,0

Compatible products

Material	Description / Price List Text / Classification
163953	GT01-C30R4-25P Conn.cable AnS/QnAS/A/QnA/F-CPU+GOT2000/GOT1000/GOT Simple;3m Class 100100303: FA-HMI: Cable
163954	GT01-C100R4-25P GOT Connection cable for CPU (MELSEC AnS/QnAS or A/QnA) and GOT1000-series; 10 m Class 100100303: FA-HMI: Cable
163955	GT01-C200R4-25P GOT Connection cable for CPU (MELSEC AnS/QnAS or A/QnA) and GOT1000-series; 20 m Class 100100303: FA-HMI: Cable
163956	GT01-C300R4-25P GOT Connection cable for CPU (MELSEC AnS/QnAS or A/QnA) and GOT1000-series; 30 m Class 100100303: FA-HMI: Cable
200496	GT10-C30R4-25P GOT Connection cable for CPU (MELSEC AnS/QnAS/A/QnA) and GT1020/GT1030; 3 m Class 100100303: FA-HMI: Cable
200497	GT10-C100R4-25P GOT Connection cable for CPU (MELSEC AnS/QnAS/A/QnA) and GT1020/GT1030; 10 m Class 100100303: FA-HMI: Cable
280470	GT21-C30R4-25P5 GOT2000;RS-422 connection cable between Q CPU and GT2103-PMDB;3m Class 100100303: FA-HMI: Cable
280471	GT21-C100R4-25P5 GOT2000;RS-422 connection cable between Q CPU and GT2103-PMDB;10m Class 100100303: FA-HMI: Cable
280474	GT21-C200R4-25P5 GOT2000;RS-422 connection cable between Q CPU and GT2103-PMDB;20m Class 100100303: FA-HMI: Cable
280475	GT21-C300R4-25P5 GOT2000;RS-422 connection cable between Q CPU and GT2103-PMDB;30m Class 100100303: FA-HMI: Cable
293474	Ethernetcable GOT Add on Kit Ethernetcable GOT Add on Kit Class 100100303: FA-HMI: Cable