

SENTRON, bezpiecznik cylindryczny, 10x38 mm, 4 A, gPV, Un DC: 1000 V



Wersja	
Nazwa markowa produktu	SENTRON
oznaczenie produktu	Wkładka bezpiecznika cylindrycznego
Ogólne dane techniczne	
charakterystyka wkładki bezpiecznikowej	gPV
rodzaj napięcia napięcia roboczego	DC
napięcie zasilające przy DC	1 000 V
Obwód główny	
prąd roboczy wartość nominalna	4 A
Szczegóły produktu	
element składowy produktu sygnalizator uderzenia	Nie
Konstrukcja mechaniczna	
pozycja montażowa	dowolnie, najlepiej pionowo
masa netto	8 g
Zezwolenia Certyfikaty	
General Product Approval	other



EG-Konf.

[Confirmation](#)



[Miscellaneous](#)

[Confirmation](#)

### Environment

[Environmental Con-  
firmations](#)

### Więcej informacji

Informacje dotyczące opakowania

[Informacje dotyczące opakowania](#)

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NW6004-4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/pl/ps/3NW6004-4>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NW6004-4](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NW6004-4)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications  
<http://www.siemens.com/specifications>

---

Ostatnia zmiana:

17.02.2023 

