

SIMATIC S7-1500 / ET 200MP; active backplane bus 12 slots for inserting S7-1500 I/O modules for hot swapping; for use in the ET 200MP with IM 155-5 PN HF (from FW V4.4.1); S7-1500 mounting rail and slot covers to be ordered separately



General information	
Product type designation	Active backplane ST 1+12 slot
HW functional status	FS01
Firmware version	V1.0.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Prioritized startup</li> </ul>	Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V16
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	V5.6 and higher
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	V2.34 / -
Power	
Power available from the backplane bus	2 W
Power loss	
Power loss, typ.	2 W
Hardware configuration	
Slots	
<ul style="list-style-type: none"> <li>Grid size</li> </ul>	35 mm; Utilization of 25 mm-wide modules possible
<ul style="list-style-type: none"> <li>Number of slots</li> </ul>	13
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>of which for CPU, max.</li> </ul> </li> </ul>	0
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>of which for IM, max.</li> </ul> </li> </ul>	1
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>of which for PS, max.</li> </ul> </li> </ul>	12; Max. 2 PS per station
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>of which for IO/CM/CP/TM, max.</li> </ul> </li> </ul>	12
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>of which for F-IO, max.</li> </ul> </li> </ul>	12
<ul style="list-style-type: none"> <li>Number of single-width slots, max.</li> </ul>	12
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>horizontal installation, min.</li> </ul>	-30 °C
<ul style="list-style-type: none"> <li>horizontal installation, max.</li> </ul>	60 °C
<ul style="list-style-type: none"> <li>vertical installation, min.</li> </ul>	-30 °C
<ul style="list-style-type: none"> <li>vertical installation, max.</li> </ul>	40 °C
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> <li>min.</li> </ul>	-40 °C
<ul style="list-style-type: none"> <li>max.</li> </ul>	70 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> <li>Installation altitude above sea level, max.</li> </ul>	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Dimensions	
Width	434 mm

Height	99 mm
Depth	14 mm
<b>Weights</b>	
Weight, approx.	352 g

<b>Classifications</b>			
		Version	Classification
	eClass	14	27-24-22-03
	eClass	12	27-24-22-03
	eClass	9.1	27-24-22-03
	eClass	9	27-24-22-03
	eClass	8	27-24-22-03
	eClass	7.1	27-24-22-03
	eClass	6	27-24-22-03
	ETIM	9	EC000810
	ETIM	8	EC000810
	ETIM	7	EC000810
	IDEA	4	3560
	UNSPSC	15	32-15-17-04

**Approvals / Certificates**

General Product Approval	For use in hazardous locations
--------------------------	--------------------------------



[KC](#)



**For use in hazardous locations**

[FM](#)

[CCC-Ex](#)



[Type Examination Certificate](#)



[Miscellaneous](#)

**Marine / Shipping**



[NK / Nippon Kaiji Kyokai](#)



**Marine / Shipping**

[CCS \(China Classification Society\)](#)



last modified:

3/12/2024