



stainless steel plug cover, for using ET200ecoPN M12-L in hazardous area zone 2 / 22

General information			
Product description	connector cover for ET200ecoPN M12-L		
Suitability for use	accessories for use of the ET200ecoPN M12-L in hazardous area Zone 2/22		
Degree and class of protection			
IP degree of protection	IP20		
Ambient conditions			
Ambient temperature during assembly, min.	-40 °C		
Ambient temperature during assembly, max.	80 °C		
Ambient temperature during operation			
• min.	-40 °C		
• max.	60 °C		
Ambient temperature during storage/transportation			
• min.	-40 °C		
• max.	80 °C		
Mechanics/material			
Material of housing	stainless steel with plastic edge protection		
Material property			
• Silicone-free	Yes		
Dimensions			
Width	50 mm		
Height	200 mm		
Depth	110 mm		
Weights			
Weight, approx.	710 g		
Classifications			
		Version	Classification
	eClass	14	27-24-26-92
	eClass	12	27-24-26-92
	eClass	9.1	27-24-26-92
	eClass	9	27-24-26-92
	eClass	8	27-24-26-92
	eClass	7.1	27-24-26-92
	eClass	6	27-24-26-92
	ETIM	9	EC002584
	ETIM	8	EC002584
	ETIM	7	EC002584
Approvals / Certificates			

[Manufacturer Declaration](#)



[CCC-Ex](#)



[Miscellaneous](#)

For use in hazardous locations



IECEX

last modified:

1/25/2024 