SIEMENS

Data sheet

6AV6671-8XE00-0AX0

converter RS-422, male, 9-pole to RS-232 male, 9-pole, can be screwed together with RS-422 interface, cable outlet 180 degrees, for connection of third-party PLC, scope of supply: 1 converter



| General information | | | |
|---|---|--|--|
| Product type designation | Converter, RS 422 to RS 232 | | |
| Installation type/mounting | | | |
| Wall mounting/direct mounting | Yes; Can be screwed onto the HMI | | |
| Interfaces | | | |
| HMI-side interface | | | |
| Number of pins HMI-side | 9; Male (RS 422) | | |
| Device-side interface | | | |
| Number of pins device-side | 9; Female (RS 232) | | |
| Degree and class of protection | | | |
| IP (all-round) | none | | |
| Standards, approvals, certificates | | | |
| CE mark | Yes | | |
| RoHS conformity | Yes | | |
| China RoHS compliance | Yes | | |
| Ambient conditions | | | |
| Ambient temperature during operation | | | |
| • min. | 0 °C | | |
| • max. | 55 °C | | |
| Ambient temperature during storage/transportation | | | |
| • min. | -20 °C | | |
| • max. | 70 °C | | |
| Relative humidity | | | |
| Operation, max. | 95 % | | |
| Mechanics/material | | | |
| Enclosure material (front) | | | |
| Plastic | Yes | | |
| Screw type | | | |
| • 4.5 V | Yes; HMI page | | |
| Torques/forces | | | |
| Tightening torque, min. | 0.18 N·m; Insufficient torque can lead to loosening of the screws | | |
| Tightening torque, max. | 0.2 N·m | | |
| Tightening torque, recommended | 0.2 N·m; Higher torques may damage the product | | |
| Dimensions | | | |
| Width | 31 mm | | |
| Height | 50 mm | | |
| Thickness | 11 mm | | |
| Weights | | | |
| Weight (without packaging) | 26 g | | |
| Scope of supply | | | |

| Delivery quantity in pieces | 1 |
|----------------------------------|--|
| Dther | |
| Merchandise | No |
| Manufacturer name | SIEMENS AG |
| Manufacturer's address | Gleiwitzerstraße 555, 90475 Nuremberg, Germany |
| Target devices | suitable for all SIMATIC HMI RS 422 interfaces, for details refer to the operating instructions of the respective device |
| Usable in the following products | |
| Product 1 | 6AV6642-0* |
| Product 2 | 6AV6542-0* |
| Product 3 | 6AV6545-0* |
| Product 4 | 6AV6644-* |
| Product 6 | 6AV6640-0C* |
| Product 7 | 6AV6643-7BA00-* |
| Product 8 | 6AV6643-7CD00-* |
| Product 9 | 6AV6643-7DD00-* |
| Product 10 | 6AV2124-* |
| Product 11 | 6AV2128-3* |
| Product 13 | 6AV6647-* |
| Product 14 | 6AV6643-8* |
| Product 15 | 6AV2123-2* |
| Classifications | |

| | Version | Classification |
|--------|---------|----------------|
| eClass | 14 | 27-33-02-92 |
| eClass | 12 | 27-33-02-92 |
| eClass | 9.1 | 27-33-02-92 |
| eClass | 9 | 27-33-02-92 |
| eClass | 8 | 27-24-92-03 |
| eClass | 7.1 | 27-24-92-03 |
| eClass | 6 | 27-24-92-03 |
| ETIM | 9 | EC002584 |
| ETIM | 8 | EC002584 |
| ETIM | 7 | EC002584 |
| IDEA | 4 | 3552 |
| UNSPSC | 15 | 32-15-17-03 |

Approvals / Certificates

<u>KC</u>

General Product Approval

Â



EMV

last modified:

5/22/2024 🖸