Data sheet

6AV6881-0KD33-0DA0

mounting frame for 10" Unified Panels sheet thickness from 1 mm, scope of supply: 1 mounting frame




Figure similar

| General information | | | |
|--|------------------------------|--|--|
| Product type designation | mounting frame | | |
| Display | | | |
| Suitable for screen diagonal | 10.1 in | | |
| Installation type/mounting | | | |
| Mounting type | Backplane mounting | | |
| Mounting in portrait format possible | Yes | | |
| Mounting in landscape format possible | Yes | | |
| Standards, approvals, certificates | | | |
| CE mark | No; No CE marking obligation | | |
| REACH | Yes; Tested | | |
| RoHS conformity | Yes; Tested / compliant | | |
| Use in hazardous areas | | | |
| ATEX Zone 2 | No | | |
| ATEX Zone 22 | No | | |
| ATEX as target device | No | | |
| • IECEx Zone 1 | No | | |
| • IECEx Zone 11 | No | | |
| • IECEx Zone 2 | No | | |
| • IECEx Zone 22 | No | | |
| • cULus Class I Zone 1 | No | | |
| cULus Class I Zone 2, Division 2 | No | | |
| cULus Class II Division 2 | No | | |
| FM Class I Division 2 | No | | |
| FM Class II Division 2 | No | | |
| Marine approval | | | |
| Germanischer Lloyd (GL) | No | | |
| American Bureau of Shipping (ABS) | No | | |
| Bureau Veritas (BV) | No | | |
| Det Norske Veritas (DNV) | No | | |
| Korean Register of Shipping (KRS) | No | | |
| Lloyds Register of Shipping (LRS) | No | | |
| Nippon Kaiji Kyokai (Class NK) | No | | |
| Polski Rejestr Statkow (PRS) | No | | |
| Chinese Classification Society (CCS) | No | | |
| Marine approval as target device | No | | |
| Ambient conditions | | | |
| Suited for indoor use | Yes | | |
| Suited for outdoor use | No | | |

| Ambient temperature during operation | | | | | |
|---|----------------------------------|--|----------------|--|--|
| • min. | -40 °C | -40 °C | | | |
| • max. | 80 °C | 80 °C | | | |
| Ambient temperature during storage/transportation | | | | | |
| • min. | -40 °C | -40 °C | | | |
| • max. | 80 °C | 80 °C | | | |
| Relative humidity | | | | | |
| Operation, max. | 90 % | 90 % | | | |
| lechanics/material | | | | | |
| Enclosure material (front) | | | | | |
| Sheet steel | Yes; Powder-coated | Yes; Powder-coated | | | |
| Dimensions | | | | | |
| Width | 293.5 mm | 293.5 mm | | | |
| Height | 218.5 mm | 218.5 mm | | | |
| Thickness | 4 mm | | | | |
| Mounting cutout, width | 263.5 mm | | | | |
| Mounting cutout, height | 188.5 mm | 188.5 mm | | | |
| Veights | | | | | |
| Weight, approx. | 0.9 kg | 0.9 kg | | | |
| cope of supply | | | | | |
| Delivery quantity in pieces | 1; frame | | | | |
| Other | | | | | |
| Merchandise | Yes; mounting frame WFP2.3 | Yes; mounting frame WFP2.3 | | | |
| Manufacturer name | QUERUM products UG | QUERUM products UG | | | |
| Manufacturer's address | Wirtsstr. 23, 85110 Kipfenberg-E | Wirtsstr. 23, 85110 Kipfenberg-Böhming, Germany | | | |
| contacting the manufacturer | | email: querumproducts@web.de | | | |
| Target devices | | for Unified Comfort Panels to reinforce the mounting plate thickness | | | |
| Note: | ensures tightness with thin mour | nting plates | | | |
| Usable in the following products | | | | | |
| Product 1 | 6AV2128-3KB*6-0AX0 | | | | |
| Classifications | | | | | |
| | | Version | Classification | | |
| | eClass | 14 | 27-33-02-92 | | |
| | eClass | 12 | 27-33-02-92 | | |
| | eClass | 9.1 | 27-33-02-92 | | |
| | eClass | 9 | 27-33-02-92 | | |
| | | | | | |
| | eClass | 8 | 27-24-92-03 | | |
| | eClass | 7.1 | 27-24-92-03 | | |
| | | | | | |
| | eClass | 6 | 27-24-92-03 | | |

last modified: 10/29/2024 🖸

EC002584

EC002584

8

7

ETIM

ETIM