## SIEMENS

## Data sheet

## 6AV6881-0GH21-2AA0



INOX frame 7" type 1, Unified stainless steel, type 1 for Panel, thin client and IPC, scope of supply: 1 frame 2 parts screwed together

Fig	ure	sim	ilar

General information		
Product type designation	protective frame INOX	
Display		
Suitable for screen diagonal	7 in	
Installation type/mounting		
Mounting	for mounting in a built-in widescreen Panel	
Mounting type	screw fixing	
Mounting position	Any, dependent on target device	
Front mounting	Yes	
Mounting in portrait format possible	Yes	
Mounting in landscape format possible	Yes	
Degree and class of protection		
IP (at the front)	IP69	
Splashproof	Yes	
Standards, approvals, certificates		
responsibility with the manufacturer	Yes	
CE mark	No; No CE marking obligation	
UL approval	No	
REACH	Yes	
RoHS conformity	Yes	
FDA-compliant	gaskets are FDA-compliant	
Ambient conditions		
Suited for indoor use	Yes	
Suited for outdoor use	Yes; Always comply with the operating instructions of the target device.	
Ambient temperature during operation		
• min.	-40 °C	
• max.	80 °C	
Ambient temperature during storage/transportation		
• min.	-40 °C	
• max.	80 °C	
Relative humidity		
• Operation, max.	95 %	
Mechanics/material		
Material	Matte	
Stainless steel	Yes; V2A 1.4300	
Enclosure material (rear)	Stainless steel V2A	
Enclosure color (front)	matte, ceramic-blasted	
Screw type		
• Torx	Yes; T20	

	Version Classification
lassifications	UAV2120-JOD U-UAAU
Product 1	6AV2128-3GB*6-0AX0
Usable in the following products	not released for hazardous areas and marine applications!
Note:	Not released for hazardous areas and marine applications!
Target devices	Unified Comfort Panels, Industrial Thin Clients, Industrial Flat Panels and Industrial Pcs with suitable dimensions
contacting the manufacturer	email: querumproducts@web.de
Manufacturer's address	Wirtsstr. 23, 85110 Kipfenberg-Böhming, Germany
Manufacturer name	QUERUM products UG
Merchandise	Yes; INOX frame
ther	
Parts per unit	1; 1x protective frame INOX incl. screws and seals (mounting frame and protective films can be ordered separately)
Delivery quantity in pieces	1; 1x protective frame INOX
cope of supply	
Depth	16 mm
Height	185.2 mm
Width	241.2 mm
imensions	
<ul> <li>Tightening torque, max.</li> </ul>	14 N·m
Tightening torque, min.	12 N·m; If there is not enough torque, the degree of protection on the front manot be guaranteed
•	

last modified:
last mounieu.

1/25/2024 🖸

eClass

eClass

eClass

eClass

eClass

eClass

eClass

ETIM

ETIM

ETIM

14

12

9.1

9

8

7.1

6

9

8

7

27-33-02-92 27-33-02-92

27-33-02-92

27-33-02-92

27-24-92-03

27-24-92-03

27-24-92-03 EC002584

EC002584

EC002584