

pipe adapter VESA 100/75, IP65, INOX, for Pro devices, including trapezoidal plate INOX IP65, scope of supply: 1 pipe adapter, 1 trapezoidal plate with 3 icotek cable sleeves for 6 mm lines



General information	
Product type designation	VESA 100/75 flange mount IP65
Installation type/mounting	
Mounting	VESA 100 mm / 75 mm with M6 thread
Mounting type	Support arm with VESA 100 mm or 75 mm
Degree and class of protection	
IP (at the front)	IP65
Standards, approvals, certificates	
Use in hazardous areas	
• ATEX Zone 2	No
• ATEX Zone 22	No
• ATEX as target device	No
• IECEx Zone 1	No
• IECEx Zone 11	No
• IECEx Zone 2	No
• IECEx Zone 22	No
• cULus Class I Zone 1	No
• cULus Class I Zone 2, Division 2	No
• cULus Class II Division 2	No
• FM Class I Division 2	No
• FM Class II Division 2	No
Marine approval	
• Germanischer Lloyd (GL)	No
• American Bureau of Shipping (ABS)	No
• Bureau Veritas (BV)	No
• Det Norske Veritas (DNV)	No
• Korean Register of Shipping (KRS)	No
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (Class NK)	No
• Polski Rejestr Statkow (PRS)	No
• Chinese Classification Society (CCS)	No
• Marine approval as target device	No
Ambient conditions	
Suited for indoor use	Yes
Suited for outdoor use	No
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Ambient temperature during storage/transportation	
• min.	-20 °C

• max.	70 °C		
Relative humidity			
• Operation, max.	90 %		
• Condensation permissible	No		
Mechanics/material			
Material			
• Stainless steel	Yes; Stainless steel V2A		
Dimensions			
Width	135 mm; VESA 100/75 PRO INOX adapter		
Height	120 mm; VESA 100/75 PRO INOX adapter		
Depth	67.5 mm; VESA 100/75 PRO INOX adapter		
Scope of supply			
Delivery quantity in pieces	2; 1x VESA INOX IP65 adapter and 1x INOX cable entry INOX IP65 with ICOTEK 3-fach cable entry 6 mm		
Components included	Without additional accessories		
Other			
Merchandise	Yes; VESA 100/75 PRO INOX adapter set IP65		
Manufacturer name	QUERUM products UG		
Manufacturer's address	Wirtsstr. 23, 85110 Kipfenberg-Böhming, Germany		
Target devices	Not suitable for 19" 4:3 devices		
Note:	Max. load 35 kg, for expandable support arm mounting		
Usable in the following products			
• Product 1	6AV2124-*		
• Product 2	6AV7251-*		
• Product 3	6AV6646-1BD*		
• Product 4	6AV7863*		
• Product 5	6AV7250-*		
Classifications			
		Version	Classification
	eClass	14	27-33-02-92
	eClass	12	27-33-02-92
	eClass	9.1	27-33-02-92
	eClass	9	27-33-02-92
	eClass	8	27-24-92-03
	eClass	7.1	27-24-92-03
	eClass	6	27-24-92-03
	ETIM	9	EC002584
	ETIM	8	EC002584
	ETIM	7	EC002584
	IDEA	4	3552
	UNSPSC	15	32-15-17-03

last modified:

1/25/2024 