

M8 connector for ET connection, 4-pole, shielded



General information			
Product type designation	Connection plug		
Product description	M8 plug connector with high degree of protection, 4-pin, metal version		
Suitability for use	for connecting ET-CONNECTION nodes (e.g. SIMATIC ET 200AL) in degree of protection IP65 / 67		
Degree and class of protection			
IP degree of protection	IP65/67		
Ambient conditions			
Ambient temperature during assembly, min.	-30 °C		
Ambient temperature during assembly, max.	80 °C		
Ambient temperature during storage/transportation			
• min.	-40 °C		
• max.	80 °C		
Mechanics/material			
Outgoing feeder type	180° cable outlet		
Material of housing	metal		
Dimensions			
Width	14 mm		
Depth	47 mm		
Classifications			
		Version	Classification
	eClass	14	27-24-26-92
	eClass	12	27-24-26-92
	eClass	9.1	27-24-26-92
	eClass	9	27-24-26-92
	eClass	8	27-24-26-92
	eClass	7.1	27-24-26-92
	eClass	6	27-24-26-92
	ETIM	9	EC002584
	ETIM	8	EC002584
	ETIM	7	EC002584
	IDEA	4	3552
	UNSPSC	15	32-15-17-03
Approvals / Certificates			
General Product Approval			

[Manufacturer Declaration](#)



last modified:

3/12/2024