

SITOR bezpiecznik cylindryczny, 14x51 mm, 1 A, aR, Un AC: 660 V



Figure similar

Wersja	
Nazwa markowa produktu	SETRON
oznaczenie produktu	Wkładka bezpiecznika cylindrycznego SITOR
Ogólne dane techniczne	
charakterystyka wkładki bezpiecznikowej	aR
rodzaj napięcia napięcia roboczego	AC
Rozpraszanie	
Strata mocy [W]	5 W
Strata mocy [W] w przypadku wartości znamionowej prądu w przypadku AC w stanie rozgrzanym na biegun	5 W
Obwód główny	
prąd roboczy wartość nominalna	1 A
Szczegóły produktu	
element składowy produktu sygnalizator uderzenia	Nie
Konstrukcja mechaniczna	
pozycja montażowa	dowolnie, najlepiej pionowo
masa netto	21 g
Zezwolenia Certyfikaty	
General Product Approval	



[Confirmation](#)



other

Environment

[Confirmation](#)

[Miscellaneous](#)

[Environmental Con-  
firmations](#)

[Environmental Con-  
firmations](#)

### Więcej informacji

Informacje dotyczące opakowania

[Informacje dotyczące opakowania](#)

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC1401>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/pl/ps/3NC1401>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=3NC1401](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=3NC1401)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



Ostatnia zmiana:

11.03.2024 

