

Siemens
EcoTech



SITOP PSU6200/1AC/24VDC/5A

SITOP PSU6200 24 V/5 A stabilized power supply input: 120 - 240 V AC (120 - 240 V DC) output: 24 V DC/5 A



input	
type of the power supply network	1-phase AC or DC
supply voltage at AC	
• minimum rated value	120 V
• maximum rated value	240 V
• initial value	85 V
• full-scale value	264 V
supply voltage at DC	120 ... 240 V
input voltage at DC	99 ... 275 V
wide range input	Yes
overvoltage overload capability	300 V AC for 30 s
buffering time for rated value of the output current in the event of power failure minimum	80 ms
operating condition of the mains buffering	at $V_{in} = 240 V$
line frequency	50/60 Hz
line frequency	47 ... 63 Hz
input current	
• at rated input voltage 120 V	1.9 A
• at rated input voltage 240 V	1.1 A
current limitation of inrush current at 25 °C maximum	29 A
fuse protection type	3.15 A
fuse protection type in the feeder	Circuit breaker 4 A characteristic C or 6 A characteristic B/C or circuit breaker 3RV2011-1EA10 (setting 4 A) or 3RV2711-1ED10 (UL 489)
output	
voltage curve at output	Controlled, isolated DC voltage
number of outputs	1
output voltage at DC rated value	24 V
output voltage	
• at output 1 at DC rated value	24 V
output voltage adjustable	Yes; via potentiometer
adjustable output voltage	24 ... 28 V; max. 120 W (144 W up to 45°C)
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
• on slow fluctuation of input voltage	0.1 %
• on slow fluctuation of ohm loading	0.2 %
residual ripple	
• maximum	30 mV

<ul style="list-style-type: none"> • typical 	20 mV
voltage peak	
<ul style="list-style-type: none"> • maximum 	100 mV
<ul style="list-style-type: none"> • typical 	60 mV
display version for normal operation	Green LED for 24 V OK
type of signal at output	Electronic contact (NO contact, contact rating 30 V DC/0.1 A) for DC O.K.
behavior of the output voltage when switching on	Overshoot of $V_{out} < 2\%$
response delay maximum	0.5 s
voltage increase time of the output voltage	
<ul style="list-style-type: none"> • typical 	100 ms
output current	
<ul style="list-style-type: none"> • rated value 	5 A
<ul style="list-style-type: none"> • rated range 	0 ... 5 A; 6 A up to +45°C; +60 ... +70 °C: Derating 3%/K
supplied active power typical	120 W
short-term overload current	
<ul style="list-style-type: none"> • on short-circuiting during the start-up typical 	6 A
<ul style="list-style-type: none"> • at short-circuit during operation typical 	6 A
bridging of equipment	No
efficiency	
efficiency in percent	90.2 %
power loss [W]	
<ul style="list-style-type: none"> • at rated output voltage for rated value of the output current typical 	13 W
<ul style="list-style-type: none"> • during no-load operation maximum 	2 W
closed-loop control	
relative control precision of the output voltage at load step of resistive load 10/90/10 % typical	2 %
setting time	
<ul style="list-style-type: none"> • load step 10 to 90% typical 	1 ms
<ul style="list-style-type: none"> • load step 90 to 10% typical 	1 ms
<ul style="list-style-type: none"> • maximum 	2 ms
protection and monitoring	
design of the overvoltage protection	< 32 V
property of the output short-circuit proof	Yes
design of short-circuit protection	Shutdown and periodic restart attempts
<ul style="list-style-type: none"> • typical 	6 A
overcurrent overload capability	
<ul style="list-style-type: none"> • in normal operation 	overload capability 150 % I_{out} rated up to 5 s/min
safety	
galvanic isolation between input and output	Yes
galvanic isolation	ES1 output voltage V_{out} according to EN 62368-1
operating resource protection class	Class I
leakage current	
<ul style="list-style-type: none"> • maximum 	3.5 mA
protection class IP	IP20
EMC	
standard	
<ul style="list-style-type: none"> • for emitted interference 	EN 55022 Class B
<ul style="list-style-type: none"> • for mains harmonics limitation 	EN 61000-3-2
<ul style="list-style-type: none"> • for interference immunity 	EN 61000-6-2
standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> • CE marking 	Yes
<ul style="list-style-type: none"> • UL approval 	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
<ul style="list-style-type: none"> • CSA approval 	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
<ul style="list-style-type: none"> • UKCA marking 	Yes
<ul style="list-style-type: none"> • EAC approval 	Yes
<ul style="list-style-type: none"> • Regulatory Compliance Mark (RCM) 	Yes
<ul style="list-style-type: none"> • NEC Class 2 	No

<ul style="list-style-type: none"> SEMI F47 	Yes
type of certification	
<ul style="list-style-type: none"> BIS 	Yes; R-41188271
<ul style="list-style-type: none"> CB-certificate 	Yes
standards, specifications, approvals hazardous environments	
certificate of suitability	
<ul style="list-style-type: none"> IECEX 	No
<ul style="list-style-type: none"> ATEX 	No
<ul style="list-style-type: none"> ULhazloc approval 	No
<ul style="list-style-type: none"> cCSAus, Class 1, Division 2 	No
<ul style="list-style-type: none"> FM registration 	No
standards, specifications, approvals marine classification	
shipbuilding approval	Yes
Marine classification association	
<ul style="list-style-type: none"> American Bureau of Shipping Europe Ltd. (ABS) 	Yes
<ul style="list-style-type: none"> French marine classification society (BV) 	No
<ul style="list-style-type: none"> Det Norske Veritas (DNV) 	Yes
<ul style="list-style-type: none"> Lloyds Register of Shipping (LRS) 	No
standards, specifications, approvals Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
<ul style="list-style-type: none"> total 	420.3 kg
<ul style="list-style-type: none"> during manufacturing 	13.1 kg
<ul style="list-style-type: none"> during operation 	406.8 kg
<ul style="list-style-type: none"> after end of life 	0.33 kg
Siemens Eco Profile (SEP)	Siemens EcoTech
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation 	-30 ... +70; with natural convection a monotonically increasing start-up from -25 °C, safe start-up from -40 °C
<ul style="list-style-type: none"> during transport 	-40 ... +85
<ul style="list-style-type: none"> during storage 	-40 ... +85
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
connection method	
type of electrical connection	push-in terminals
<ul style="list-style-type: none"> at input 	L1/+, L2/N/-, PE: push-in for 0.5 ... 4 mm ² single-core/finely stranded
<ul style="list-style-type: none"> at output 	+1, +2, -1, -2, -3: push-in for 0.5 ... 2.5 mm ²
<ul style="list-style-type: none"> for auxiliary contacts 	13, 14 (alarm signal): 1 push-in terminal each for 0.2 ... 1.5 mm ²
mechanical data	
width × height × depth of the enclosure	35 × 135 × 125 mm
installation width × mounting height	35 mm × 225 mm
required spacing	
<ul style="list-style-type: none"> top 	45 mm
<ul style="list-style-type: none"> bottom 	45 mm
<ul style="list-style-type: none"> left 	0 mm
<ul style="list-style-type: none"> right 	0 mm
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
<ul style="list-style-type: none"> DIN-rail mounting 	Yes
<ul style="list-style-type: none"> S7 rail mounting 	No
<ul style="list-style-type: none"> wall mounting 	No
housing can be lined up	Yes
net weight	0.7 kg
accessories	
electrical accessories	Buffer module, redundancy module
mechanical accessories	Identification labels SIMATIC ET 200SP 6ES7193-6LF30-0AW0
further information internet links	
internet link	
<ul style="list-style-type: none"> to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool 	https://www.siemens.com/tstcloud
<ul style="list-style-type: none"> to web page: power supplies 	https://siemens.com/sitop

- to website: CAx-Download-Manager
- to website: Industry Online Support

<https://siemens.com/cax>
<https://support.industry.siemens.com>

identification link Yes; acc. to IEC 61406-1:2022

additional information

other information Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

security information

security information Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Classifications

	Version	Classification
eClass	14	27-04-07-01
eClass	12	27-04-07-01
eClass	9.1	27-04-07-01
eClass	9	27-04-07-01
eClass	8	27-04-90-02
eClass	7.1	27-04-90-02
eClass	6	27-04-90-02
ETIM	9	EC002540
ETIM	8	EC002540
ETIM	7	EC002540
IDEA	4	4130
UNSPSC	15	39-12-10-04

Approvals Certificates

General Product Approval



[Manufacturer Declaration](#)

[Declaration of Conformity](#)



General Product Approval

Marine / Shipping

Environment



[BIS CRS](#)



last modified:

12/23/2024