

Siemens
EcoTech



SITOP PSU4200/3AC/24VDC/10A

SITOP PSU4200 3AC 24 V/10 A stabilized power supply PSU4200 input: 400/500 V AC output: 24 V DC/ 10 A



input	
type of the power supply network	3-phase AC
supply voltage at AC	
<ul style="list-style-type: none"> • minimum rated value • maximum rated value • initial value • full-scale value 	400 V 500 V 320 V 550 V
wide range input	Yes
buffering time for rated value of the output current in the event of power failure minimum	5 ms
operating condition of the mains buffering	at $V_{in} = 400/500\text{ V}$
line frequency	50/60 Hz
line frequency	47 ... 63 Hz
input current	
<ul style="list-style-type: none"> • at rated input voltage 400 V • at rated input voltage 500 V 	0.7 A 0.6 A
current limitation of inrush current at 25 °C maximum	50 A
duration of inrush current limiting at 25 °C	
<ul style="list-style-type: none"> • typical 	20 ms
I ² t value maximum	0.9 A ² ·s
fuse protection type in the feeder	three-poled coupled circuit breaker from 3 A characteristic C to 16 A characteristic C or circuit breaker 3RV2011-1EA10 (setting 3 A) or 3RV2711-1ED10 (UL 489)
output	
voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	24 V
output voltage	
<ul style="list-style-type: none"> • at output 1 at DC rated value 	24 V
output voltage adjustable	Yes; via potentiometer
adjustable output voltage	24 ... 28 V
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
<ul style="list-style-type: none"> • on slow fluctuation of input voltage • on slow fluctuation of ohm loading 	0.2 % 0.3 %
residual ripple	
<ul style="list-style-type: none"> • maximum • typical 	150 mV 48 mV
voltage peak	

<ul style="list-style-type: none"> • maximum 	240 mV
<ul style="list-style-type: none"> • typical 	30 mV
display version for normal operation	Green LED for 24 V OK
type of signal at output	Signal contact (signal load capacity: 5 mA) for DC OK
behavior of the output voltage when switching on	No overshoot of Vout (soft start)
response delay maximum	1.5 s
voltage increase time of the output voltage	
<ul style="list-style-type: none"> • typical 	210 ms
<ul style="list-style-type: none"> • maximum 	500 ms
output current	
<ul style="list-style-type: none"> • rated value 	10 A
<ul style="list-style-type: none"> • rated range 	0 ... 10 A; +60 ... +70 °C: Derating 3%/K
supplied active power typical	240 W
bridging of equipment	Yes
number of parallel-switched equipment resources for increasing the power	2
efficiency	
efficiency in percent	90 %
power loss [W]	
<ul style="list-style-type: none"> • at rated output voltage for rated value of the output current typical 	27 W
<ul style="list-style-type: none"> • during no-load operation maximum 	3 W
closed-loop control	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	0.2 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	0.5 %
relative control precision of the output voltage at load step of resistive load 10/90/10 % typical	1.5 %
setting time	
<ul style="list-style-type: none"> • load step 10 to 90% typical 	1 ms
<ul style="list-style-type: none"> • load step 90 to 10% typical 	1 ms
protection and monitoring	
design of the overvoltage protection	< 32 V
property of the output short-circuit proof	Yes
design of short-circuit protection	Constant current characteristic
<ul style="list-style-type: none"> • typical 	12.2 A
enduring short circuit current RMS value	
<ul style="list-style-type: none"> • typical 	12.5 A
safety	
galvanic isolation between input and output	Yes
galvanic isolation	ES1 output voltage Vout according to EN 62368-1 (Safety extra low output voltage Vout according to EN 60950-1)
operating resource protection class	Class I
leakage current	
<ul style="list-style-type: none"> • maximum 	0.8 mA
<ul style="list-style-type: none"> • typical 	0.4 mA
protection class IP	IP20
EMC	
standard	
<ul style="list-style-type: none"> • for emitted interference 	EN 55032 Class A
<ul style="list-style-type: none"> • for mains harmonics limitation 	EN 61000-3-2
<ul style="list-style-type: none"> • for interference immunity 	EN 61000-6-2
standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> • CE marking 	Yes
<ul style="list-style-type: none"> • UL approval 	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (UL 62368-1, CSA C22.2 No. 62368-1-19)
<ul style="list-style-type: none"> • CSA approval 	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (UL 62368-1, CSA C22.2 No. 62368-1-19)
<ul style="list-style-type: none"> • UKCA marking 	Yes
<ul style="list-style-type: none"> • EAC approval 	Yes

<ul style="list-style-type: none"> ● Regulatory Compliance Mark (RCM) ● NEC Class 2 	<p>Yes</p> <p>No</p>
type of certification	
<ul style="list-style-type: none"> ● BIS ● CB-certificate 	<p>Yes; R-41183539</p> <p>Yes</p>
MTBF at 40 °C	1 330 000 h
standards, specifications, approvals hazardous environments	
certificate of suitability	
<ul style="list-style-type: none"> ● IECEx ● ATEX ● ULhazloc approval ● cCSAus, Class 1, Division 2 ● FM registration 	<p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p>
standards, specifications, approvals marine classification	
shipbuilding approval	No
Marine classification association	
<ul style="list-style-type: none"> ● American Bureau of Shipping Europe Ltd. (ABS) ● French marine classification society (BV) ● Det Norske Veritas (DNV) ● Lloyds Register of Shipping (LRS) 	<p>No</p> <p>No</p> <p>No</p> <p>No</p>
standards, specifications, approvals Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
<ul style="list-style-type: none"> ● total ● during manufacturing ● during operation ● after end of life 	<p>702 kg</p> <p>20.7 kg</p> <p>680.6 kg</p> <p>0.57 kg</p>
Siemens Eco Profile (SEP)	Siemens EcoTech
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> ● during operation ● during transport ● during storage 	<p>-25 ... +70; with natural convection</p> <p>-40 ... +85</p> <p>-40 ... +85</p>
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
connection method	
type of electrical connection	push-in terminals
<ul style="list-style-type: none"> ● at input ● at output ● for signaling contact 	<p>L1, L2, L3, PE: push-in for 0.5 ... 4 mm²</p> <p>+, -: push-in for 0.5 ... 2.5 mm²</p> <p>13, 14: push-in for 0.2 ... 1.5 mm²</p>
mechanical data	
width × height × depth of the enclosure	70 × 135 × 125 mm
installation width × mounting height	70 mm × 225 mm
required spacing	
<ul style="list-style-type: none"> ● top ● bottom ● left ● right 	<p>45 mm</p> <p>45 mm</p> <p>0 mm</p> <p>0 mm</p>
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
<ul style="list-style-type: none"> ● DIN-rail mounting ● S7 rail mounting ● wall mounting 	<p>Yes</p> <p>No</p> <p>Yes</p>
housing can be lined up	Yes
net weight	0.64 kg
further information internet links	
internet link	
<ul style="list-style-type: none"> ● to website: Industry Mall ● to web page: selection aid TIA Selection Tool ● to web page: power supplies ● to website: CAx-Download-Manager ● to website: Industry Online Support 	<p>https://mall.industry.siemens.com</p> <p>https://www.siemens.com/tstcloud</p> <p>https://siemens.com/sitop</p> <p>https://siemens.com/cax</p> <p>https://support.industry.siemens.com</p>

additional information

other information

Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

security information

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Classifications

	Version	Classification
eClass	14	27-04-07-01
eClass	12	27-04-07-01
eClass	9.1	27-04-07-01
eClass	9	27-04-07-01
eClass	8	27-04-90-02
eClass	7.1	27-04-90-02
eClass	6	27-04-90-02
ETIM	9	EC002540
ETIM	8	EC002540
ETIM	7	EC002540
IDEA	4	4130
UNSPSC	15	39-12-10-04

Approvals Certificates

General Product Approval



[Manufacturer Declaration](#)



[BIS CRS](#)

Environment



Siemens EcoTech



last modified:

2/16/2025