## SIEMENS

## Data sheet

product type designation

## 6GT2831-6BA60-0AX0

	Mifare, ISO15693 L -25 to +55 °C 90x62 cable company logo
SIEMENS SIMATIC RF1070R	

## Reader RF1070R OEM USB/RS232

SIMATIC RF1000 Access control reader RF1070R OEM variant ISO 14443 A/B Mifare, ISO15693 Legic Prime, Legic Advant USB port RS232 interface IP65 front, -25 to +55 °C 90x62x25 mm LxWxH with integrated antenna including 1.8 m USB cable company logo enclosed.

redie fregueseie

Legic, ISO 15693 and ISO 14443 A/B transponder, for connecting to PC and control systems, for front panels with customer-specific design

radio frequencies	
operating frequency / rated value	13.56 MHz
range / maximum	0.03 m; Range is dependent on transponder type: observe http://support.automation.siemens.com/WW/view/en/67384964
protocol / with radio transmission	Legic Prime, Legic Advant, ISO 15693, ISO 14443 A/B, chip set: SM4200M, Felica, NXP NTAG21x, HID iClass
transfer rate / with radio transmission / maximum	106 kbit/s
product feature / multitag-capable	Yes
electrical data	
transfer rate / at the point-to-point connection / serial / maximum	115.2 kbit/s
interfaces	
standard for interfaces / for communication	USB 2.0, RS232
type of electrical connection	1.8 m connecting cable with USB 2.0 type A connector or RS232 connecting cable
mechanical data	
material	PC-GF
color	titanium gray
mounting distance / relating to metal surfaces / recommended / minimum	0 mm
supply voltage, current consumption, power loss	
supply voltage / at DC	
<ul> <li>rated value</li> </ul>	5 V
•	4.6 5.25 V
consumed current / at DC	
• at 5 V / typical	0.15 A
• at 5 V / maximum	0.3 A
ambient conditions	
ambient temperature	
during operation	-25 +55 °C
during storage	-25 +55 °C
during transport	-25 +55 °C
protection class IP	IP65; on front after professional gluing of the included front label and cabinet installation, IP20 rear
shock resistance	EN 60721-3-7 Class 7 M2
shock acceleration	300 m/s²
vibrational acceleration	50 m/s²
design, dimensions and weights	
width	90 mm
height	62 mm

danth	00.5 mm	
depth	23.5 mm	
net weight	0.12 kg	
fastening method	4 M4 screws for cabinet installation	
product features, product functions, product components / ge		
display version	3-color LED	
product feature / silicon-free	Yes	
standards, specifications, approvals		
certificate of suitability	Radio according to R&TTE guidelines EN300 330 and EN 301489, FCC, cULus	
certificate of suitability		
• IECEx	No	
reference code		
<ul> <li>according to IEC 81346-2:2019</li> </ul>	BYB	
accessories		
accessories	Card holder, USB cable 0.5 m, RS232 connection cable, front label in customer design to be created by the customer, HID license card, BLE license card, cleanroom cover, desktop housing	
further information / internet links		
internet link		
<ul> <li>to web page: selection aid TIA Selection Tool</li> </ul>	https://www.siemens.com/tstcloud	
• to web page: RFID country approval	https://www.siemens.com/rfid-approvals	
<ul> <li>to web page: identification and localization systems</li> </ul>	https://www.siemens.com/ident	
to web page: SiePortal	https://sieportal.siemens.com/	
to website: Image database	https://www.automation.siemens.com/bilddb	
to website: Mage database     to website: CAx-Download-Manager	https://www.automation.stemens.com/bilddb	
to website: OrX-Download-Manager     to website: Industry Online Support	https://support.industry.siemens.com	
security information	парелюцироналицион узослютово. сонт	
security information	Siemens provides products and solutions with industrial cybersecurity functions	
	necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under	
Approvals / Certificates	https://www.siemens.com/cert. (V4.7)	
General Product Approval	Radio Equipment Type Approval Certificate	
	-	
IECEX CE UK IECEX EG-Konf.	Lindustry Canada (IC) Miscellaneous	
Radio Equipment Type Approval Certificate		
Miscellaneous FCC		
last modified:	12/17/2024 🖸	