





SETRON, uchwyt bezpiecznika cylindrycznego, 22x58 mm, 3 fazy+N, In: 100 A, Un AC: 690 V, sygnalizator LED



Wersja		
Nazwa markowa produktu	SETRON	
oznaczenie produktu	Uchwyt bezpiecznika cylindrycznego	
wykonanie produktu	Sygnalizator LED	
Ogólne dane techniczne		
liczba biegunów	4	
wersja biegunów	3 faz. + N	
wielkość wkładki bezpiecznikowej	22x58 mm	
Napięcie zasilania		
napięcie robocze	690 V	
• przy AC wartość znamionowa		
Stopień ochrony IP	IP20	
Konstrukcja mechaniczna		
wysokość	117 mm	
szerokość	144 mm	
głębokość	70 mm	
masa netto	686 g	
Certyfikaty		
oznaczenie środków roboczych zgodnie z IEC 81346-2:2009	F	
Zezwolenia Certyfikaty		
General Product Approval	Test Certificates	other
	 EG-Konf.	
<a href="#">Confirmation</a>	<a href="#">Miscellaneous</a>	<a href="#">Miscellaneous</a>
other	Environment	
<a href="#">Confirmation</a>	<a href="#">Environmental Confirmations</a>	

### Więcej informacji

Informacje dotyczące opakowania

[Informacje dotyczące opakowania](#)

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mifb=3NW7262>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.industry.siemens.com/cs/ww/pl/ps/3NW7262>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)



[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NW7262](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NW7262)


CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





Ostatnia zmiana:

26.02.2025 [↗](#)

