



SIMATIC DP, Electronic modules for ET 200 PRO 4 DI/4 DO 24 V DC, 0.5A  
Module diagnostics; incl. bus module, Connection module IO 6ES7194-4..00-0AA0  
order separately

Supply voltage	
Load voltage 2L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>Short-circuit protection</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Reverse polarity protection</li> </ul>	Yes
Input current	
from load voltage 2L+ (without load), max.	20 mA
from backplane bus 3.3 V DC, max.	20 mA
Encoder supply	
Short-circuit protection	Yes; per module, electronic
Output current	
<ul style="list-style-type: none"> <li>up to 55 °C, max.</li> </ul>	1 A
Power loss	
Power loss, typ.	2 W
Digital inputs	
Number of digital inputs	4
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Input voltage	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>for signal "0"</li> </ul>	-3 to +5V
<ul style="list-style-type: none"> <li>for signal "1"</li> </ul>	+11 to +30V
Input current	
<ul style="list-style-type: none"> <li>for signal "1", typ.</li> </ul>	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
<ul style="list-style-type: none"> <li>at "0" to "1", max.</li> </ul>	3 ms
<ul style="list-style-type: none"> <li>at "1" to "0", max.</li> </ul>	3 ms
Cable length	
<ul style="list-style-type: none"> <li>unshielded, max.</li> </ul>	30 m
Digital outputs	
Number of digital outputs	4
output characteristic acc. to IEC 61131, type 0.5	Yes
Short-circuit protection	Yes; per channel, electronic
<ul style="list-style-type: none"> <li>Response threshold, typ.</li> </ul>	0.7 A
Limitation of inductive shutdown voltage to	Typ. (2L+) -47 V
Controlling a digital input	Yes
Switching capacity of the outputs	
<ul style="list-style-type: none"> <li>on lamp load, max.</li> </ul>	5 W
Load resistance range	
<ul style="list-style-type: none"> <li>lower limit</li> </ul>	48 Ω

• upper limit	4 kΩ	
<b>Output voltage</b>		
• for signal "1", min.	2L+ (-0,8 V)	
<b>Output current</b>		
• for signal "1" rated value	0.5 A	
• for signal "0" residual current, max.	0.5 mA	
<b>Parallel switching of two outputs</b>		
• for uprating	No	
• for redundant control of a load	Yes	
<b>Switching frequency</b>		
• with resistive load, max.	100 Hz	
• with inductive load, max.	0.5 Hz	
• on lamp load, max.	1 Hz	
<b>Total current of the outputs (per group)</b>		
all mounting positions		
— up to 55 °C, max.	2 A	
<b>Cable length</b>		
• unshielded, max.	30 m	
<b>Encoder</b>		
<b>Connectable encoders</b>		
• 2-wire sensor	Yes	
— permissible quiescent current (2-wire sensor), max.	1.5 mA	
<b>Interrupts/diagnostics/status information</b>		
Diagnostics function	Yes	
<b>Alarms</b>		
• Diagnostic alarm	Yes	
<b>Diagnoses</b>		
• Diagnostic information readable	Yes	
• Short-circuit	Yes; Short-circuit of outputs to ground; module by module	
<b>Diagnostics indication LED</b>		
• Status indicator digital input (green)	Yes	
• Status indicator digital output (green)	Yes	
<b>Potential separation</b>		
between backplane bus and all other circuit components	Yes	
<b>Potential separation digital inputs</b>		
• between the channels	No	
• between the channels and backplane bus	Yes	
<b>Potential separation digital outputs</b>		
• between the channels	No	
• between the channels and backplane bus	Yes	
<b>Isolation</b>		
Isolation tested with	707 V DC (type test)	
<b>Dimensions</b>		
Width	45 mm	
Height	130 mm	
Depth	35 mm	
<b>Weights</b>		
Weight, approx.	140 g	
<b>Classifications</b>		
	<b>Version</b>	<b>Classification</b>
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	9	EC001599

ETIM	8	EC001599
ETIM	7	EC001599
IDEA	4	3566
UNSPSC	15	32-15-17-05

**Approvals / Certificates**

**General Product Approval**

[Manufacturer Declaration](#)



[KC](#)

**Marine / Shipping**



[NK / Nippon Kaiji Kyokai](#)



**Marine / Shipping**

[CCS \(China Classification Society\)](#)



last modified:

11/22/2024