



SIMATIC DP, Power module for Electronic modules ET 200 PRO PM-E, 24 V DC, incl. bus module, connection module PM-E 6ES7194-4B.00-0AA0 order separately

Supply voltage			
Load voltage 2L+			
<ul style="list-style-type: none"> Rated value (DC) Short-circuit protection Reverse polarity protection 	24 V Yes; via an exchangeable fuse in the power module Yes; against destruction		
Input current			
from load voltage 2L+, max.	3 mA		
Current carrying capacity			
max.	10 A; up to 55 °C (on the internal busbars of the ET 200pro)		
Power loss			
Power loss, typ.	0.1 W		
Interrupts/diagnostics/status information			
Diagnostics function	Yes		
Diagnoses			
<ul style="list-style-type: none"> Diagnostic information readable missing load voltage 	Yes Yes		
Diagnostics indication LED			
<ul style="list-style-type: none"> For load voltage monitoring Group error SF (red) 	Yes Yes		
Parameter			
missing load voltage	Potential group of the power module		
Potential separation			
between load voltage and backplane bus	Yes		
Isolation			
Isolation tested with	707 V DC (type test)		
Degree and class of protection			
IP degree of protection	IP65/67		
Dimensions			
Width	45 mm		
Height	130 mm		
Depth	35 mm		
Weights			
Weight, approx.	140 g		
Classifications			
		Version	Classification
	eClass	14	27-24-26-11
	eClass	12	27-24-26-11
	eClass	9.1	27-24-26-11

eClass	9	27-24-26-11
eClass	8	27-24-26-11
eClass	7.1	27-24-26-11
eClass	6	27-24-26-11
ETIM	9	EC002583
ETIM	8	EC002583
ETIM	7	EC002583
IDEA	4	3575
UNSPSC	15	32-15-17-06

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)



[KC](#)

Marine / Shipping



[NK / Nippon Kaiji Kyokai](#)



Marine / Shipping

[CCS \(China Classification Society\)](#)



last modified:

3/12/2024