



SIMATIC DP, POWER M. F-PM-E PPM PROFIsafe, for ET 200SP; 24 V DC safe shutdown of DQ and F-DQ up to PL D/SIL2 or PL E/SIL3 2 for safe dig. inputs 1 for safe dig. output PPM

General information	
Product type designation	F-PM-E 24 V DC/8 A PPM ST
usable BaseUnits	BU type C0
Color code for module-specific color identification plate	CC52
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V12
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	V5.5 SP3 / -
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	V2.31
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	75 mA; without load
Current consumption, max.	21 mA; From the backplane bus
output voltage / header	
Rated value (DC)	24 V
Encoder supply	
Number of outputs	2
Short-circuit protection	Yes; Electronic (response threshold 0.7 A to 2.1 A)
Output current	
<ul style="list-style-type: none"> <li>up to 60 °C, max.</li> </ul>	0.3 A
24 V encoder supply	
<ul style="list-style-type: none"> <li>24 V</li> </ul>	Yes; min. L+ (-1.5 V)
<ul style="list-style-type: none"> <li>Short-circuit protection</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Output current, max.</li> </ul>	600 mA; Total current of all encoders
Power	
Power consumption from the backplane bus	70 mW
Power loss	
Power loss, typ.	5 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Inputs</li> </ul>	7 byte
<ul style="list-style-type: none"> <li>Outputs</li> </ul>	5 byte
Hardware configuration	
Automatic encoding	Yes
<ul style="list-style-type: none"> <li>Electronic coding element type F</li> </ul>	Yes

Digital inputs	
Number of digital inputs	2
Source/sink input	Yes; P-reading
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input voltage	
<ul style="list-style-type: none"> <li>Type of input voltage</li> </ul>	DC
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>for signal "0"</li> </ul>	-30 to +5 V
<ul style="list-style-type: none"> <li>for signal "1"</li> </ul>	+15 to +30 V
Input current	
<ul style="list-style-type: none"> <li>for signal "1", typ.</li> </ul>	3.7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes
— at "0" to "1", min.	0.4 ms
— at "0" to "1", max.	20 ms
— at "1" to "0", min.	0.4 ms
— at "1" to "0", max.	20 ms
for technological functions	
— parameterizable	No
Cable length	
<ul style="list-style-type: none"> <li>shielded, max.</li> </ul>	1 000 m
<ul style="list-style-type: none"> <li>unshielded, max.</li> </ul>	500 m
Digital outputs	
Number of digital outputs	1
Short-circuit protection	Yes
<ul style="list-style-type: none"> <li>Response threshold, typ.</li> </ul>	> 14.8 A
Open-circuit detection	Yes
<ul style="list-style-type: none"> <li>Response threshold, typ.</li> </ul>	8 mA
Overload protection	Yes
<ul style="list-style-type: none"> <li>Response threshold, typ.</li> </ul>	8.8 A
Limitation of inductive shutdown voltage to	Max. -1.5 V
Switching capacity of the outputs	
<ul style="list-style-type: none"> <li>with resistive load, max.</li> </ul>	8 A
<ul style="list-style-type: none"> <li>on lamp load, max.</li> </ul>	100 W
Load resistance range	
<ul style="list-style-type: none"> <li>lower limit</li> </ul>	3 Ω
<ul style="list-style-type: none"> <li>upper limit</li> </ul>	2 000 Ω
Output voltage	
<ul style="list-style-type: none"> <li>for signal "1", min.</li> </ul>	24 V; L+ (-0.5 V)
Output current	
<ul style="list-style-type: none"> <li>for signal "1" rated value</li> </ul>	8 A
<ul style="list-style-type: none"> <li>for signal "0" residual current, max.</li> </ul>	1.5 mA; PP-switching: max. 1.5 mA; PM-switching: max. 1 mA
Switching frequency	
<ul style="list-style-type: none"> <li>with resistive load, max.</li> </ul>	10 Hz; Symmetrical
<ul style="list-style-type: none"> <li>with inductive load, max.</li> </ul>	0.1 Hz; according to IEC 60947-5-1, DC-13, symmetrical
<ul style="list-style-type: none"> <li>on lamp load, max.</li> </ul>	4 Hz; Symmetrical
Total current of the outputs	
<ul style="list-style-type: none"> <li>Current per channel, max.</li> </ul>	8 A; note derating data in the manual
<ul style="list-style-type: none"> <li>Current per module, max.</li> </ul>	8 A; note derating data in the manual
Cable length	
<ul style="list-style-type: none"> <li>shielded, max.</li> </ul>	1 000 m
<ul style="list-style-type: none"> <li>unshielded, max.</li> </ul>	500 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes; See Chapter "Alarms/diagnostic messages" in the manual
Substitute values connectable	No
Alarms	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Hardware interrupt</li> </ul>	No
Diagnostics indication LED	

- RUN LED Yes; green LED
- ERROR LED Yes; red LED
- Monitoring of the supply voltage (PWR-LED) Yes; green PWR LED
- Channel status display Yes; green LED
- for channel diagnostics Yes; red LED
- for module diagnostics Yes; green/red DIAG LED

#### Potential separation

Potential separation channels	
• between the channels	No
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	No

#### Isolation

Isolation tested with	707 V DC (type test)
-----------------------	----------------------

#### Standards, approvals, certificates

Suitable for safety functions	Yes
-------------------------------	-----

#### Ecological footprint

• environmental product declaration	Yes
-------------------------------------	-----

#### Global warming potential

— global warming potential, (total) [CO2 eq]	88.3 kg
— global warming potential, (during production) [CO2 eq]	13.1 kg
— global warming potential, (during operation) [CO2 eq]	76.6 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-1.37 kg

#### Highest safety class achievable in safety mode

• Performance level according to ISO 13849-1	PLe
• SIL acc. to IEC 61508	SIL 3

#### Ambient conditions

Ambient temperature during operation	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	50 °C

#### Dimensions

Width	20 mm
Height	73 mm
Depth	58 mm

#### Weights

Weight, approx.	70 g
-----------------	------

#### Classifications

	Version	Classification
eClass	14	27-24-26-11
eClass	12	27-24-26-11
eClass	9.1	27-24-26-11
eClass	9	27-24-26-11
eClass	8	27-24-26-11
eClass	7.1	27-24-26-11
eClass	6	27-24-26-11
ETIM	9	EC002583
ETIM	8	EC002583
ETIM	7	EC002583
IDEA	4	3575
UNSPSC	15	32-15-17-06

#### Approvals / Certificates

General Product Approval	For use in hazardous locations
--------------------------	--------------------------------

[Manufacturer Declaration](#)



For use in hazardous locations

Functional Safety

[EM](#)

[CCC-Ex](#)



[Miscellaneous](#)



Functional Safety

Marine / Shipping

[Type Examination Certificate](#)



[NK / Nippon Kaiji Kyokai](#)

Marine / Shipping

Industrial Communication



[CCS \(China Classification Society\)](#)



[PROFIsafe](#)

last modified:

10/9/2024